August 1959 - 35 cents

MODEL IRPLANI NEWS

IN THIS ISSUE

Delta Jet Glider Low Wing RC

ALSO . . . Aeronca Tri-Traveler Flying Model, Lauderdale's Dizzy Bee

G TIGERS-BIG AND LITTLE



RADIO CONTROL TRAINER MAMBO. designed and engineered for radio control.



CONTROL LINE Ideal for Beginners. PROFILE TRAINER II

Guillow's



SPORT FREE

FLIGHT FAIRCHILD PT-19 may also be flown as Control Line Model, as well as Radio Control



COMBAT FLYERS, the FLITE STREAK, JR. is supermaneuverable.





The 1/2A SUPER STUNTMASTER is a real tiger with Fox 15 power.

by SCHENTIFIC

SMART CHAMPIONS CHOOSE







FREE FLIGHT . . . Get up there fast with a RAMROD 600.

Berkeley



Brand new RC Trainer the EXPLORER-Rudder only. intermediate or Guillow's

multi-channel.



SCALE FANS . . . Try this new super Combat-stunt HAWKER TYPHOON.



RIGHT PRICE



For the Combat Keen flyer, the LANCER is the answer.

by Berkeley

R C FANS **ROTO VALVE Provides** Speed Control



Kits shown are recommended by their manufacturers for use with the Fox 15. Both kits and Fox Motors are available from your Favorite Hobby Shop.

FOX MANUFACTURING CO., Inc.

Designers and Manufacturers of the World's Finest Model Airplane Motors

5305 TOWSON AVENUE, FORT SMITH, ARKANSAS









FUEL PUMP and FUELER

FROM PERFECT

You can now fuel your flying models easily and accurately...the "professional" way. Available only from PERFECT, a plunger type fuel pump and an all new bulb fueler with the exclusive features demanded by all model flying hobbyists. Both of these items . filter your fuel automatically . fit into any tank · measure fuel accurately · empty fuel cans completely • are easy to handle • are corrosion proof • and will give you years of trouble-free, dependable service. Get yours today from your favorite hobby dealer.

PERFECT FUELER

* EXCLUSIVE FEATURES

- * Transparent Polyethelene Bulb
- * Built-In Fuel Filter
- ★ Nozzle Fits Into Tank
- ★ Graduated To Measure Fuel
- * Telescoping Tube Empties Can
- * Fits Pocket Conveniently





PERFECT) FUEL PUMP

* EXCLUSIVE FEATURES

- * Flexible Gas Line
- * Built-in Fuel Filter
- * Nozzle Fits Into Tank
- * Measures Fuel per Stroke
- ★ Adjustable Tube Empties Can
- * Spout Swivels to Any Position

For Perfect Performance Use Only Guaranteed

(PERFECT) Products



Foreign

P. G. F. CHINN

As is now generally known, no country has volunteered to run the Free-Flight Gas World Championships this year, so there will be no contest. It is clear, despite all the FAI discussions on who should be entitled to run World Championship events and where, that the present situation is just not good enough. It is hoped that some workable system will be devised at the next annual meeting of the FAI Model Commission and that all the delegates will be in a position to say, definitely, whether or not, their countries can be relied upon to take their turns in organizing these

The other two free-flight contests for this The other two free-flight contests for this year, Wakefield and A2 Glider, will be held, respectively, in France and Belgium. The former will be at the American airfield at Brienne-le-Chateau, July 18-20 and the A2 will be at Reustem, August 23.

In addition, the big R/C event for the King of the Belgians Cup, will be at Hirzenhain, Germany, on September 19 and 20. This will be flown to the new FAI radio-control rules. These rules are divided

20. This will be nown to the new FA.

radio-control rules. These rules are divided into four categories: single-control glider, single-control power, multi-control aerobatic glider and muti-control aerobatic power. Stunt schedule for the latter event includes wing-over, Immelmann turn, three superimposed loops, three superimposed outside loops, split-S, roll, roll in opposite direction, stall, inverted flight, left and right circle while inverted, horizontal eight, Cuban eight, vertical eight, and up to three turns of a spin.

FAI rule changes include a new requirement in regard to towline pennant size, which is now increased from 1.5 sq. dm. to 2.5 sq. dm. (38.75 sq. in.). The exchange of engines between contestants is now prohibited. Although this situation seldom crises it will for example, proven them. arises, it will, for example, prevent team use of one especially hot racing motor in several speed models.

GREAT BRITAIN Big changes are taking place, in the U.K. model market, which are bound to effect British modeling habits. These changes are a result of the long-awaited relaxing of import restrictions and, with much model merchandise now being im-ported from the U.S., Japan and, to a lesser extent, from Germany and other countries, British modelers at last have at their dis-posal almost every type of model item they could wish for.

could wish for.

There are now, for instance, as many different imported engines on the market as home-produced engines. Particularly welcome have been stunt type glow engines from the U.S. and Japan, such as Fox and Veco, O.S. and Enya. Cox's Pec-Wee, as well as the .049 models, are also proving popular and some members of the industry are predicting that Britishmade baby glow motors, on the the American pattern, will eventually take over from the small diesel as the standard beginner's engine. Hitherto, in Britain and throughout Europe, 99 percent of engine sales have been of diesels, while readymade engine powered models have been made engine powered models have been practically unknown. The production of glow-engined plastic models in England, however, is now near, and it is certain that familiarizing the (Continued on page 54)

You're always "on frequency" with a CG transmitter-receiver combo


(New CG Venus Transmitter meets new FCC specs)

Here's an entirely new, single channel, extremely stable tone transmitter that'll stay right "on frequency" through every flight you make.


Known as the Venus, this new high powered version, modeled after the famous CG T-12 transmitter, is lightweight and a dream to operate. A high precision CG crystal keeps the Venus within 0.01% of specified operating frequency - well within new FCC specs.

And it's economical to run, too! "Balanced Power" design saves battery power -gets up to a year's use from "B" batteries.

Best of all, the Venus is economy priced at only \$29.95. Get your order in early. Contact your local dealer or write direct to CG Electronics.



only \$29.95



The Receiver Without Equal -The Well Known RT1-3V

• Size: 11/2" x 21/6" x 1"

Gas here

all

enente

is is ome

del will

pon

this

be

and

the

lirind

ler,

tic

nd to

to

m

to se ed th

Ŋ

- · Weight: 2 oz. complete
- · Power: 3 volts total
- Temperature Range: Guaranteed to operate between 0°F to 130°F
- Completely transistorized
- · Factory pre-tuned







No Wiring, No Soldering, No Tuning With JUPITER COMPACT A Complete RC Unit!


- · No electrical installation
- · Weight: complete with battery and escapement, 4 oz.
- · Size: 21/2" x 3" x 21/4"
- · Power: only 3 volts required
- · Completely transistorized
- · Factory pre-tuned
- Guaranteed for 0°F to 130°F operation



Economy-Sized PIONEER Delivers Big Performance

Size: 2¾" x 1½"

- · Weight: 11/a oz.
- · Economical 3 volt operation
- · Operates standard escapements
- Temperature stabilized
- · Finest quality printed circuit construction







Ask for FREE Catalog

CG ELECTRONICS CORPORATION

Dept. B-8 · 15000 Central S. E., Albuquerque, New Mexico



JAY P. CLEVELAND, President and Publisher



Vol. LXI, No. 2

CONTENTS

CONSTRUCTION

The 1	ri-Tre	iveler
Houdi	ini	
Delta	Dart	***************************************

ARTICLES

A	Place	to	Fly		******************	1
So	uped-	Up	Pre	Fabs	*****************	1
w	ing Le	adi	ina	la Thre	e Dimensional	2

FEATURES

Foreign Notes	
MAN at Work	***************
Early Birds	
Engine Review	
Varicomp Swi	tcher 2
Radio Control	News 1
WILLIAM WIN	ITER. Editor

WITTICH HOLLOWAY, Art Director
Contributing Editors: Peter Chinn (England),
Don Grout, Ed Lorenz, Ted Martin,
Bruce Wennerstrom, Harry Williamson

Executive and Editorial Office: 351 Fifth Avenue, New York 17, N. Y. Advertising Manager, N. E. Slane, 551 5th Ave. New York 17; West Coast Adv. Mgr., Justin Hannon, 4708 Crenshaw Blvd. Los Angeles 43, Calif.

Published Monthly by Air Age, Inc. Editorial and Business Offices: 551 Fifth Ave., New York 17, N.Y. Jay P. Cleveland, President; Y. P. Johnson, Vice Pres.; Louis V. DeFrancesco, Treas.; G. E. DeFrancesco, Sec. Second Class Postage paid at Columbia, Missouri. Additional Second Class Entry at New York, N.Y.

Copyright 1959 by Air Age, Inc. Printed in U. S. A.



► Pan American's new film "Wings for Tomorrow," a 13% minute, 16mm motion picture in sound and color, contains superb footage on models (and 707's) in action. It is deftly put together. To make a poor joke, the story gets in everything but motherhood and Christmas. It explains PAA-Load flying, modeling in general, ties all this in with careers and enobling influences (ahem), plugs Pan American, follows Ken Scribner, a Pan Am pilot from a knee breeches boy to adult Clipper Captain. Any good film seems too short. This one gets organized out yonder, then pours across the course at Mach 2. We suspect many a club will run it more than once in the same evening. Man, how a little Jetex job soars and banks majestically, like a 707 waiting its shot at the approach, when followed in slow motion.

Only trouble with the preview, attended by the model eds, Dallas Sherman (the payload pappy), and George Gardner, was the fascinating twin pusher "young Scribner" flew. In a moment of madness, mutual probably, yours truly had concocted the design for Al Lewis. That the story teller had this mock museum piece reconstructed from a ten-year old magazine plan suggested that Pan Am wanted, and got, the most in realism. The footage left on the cutting room floor would make wonderful entertainment for modelers who would take their models straight. Too bad, Pan-Am couldn't package what was left over. story or no story.

Wings for Tomorrow can be booked through the Academy of Model Aeronautics, 1025 Connecticut Ave., Washington, D.C.; Educational Director, Pan American World Airways, and will be available in offices of Ideal Pictures, and at many District Sales Offices of Pan American World Airways. MAN at Work suggests that you invite the town fathers, or recalcitrant officials, to a showing. You may end up with the rotunda in city hall for the next stunt contest!

The story incidentally was more perfect than even Pan Am knew. Talking of the Wright Brothers; who should be on screen, but C.O. "Pop" Wright, who has been flying these things since 1917. And a market tip: buy Jetex!

Most recent "attempt" to fly all day with that ugly RC model was grounded by the stork, of all things. When our CD, Bill Poythress, couldn't make it, the various (Continued on page 62)



ne

M

me

res

Er

NEXT MONTH'S COVER Miniplane

SUBSCRIPTION PRICES

SEE PAGE 57 FOR ANNIVERSARY SUBSCRIPTION OFFER

Payment from all countries except Canada must be in U.S. Funds.

CHANGE OF ADDRESS—Send to MODEL AIRPLANE NEWS, SUBSCRIPTION DEPT.,
551 FIFTH AVENUE, NEW YORK 17, N.Y. at least one month before the date of the
issue with which it is to take effect. Send old address with the new, enclosing if possible your ac'dress label or copy. The Post Office will not forward copies unless you
provide extra postage. Duplicate issues cannot be sent.

PLANE ON THE COVER

When Paul Mantz, famous stunt flier, used Thimble-Drome Flying Tiger model to plan air action scenes for his TV series "Rogue for Hire," to be released this fall, young admirers Tommy Sparks and Mike James were lucky to be on set for a demonstration by Mantz. Yes, the P-40 in background is the real thing. Photographer even got a vapor trail!



ALWAYS USE

"OK" DIESEL FUEL ... 80c PT.

FOR ALL GLOW ENGINES . . .

or vill 29 of

at wn

a roint

erng be

ho 17.

av

ed ur it.

2)

QUART GALLON

Minimum takeoff and maximum climb with plenty left for flashing acceleration in maneuvers. Plus purring smoothness when you throttle back to cruising.

That's what you get from "OK" Glow or Diesel Fuels. More flash, fun and action. Finer control with fewer adjustments and coaxing.

"OK" Fuels leave your engines clean, free from varnish or residue. Ready to go, even after long usage. Whether you're in big time competition or flying for fun, insist on "OK" Engine Fuels . . . the kind that give you the 3 big features you want.

BUY OK GLOW FUEL IN THE NEW **ECONOMY SIZE GALLONS AND SAVE!**

It's the economical way to buy OK Fuel particularly for use in meets, contest flying, clubs, or just for your own usenly \$4.50

COMPLETE AS SHOWN



FOR SUPERB ENGINE OPERATION **GET AN "OK" ACCESSORY KIT**

CONTENTS: ½ pint OK Glaw Fuel.

1 filler spaut with plastic tubing.
1 set battery leads fully assembled and soldered with battery connection and glow plug clip.

1 combination plug wrench and screw driver.

For Use with All Model Engines

AT LEADING HOBBY SHOPS **EVERYWHERE**

HERKIMER TOOL & MODEL



AHC IS THE HOBBYISTS Annotation 32 (1 to 2 3)

Annotation 32 (1 to 3 3)

Annotation 32 (1 t 1,25 4,95 1,95 6,98 2,98 8,96 14,96 8,98 1,49 4,80 2,80 8,98 8,95 2,90

ENGINES

pick Bac A49 or Lacqued 19. Common 19 or Lacqued 19. Common 19 for Grand 19. Common 19 for or Grand 19. Col. Lact Throrite Control 21. Common 19. See 19. 19 or 28 no. 2 Speed 19.38 Combot Speed 19. 25 Combo

Hornet ,049 or .051 4a, 4.95 oc .049 Pbg. 4.95 W/Str. 5.95 McCoy 1049 (AA) 7.98 McCoy 1049 - 6.98; Cub. 978 7.95 ISMITTON ENGINES Lightfree AS Las 12.00 Ring 10.00 Year Turis A0

FREE GAS ENGINE

Enemater 42° S.C. 1.50 Jr. 10° Real Refers Xr. 20° Rose Medical Xr. 20° Rose Fils Trainer 18° 200 - 200 - 200 Rose Fils Trainer 18° 200 - 200 - 200 Rose Fils Trainer 18° 200 - 20° Rose Fils Trainer 18° 20° - 20° Rose Fils Trainer 18° 20° - 20° Rose Fils Trainer 18° 20° - 20° Rose Fils Trainer 18° Rose Fils

2 Prinkley 18 - 745; Widnes Frecher Er, with begins at Flight Teniner (Assembled).

8 Flight Teniner (Assembled).

8 Flight Teniner (Assembled).

9 Flight Teniner (Assembled).

9 Flight Teniner (19 w. Cabo Sept. 19 w. Cabo Sept

ORDER FROM THIS MAGAZINE ... OR SEND FOR OUR CATALOG

ONLY AHC GIVES YOU ALL THESE EXTRAS!

. One year substriptions to Model Airplane News, Air Trails and Rying Models or their equivalent value to our regular customers. L. (6-Day Money Bost generates on missed purchases.)

B. DONUS TERMS with every degline (\$3,78 or over) purchased. Includes: Correct Size Propeller. Gib Engine Handbook, etc.

B. DONUS TERMS with Gas Flanes (selling at over \$1,95).

Includes: Construction Manual, Rubber Wheels, Insignia, etc.

B. BLS.A. no postage or packing charges for orders of over \$2,00 (include 212 of order of control of the co

Membership in "Medalcrefters of America," the club that beeps you up to date on gas madeling and SAVES YOU MONEY ON YOUR PURCHASES, Over 100,000 members!

36 ,049 to .074

Par Wor Nicke (18.20)

10 Where Friend (18.20)

11 Where Friend (18.20)

12 Where Friend (18.20)

13 Terridon (18.20)

14 Terridon (18.20)

15 Carrier (18.20)

16 Carrier (18.20)

17 Carrier (18.20)

18 Car

ERRELEY control lines .008, .010, .012 - 2'-88' .008, .010, .012, .014 2-70 Stranded .015, .021 95' 1.00 70' 1.25; 200'

ADVANCED MODELERS

AH

SA

Worl

11

OP

Fre

M/

Her

outli and any ouns 1 2" paci R/C inch print and a Li 3 or

ASSI

OL

0

WORLD'S

BIGGEST SELECTION

H

WE ALSO SELL TO DEALERS

TOP

VALUES

MISC: Aerodynamics of Model P 3.50; Model Air, Eng.—3.50; M Plana Manual or Bidg, & Flying

SATISFACTION GUARANTEED OR YOUR MONEY BACK

SPECIAL BONUS OFFERS GAS PLANES Benus items in Medal Constru Rubber Wheels

WE MATCH ANY OFFER

ORDER NOW! Get all these AHC 'EXTRAS

Mar-Fury 049 5.96 12 10.96 on .09 9.95 Doubleon 11.96 Water cooled 14.95 Dilute 1a.95 2.90 or 38.5CW 24.95 35.8W 19.96 Cub .049MS F.95 .2764MS 8.95 .099MS 9.96

ENGINE

mast all competition If sequent crises a higher trade-in-allowance to increa, cign the ad and cond at one N.Y. office with your order. USI TEMS INCUSED AT NO IA CHARGE. Your old engine in h 25% of the amount of your hear. Only 1 engine occupied per r. (Sarry, OMY, 10%, on special mornhandae and R/C Equip-y). If in deuth cand payment in and its roll refund belance.

14.99 14.99 1.47 1.64 2.96 1.33 4.79

Selection of Statement Selections of Statement Selections (Section Selection Selection

AIRPLANES

Chick Ace of 118 to 32 to 128 ORDER FROM ANY Manufacturer

AME Stocks Every Place, Begins & Ble. of Every Manufacturor You See in This Mag.

FREE! PREMIUMS

51

100 se Bo pag Slant ANC
Letelog that sells for IIsc
Letelomer (OK) - Enterprise - Connet
Chaminal - X-Acta - Won Moc Antael Cox - Consolidated - K & 8 Letelomer - Cox - Consolidated - K & 8 Letelomer - Cox - Co

Secretary 34", 15" to 33
Secretary 24", 15" to 35
Secretary 24", 120 to 25° to 374
Secretary 24", 120 to 25° to 374
Secretary 24", 120 to 25° to 376
Secretary 24", 120 to 25° to 376
Secretary 25° to FREE-FLIGHT PLANES

DUCTED FAN MODELS Crossfer 37" - 549 to 599 Fairer Dalla 34" 004 to 599 Sabre F845 34" 83 to 5314 Styray 23" - 549 to 599 T-33A 26" - 549 to 599

eronca Sadan 34" 339 to ireaupo 23" 830 to .049 ird Dog 23" 800 to .094 appr 1/34 40" .049

The second of th

Sniffer 19" AA
Snace Geror 14" . 000
Stinens Sentinel 34" . 000
Stinens Verseur 18" . 009 . 014
Stinens Verseur 18" . 009 . 014
Stinens Verseur 18" . 009 . 014
Stinens Verseur 18" . 009 . 0.04
Tall 18" . 000 to .014
Taller Cab 38" . 000 to .014
Tal

READY-TO-RUN

CYCA

AND TRIED

TESTED

PROVER O

ACCESSORIES

AHC BEST BUYS

AMBROID
MODEL CEMENTS
Take Ambroid's Universal
Liquid Coment, for example.
Préserred by top modeiers.
Strong, fast-drying, bot
fuel-preof and waterpreof.
1 % es. Table 30
4 se 40 Piet 1.75

SPACE JET 21

Encollent stunt model for
fant — Carl Geldberg Ma
21" wingspan, Power

LON control lines .806 .010 .012 .014 .016 2-5 .810 .012 .014 .016 2-7 rended .018 - 018 x 2/92' rended .018 - 018 x 2/70' rended .018 - 018 x 2/70' rended .018 - 018 x 2/70' rended .018 - 018 x 2/70'

\$1.49



.15 .10



0

" TRAINER \$2.96

TBF-1 AVENGER Consolidated's super o thentic to the last de For .29 to .61 engines.



PAIRCHILD PT-19 \$34.95 One of our most papelar Radio Con-tral models—by Jetca. 72 winapers. 70 to Ad ann. Scale job, portok br.

TURN PAGE FOR MORE AHC SUPER BARGAINS AND HANDY ORDER FORM For First Service with 100% Guarantee of Sutisfaction Send Order To: America's Hobby Center. Inc., 146 West 22nd St., New York 11, N. Y.

BRANDS SAVINGS BIG 160

AHC IS FIRST IN SERVICE SAVINGS & SATISFACTION World's Largest Selection, Too!

Buy With Confidence at AHC . . . Where You Get Not One But TWO GUARANTEES! Manufacturer's Quality Guarantee & AHC'S Famous 14 Day Money Back Guarantee

D R/C

HEAD

PHONES

275 230

1/2 PRICE

\$1.98 R/C

Deluxe Receiver

KIT

98c



ar bags type of ord flan

TO

St., Y.

Muscian Muscian ingues.23

BRAT S4.95

mes this regimes to 2 wing. SA.76 13.76

\$2.95 Serisity. gas ent. AHC.

S14.95 model, Am 61" spen modelable

\$2.50 finte-print sic replice inties".

DA. H ada Con management in

AMTRON -**WW**-

AN AHC EXCLUSIVE A FANTASTIC

HI-FI RADIO CONTROL OUTFIT W OPERATES ANY MODEL . . . BOATS, CARS & PLANES From 1/2A to the Very Largest . Up to 11/2 Miles

From V2A to the Very Largest

Up to 1½ Miles

We'en sold hundrods of those terrific R/C untified They'en made acticativity for us to

end Americs's highest and best known Radio Control manufactures (C. 2008)

because of our hope purchasing power. Performance-wise control was to the control of the control

MADE TO LATEST FCC REGULATIONS, TOOL

GET BOTH THE RECEIVER AND TRANSMITTER KITS

Both for only

A Verified \$25.00 Value!

ASSEMBLED OUTFIT Ready-To-Operate \$2395
ALL FINISHED, TESTED AND
INTERMEDED BEADY FOR USE

INDIVIDUAL PRICES

\$ 6.95 unents, loss batteries-only MBLED RECEIVER. Ready.T 10.95 8.95

12.95

XFGI) R/C TUBES

Reg. SALE _1.40 ___89 _3.83 __2.93 _1.25 ___.98

viey "Astro-Heg" \$15.95 ones winner of 1st, Zed, 3nd & 4th Audit 1958 Nationals 72 open. "48 EC engines. Order

Berkeley "Astro-Hog" Sensational winner of 1st. 2nd. place in Multi-1958 Nationals Length 50". For 35 RC angis yours from AHC.

years from AHC.

Are 9 - 45° Dt to 15

Are 16 - 57° 15 to 19

Are 17 - 57° 15 to 19

Are 17 - 57° 15 to 19

Are 17 - 57° 16 to 19

Central 17

MINITONE

New R/C MC Bends Sole! 26.996; 395 27.046; 27.096; 395

CRYSTALS 27.255 mc.

789 289

finiature DC Mater

095

20

EACH

ANC Sale on Quality R/C Yest

Reg. Solo \$4.93 \$3.95 2.95 2.95 2.75 2.29

S

9.95

Nylon Gears

MILLIAMETERS

TWIN TUBE . PRINTED CIRCUIT AMTRON anguard -DELUXE R/C OUTFIT

ere's the Precision Equipment You Always Wanted at a Fraction of What You'd Expect to Pay!

"MANDAM" REPUBL is a superior quality actific ammentated for reliability, accoracy and performance. It will fit in the part allows are maintained as a reliability, accoracy are maintained as a reliability, accoracy are maintained as a reliability accoracy and according to the reliability and reliability.

SALE PRICED AT LESS THAN THE REGULAR WHOLESALE COST!

2 CHANNEL

465 mc.

Transmitter BCT-7 By far the finest, most reliable unit made.

REG. 34.95

OUTFIT

95

ABLED COMPLETE OUTFIT INDIVIDUAL PRICES \$12.96

=

SINGLE CHANNEL TONE

RECEIVER BCR-8

FOR USE WITH 907-7 TRANSMITTER See Below

REB. 1995

NO TUBES! COMPLETELY TRANSPETORIZED

Order Two Recolvers & Save An Extra 88.00 34 85

17.95 12.95

ANC WAS EVERYTHING YOU WANT! EVERY BRAND! ALL PARTS AND ACCESSORIES! SEND US YOUR ORDER AND GET ALL THE ANC EXTRAS!

ADGES
AND
RACHERON
LUC Base'r B Treascitive
Britisty Annual Mach 197
Reve B Treas. Cambo Etc.
Receivers - Single Channel
Acc Content Single Channel
Acc Cond. 52 826 Annual
Acc Content Single Channel
Acc Cond. 53 826 Annual
Receivers - Single Channel
Acc Cond. 53 826 Annual
Receivers - Single Channel
Acc Cond. 53 1978 826 Annual
Receivers - Single Channel
Receivers - Sin

CG 112 fez 3-29 (Kanenhied)
Delivan IV (Annehied)
Delivan IV (Anne 23.95 21.96 29.95 49.80 34.95 24.95 49.36 49.95 39.95 99.50 99.95 99.95



Order the Badio Gastrel Beference Books 'Fee Wand From ARC. If Pri-Red Gentral Whool by McCleste 235 Smight Redin Corn by Fi. Michiel 335 Smight Redin Corn by Fi. Michiel 335 Gastrell Corn by Fi. Michiel 335 Gastrell Corn by Fi. Michiel 335 Books of Redin Gen (Hebs Help.) 335 Books of Redin Gen (Hebs Help.) 335 Corn. 81: C Seujencet (Hebb Help.) 335 Corn. 81: C Seujencet (Hebs Help.) 335 C Seujencet (Help.) 335 C Seujencet (Hebs Help.) Simple Radio Cen. By Pl. 9. Pl.
Application of R.C. I Mobby H.
Model Cen. by Radio By E. Saf
Gom. R.C. Equipment (Hobby h.
Basics of Radio Con. (Hob. H.
R.C. for Plannes & Boats by W.
Radio Cen. of Models by Semer
R.C. For Model Beath by Model
Guide to R./C. Winsten Minit

And American State of the Control of

Lecente Tantor del 7 de 194 fies Lecente Tantor del 7 de 195 fies

NEW At Plastic. 40" Span
For July to J74 Eng.

ALIGNING TOOLS

REG.

14 Q 1:305 Compound Escapement

4.95 1.95 23.95 24.96

R/C Battery

CHARGERS

4000 Clim Signa Brier, Sais 31
Livité devel 1900 Clim Signa Brier, Sais 31
Ribar Paledon.

Raby Paledon.

Raby Sais Signa Brier, Sais 32
Miller Rein, Raby Sais 32
Miller Rein, Raby Sais 32
Sais Neat. "Antren Engar. 31
One Reed Basis — 5 Rend
One Rein Sais — 5 Rend
One Sais — 5 Rend
On . .89 .35 1.00 1.75

AIR-SEA RESCUE BOAT R/C best model that at almost half price. \$12.95 rail length, 8" been examile behas hell to with muhogamy. For 00 to 19 eng. icc. molester.

Choice of Flat Screwdriver or Busages Tip

WET CELL STORAGE BATTERIES

ASSEMBLED 2 Volt 2-6 V. 100, 35.95 Rog. \$7.95 4 96 6 96

Formatis "Weller"
SOLDERING GUN
Steinberg grafessional soldering gen that gives instent
heat. Handsome bilimper!

R/C*fant Here's your chance to own the "Caddlag" of R/C requirement at treamments savings. The BABCOCK RCT7 is the component of the savings. The BABCOCK RCT7 is the savings of the savings of the saving savings of the Transmiller and Either Reserver Transmission of the property o

Use Handy AHC Order Blank on Next Page Send Order To: America's Hobby Center, Inc., 146 West 22nd St., New York 11, N. Y

M

959



-25°

CATALOGS
OF Parket Control 25th
St. Studen Control 25th
St. Studen Control 25th
St. Studen Control 25th

24 HOUR SERVICE AT ALL TIMES

TRUCTION. The servers to every problem yee will ever

WORKSENCH EDITIONS of the famous Winelaw basis (Reg. \$1.00 each) for only 25g GLO BINGHE HANDBOOK. Talk all about the theory and operation of glu segions CONTROL LINES. Here to build and fly them. Curren subject from A to 2 GAS MODIE. PLANE CONSTRUCTION. The correspond to swarp problem was well awaren.

Sci



Over 200 successful flights in all kinds of weather made the author happy with the results of time well spent on detail and paint job.




Scale tail surfaces and near-scale dihedral make Lutz's Champion exceptionally accurate free-flight scale. Yep, the door works!

▶ Descended from the famous Aeronca Champion, the new Champion Traveler is manufactured by the Champion Aircraft Corp., Osceola, Wis. The new Champions have increased horsepower, new oleo-type shock-absorbing landing gear, completely upholstered interiors and a flashy new paint and trim combination. This outstanding airplane makes a rewarding model.

At the 1958 Nationals, the model was relatively new and not well tested, but later in the season took second in the Ninth Annual Flightmasters Scale Contest, Inglewood (Calif.) being beaten out by a ship with two-speed motor permitting full-nower take-off and throttled-back descent to power-on landing. At the time of writing the Tri-Traveler has logged over 200 flights in all kinds of weather. Scale tail area and near-scale dihedral don't seem to affect performance adversely.

The box-type fuselage is constructed from %" sq. balsa with the nose portion planked with 1/16" sheet balsa. Cut out the two upper cabin side frames from 1/16" plywood. Drill the wing dowel holes in the right and left frames at the same time. This assures both wings have the same angle of incidence which is very important. Add the bulkheads, 1/16" balsa rudder keel and stringers. Don't forget the 1/16" x 1/32" balsa cap strip on the bottom longerons which will serve as a covering ledge to keep the covering from sticking to the fuselage upright braces when doped.

The main landing gear mount is cut from 1/16" plywood. Sew the 1/16" piano (Continued on next page)





Wing lights, gas caps, antenna, typify details that make a standout craft. Cabin side slope automatically provides the dihedral.

The Tri-Traveler . . . Continued

wire gear to this mount and glue several times. The nose gear is bent from 3/32" piano wire and held to the firewall by J-bolts. The firewall and engine mount box are also cut from 1/16" plywood. When building up the engine mount box, which may be altered to fit any 1/2A engine, make certain that at least four degrees of downthrust are built in.


Install the operating cabin door on the right side of the fuselage if you intend to add the interior details to your model. The seats are built from 1/16" dowel with soft balsa cushions. The cabin floor is 1/16" sheet balsa with


the sides and top being 1/32" sheet balsa. To simulate the upholstered panels and seat cushions, colored flock is used. This flocking compound can be purchased from any arts and crafts store. It is very light and easy to apply.

A trip to your local airport will give you unlimited ideas for the numerous small details. The cowl is built up from balsa blocks, then hollowed out. Use four large dress snaps to hold the cowl to the firewall. A small piece of wire screen and a length of 3/16" dia. aluminum tubing will make the details for the cowl.

The wing tips and tail outlines of the original model were formed over a template cut from " sheet, with the inside contours as a guide when cutting out the templates; the strips of wood were boiled for ten minutes before bending them around the templates. The plans show sheet balsa edges for simplicity. The 28 wing ribs are cut out, pinned together and sanded to the correct airfoil shape. While the wing ribs are still pinned together, drill a "" hole through them where the rear spar is located. Cut out the % x %" notch for the main spar, allowing an added 1/16" depth for the 1/16" balsa leading edge sheeting. Install the 1/16" wire hooks and add the 1/16" plywood end ribs which extend the full chord of the wing. Drill the two " holes in the end ribs to match the two " dowels on the fuselage. Make certain that both wings are mounted at the same angle.

All control surfaces are attached with soft iron wire as hinging material. The wing struts are constructed from 5/16 x %" basswood or hard balsa. Use thin brass or aluminum to make the fittings. Use 1/16" dowel pegs to help hold the fittings in place. The length of the wing struts controls the amount of dihedral, which should be 1-%" at each tip. Follow the plans closely when assembling the wing struts, making (Continued on page 36)







Fort Wayne, Ind., Mad Modelers, had circles in McMillen Park as long ago as 1947. Shown are

s 50 and 70 ft. circle—club then hoped for new additional UC circles of 70, 60, and 42 ft.



FACILITIES

FADERSHIP

How

by c

in se

It se

perm

leave

noise

son"-

We

yard:

out 1

our

taker

tion

long

Two-level "control tower," one feature of the Charles A. Donnelly Modelport, in New Orleans.

Professional analysis of 30 "success stories," offers proof—useful tips—that you can do something about flying-site problem.

by WILLIS C. BROWN, AMA#1

Specialist for Aviation Education
U.S. Office of Education

▶ Do you want to see that impressive level-green expanse of the ideal flying site in your town? Others have done it. You really can have that flying site you have always wanted, if you don't "goof" on your planned strategy.

Don't give me that old story about getting kicked out of your local park, or the town Fathers passing an ordinance forbidding your flights as a noisy nuisance. Perhaps these real quotes sound familiar? They are from groups that had nothing but bad luck until they saw the light.

"At various playgrounds and open areas in the city our % A models are flown regularly without interference.

place to




Many cities have had Modelports for 10 to 15 years, others n process of construction. Dayton takes theirs seriously.



Before Wilderness of weeds and brush marked site of the future impressive flying area in Dayton outskirts.



After City fathers—Dayton by no means unique—consider cost of flying area improvement worthy investment



However, the larger motors made too much noise and we were squeezed out by complaints." - "always had trouble in securing a site for flying our models. It seems that we no sooner obtain a permanent site than we were asked to leave. Complaints of neighbors over noise, we surmised was the usual reason"-"our Police enforced a ban on the flying of model planes in our parks. We turned to various fields-school yards-complaints would be lodged, and out we went. We reached the end of our patience when a cemetery caretaker invited us to use an unused portion of the cemetery-imagine how long this lasted."

But perhaps these five actual stories

from those who have found different successful methods may give you the idea you need.

1. From the Folsom, Pa. Golden Eagles R. C. Club comes a letter quoted in part. "We have been having a considerable amount of trouble finding and maintaining a flying site for our club members in this area. On the 28th of November (1958) the club officers went to the—Oil Laboratory, to see if we could obtain written permission to use their fields as our future sites.

We found the management more than willing to cooperate and give their permission. A meeting of club members was called, and a basic set of rules written. These rules were also submitted to the ---Oil Co. management. The rules were voted on and approved."

The letter adds the thought that the management were evidently impressed by the rule making and self governing features of the Academy of Model Aeronautics. They probably gave approval because of this and the liability insurance features inherent in AMA membership.


Notice that this club had a plan which included self governing rules—something tangible on which the management could vote, a very businesslike way of going about getting a flying site. Have you carefully planned and tried this businesslike approach?

2. Another (Continued on page 48)


Buring dedication (1954) of Model Flying Circle, Boulder, Colo., spansored by Civil Air Patrol, City of Boulder, Boulder Exchange Club.







lines give that going-places look. Engine is accessible, Roto-Valve and linkage easily put in.



Front to back: Battery-bex tray, Gyro 22X r'cvr, Bonner motor-control SN, Bonner Varicomp esc'p.

pla

ten

of !

tog

mo

cen

KXX

flai

sec

bot

she

gea

fast

the

The

inst

rem

two

run

its

con

1/1

cen

HOUDINI

Once upon a time they said it couldn't be done but low wings have it over most cabin jobs in RC. Try this .15 pronto.




Top lifts off, and receiver and battery trays both slide out easy like. One thing about low wings—you'll never pop wing in loop!

▶ Editor's Note—Having flown the first Houdini in the spring of 1958, found that it will break out of a turn within 90 degrees if not thrown in steeply. With normal entry it will complete a 360 on its own, perhaps losing little altitude. Heavy-on-rudder entries (no hold) start it down but recovers. Responsive. Flown tame, no worse than many cabins, better than some. If stunted, flat-trin gave long, screeching pull-outs. Pays off a bit on approach turns in wind but well worth it!

Low wings once were thought unstable and difficult to fly. Houdini will do such maneuvers as rolls, split S, wingover, etc., without difficulty. It has been flown for more than a year with mishaps due only to radio failure. Houdini performs as well, if not better, than most high wing models.

Houdini, like any single-channel low wing, has excessive dihedral with enough angular difference between the wing and stab to insure a more rapid pull-out from a vertical position. The landing gear is placed well back, slightly ahead of the center of gravity, for straight tracking without tendency to ground loop. The rudder was built so that when the top of the fuselage was covered, the silk would cover the rudder at the same time, fairing it into the fuselage. This enchances the appearance and adds strength. Construction is simple but sturdy. Weight is 3½ pounds.

Fuselage and rudder: The two fuselage sides are cut out of hard straight-grained 3/32" thick sheet balsa, as are the two doublers. The doublers and the mating area of the fuselage sides are given a coat of cement and set aside to dry separately. When dry another coat of cement is applied to surfaces, the parts clamped together.



by JERRY STOLOFF

Mark off on the inside of the fuselage sides the position of all the stringers and uprights and cement them in place. Firewall F-5 is cut out of 3/16" plywood as per template. Bulkhead F-4 is cut out of 3/16" sheet balsa as are F-1-2-3. Cement formers F-4-5 in place. Sand inside of fuselage at the rear section so that when it is cemented together, there is a proper joint. The cross braces are added and the formers F-1-2-3 cemented in place. The motor bearers are pushed through former F-5 and cemented securely to the inside of the doublers. The kxx" stringers are cemented in their respective slots of the top formers, making sure to taper them so that they flair into the rear of the fuselage.

The bottom nose blocks are cut out and cemented securely. The gussets, where the wing and tail dowels go through the fuselage, are cemented in place. The bottom half of the fuselage then is covered with 1/16" sheet balsa with the grain running crosswise. The tail gear is bent to shape from 1/16" diameter music wire and fastened to the %" plywood mount. It is then cemented on the inside of the fuselage at its proper location with the gear protruding through the bottom of the fuselage. The top, front cowl block is cut out slightly oversize and just tacked in place with small dabs of cement. The removable hatch block also is cut slightly oversize and two %" sq. pieces of balsa are cemented on the underside, running lengthwise as guides to keep the cowl block in its proper location. The blocks then may be sanded to conform to the fuselage width and contour.

The rudder is constructed flat with the exception of the 1/16" x x" caps which are assembled after the rudder is cemented in place. The fuselage, including the rudder, is



Cranking the .15, Jerry readies Houdini for an ROG take-off. Get easy-to-work microswitch—this rudder job lives up to its name.

thoroughly sanded and the bottom nose blocks rounded off. The removable hatch is separated from the rest of the fuselage. You now are ready for the radio installation, keeping in mind that the model must balance at the position shown on the plan. The ½" square grooved uprights which hold the battery tray and the receiver are cemented to the inside sides of the fuselage. The escapement is mounted on ½" plywood and cemented in position, making sure that the torque (Continued on page 31)

Early Birds By Douglas Rolfe

Number 7

DEVELOPMENT OF THE PUSHER BIPLANE

The pusher biplane was introduced by the Wright Brothers, Voisin, Curtiss and the Farman Brothers. There were others, of course, but not of such historical importance. The Wright was in effect a dead-end but all the others were developed until the pusher boxkite became obsolete.

The Grahame-White boxkite shown was a modified Henri Farman in use 1909-1911. The Maurice Farman "Longhorn" (after the lengthy front skids) belongs to this period. Both Henri and Maurice Farman dropped the front elevator in later types, introduced the nacelle, but retained the four-wheel landing gear.

The clumsy-looking Maurice Farman with front elevator and biplane tail was slow but very easy to fly. The Wrights also abandoned the front elevator and one of their last designs, the "Tin Cow" (by mistake included in the last instalment covering tractor biplanes) had a bonafide fuselage.

Vickers F.B.5 was prototype model of famed W.W.1 "Gun Bus". The Voisin Type Q was a brilliant example of fine engineering in these far-off days and largely of metal construction. Note the oleo strut wingtip skids!



1912 MAURICE FARMAN" LONGHORN"
70 H.P. RENAULT V-8 AIR-COOLED ENGINE

Pougas

1915 VOISIN TYPE Q 130 H.P. CANTON UNNÉ AIR-COOLED RADIAL



1912-13 WRIGHT "SCOUT" 50 H.P. WRIGHT 6-CYL. ENGINE



1912 MAURICE FARMAN "SHORTHORN" 70 H.P. RENAULT V-8 AIR-COOLED ENGINE

HIT

59



Kurt Reich, eight, has understanding helper in his dad, George, 37, US Wakefield finalist for

1958 and contest flier for more than 20 years. Model is popular Ranger. Pix, Cleveland Press.

Souped-Up Pre-Fabs

by CHARLES TRACY

Who'll be first to crack three minutes with simple kit? Some promising tips.

be

are

WO

sec

11,

ley

Fle

sec

tw

An

are

wi

Soi

and

ma

all-

oth

GETZLOFF PROP ... 8"DIA - 16.61" PITCH 7/8"WIDE - 37/64 THICK TOP VIEW RADIUS CUT AT SAME POINT AS 19/6"R. SIDE VIEW CUT OFF SHADED PORTIONS 3/2"R. FRONT VIEW SCALLOPED T.E.

► Champion modelers of the midwest are enthusiastic about indoor "prefab" flying. Interest in it has been growing in the last eight years because it appears as a regular event on the program of the Great Lakes Indoor Air Meet held in Cleveland every winter under direction of The Cleveland Press.

A "prefab" is a sheet-wood model made from a kit. Several manufacturers make them, commonly used examples being the Carl Goldberg Ranger 21 and the Top Flite Stinson, Luscombe, etc. series.

Souped-up" by established Cleveland standards, one of these little jobs will cruise around a medium-sized school gym for two minutes. They're ideal for indoor flying contests because a giant-size hall isn't required.

Prefabs fit nicely under a 30- 40- or 50-foot ceiling. They offer plenty of challenge. In fact, it is downright tough to complete with Detroit's Dick Kowalski, who set the new record of two minutes, 41.6 seconds last winter in the open age division using a Goldberg Ranger 21. Or Mike Karlak, Cleveland's champ, who flies a Ranger two minutes, 38 seconds on an official flight. He's in the open class too.

STANDARD PROPELLER SAW OFF SHADED PORTIONS OF BLOCK ... 21/2"--1/2

" 1/2" WIDE

TOP-AIRFOIL SHAPE ...



WRAP WET SILKSPAN PAPER RIBBONS OVER WING AND FORM TO HOLD BALSA SHEET WING TO SHAPE. BAKE IN OVEN FIVE MINUTES AT 350 DEGREES.

MODEL AIRPLANE NEWS . August, 1959



If Shirley McQuillan seems to question husband Dawson's winding, she's worried about prop in his mouth. Ranger deadsticks, above.


The whole idea behin'd prefab contest flying was to put an event on the indoor program that would appeal to kids because they might easily make kit-models for it. So what are the kids doing with prefabs today?


A little nine-year-old girl, Susan Getzlaff, Cleveland, won the prefab Dodo event with a flight of one minute, 10 seconds, using a Top Flite Luscombe! Then Ron Roharik, 11, flew his Ranger one minute, 39.4 seconds; Dan O'Malley, 12, rolled up one minute, 52.8 seconds as champion Fledgling; Ronald Roskilly, 15, scored one minute, 35.8 seconds, as Junior winner; Don Eble, 20, made a hop of two minutes, 28.2 seconds as senior ace.

But it's true—almost anybody can put together a prefab. And for the Great Lakes Indoor, everybody does. They are entered by the hundreds. In last winter's meet, every winner used a Goldberg Ranger except Miss Getzlaff. Some second and third place fliers used Goldberg Cessna's and Spirit of St. Louis. But in the meet were every kind made.

The fascination seems to be in the variety of ways to meet the prefab challenge. Rules keep it from being an all-out redesigning job in favor of the experts, as every other AMA event has now become.







Rubber winder made by Wilson's of Cleveland, allows five to ten times as many turns. As rubber wound, winder moved toward nose.

Prefab rules give you the same box of parts and materials as the next guy. No special light indoor wood or tricky tungsten wire bracing is allowed. Some things you can change. Look at this official description of a prefab in the Great Lakes indoor rules:

PRE-FABS: Made from Top Flite or Goldberg kits; all sheet-wood construction. Changes in general design layout or surface areas not allowed. No paper covering. Changes in following are okay: dihedral, polyhedral or cathedral in wing or tail; propeller; rubber motor; airfoil; prop bearing; nose fitting. Ballast and decals may be omitted. Except for these changes and omissions, all other parts and materials in kit must be used. Added external bracing not permitted. Ribs to hold airfoil are allowed. No substitute materials. Sanding for lightness okay, but leave trace of decoration scheme to prove kit wood was used for all parts. Timed for duration. Best flight of six scored as entrant's record. No delayed flights. So with the rules in hand, what can you do to win?

There are three key factors: light weight, correct propelller and rubber motor of proper size.

Kowalski's plane weighed .31 ounces, Karlak's .30 ounces. Kowalski used 12 ribs on the wing, six on the stabilizer. These not only formed the airfoil but, by holding the camber, gave the wing necessary rigidity to keep it from flapping, a common fault with "strutless" Rangers. (We begged Carl Goldberg to remove the struts five years ago. He did.)

Kowalski used a hand-carved balsa propeller 8-inch diameter, 16-inch pitch. It was turned by a 25-inch loop of %-inch Pirelli rubber. His dihedral was 1%-inches under each tip.

Carefully sandpapering all parts of the plane before assembly brings the weight down. A razor-blade plane can make the job easier and faster.

Dan O'Malley used a model heavy by usual standards. He smoothed and lightened a regular 8-inch balsa machinesawed propeller, then added %-inch tips to it, increasing the diameter to 9%-inches. His motor was % flat, brown rubber, in one loop, twice the fuselage length.

Ribs in the wing should be kept shallow. Deep or thick airfoils are unstable longitudinally. The plastic nose blocks are replaced with wood to make easier winding and storing the rubber back into the fuselage.

CONTINUED ON NEXT PAGE





Two minutes, 41.6 secs. Open prefab set by Dick Kowelski, Detreit, in Cloveland's Public Auditorium. But the ceiling was 90 ft. high.



Few of the trophics (ahemt) at Great Lakes Indoor Meet, Junior winners Jim Skinner, Dan O'Mailey, Ron Roharik, Elmer Schroder.

SOUPED-UP PRE-FABS . . . Continued


Wheels are cut in two, sanded and drilled full of holes to cut weight. Even windshields of plastic are sanded thin.

The big trick, however, is backing the wing to the proper airfoil. Carve wooden form to the airfoil shape. Lay sanded wing panels on it. Wet one-inch wide ribbons of Silkspan tissue and bind the wing panels to the form. Put into an oven at 350 degrees for five minutes. Remove, cool and unwind the paper. Your wing will be stiffly formed to the airfoil you want. Apply the ribs to hold it.


Carve the wooden form carefully. Use a razor-blade plane. Sandpaper it smoothly. Don't taper the form. Leave it rectangular, same width as chord of wing at root. Then you may use the same form for both wing panels. Wing, of course, is cut in two for this operation. Dihedral is added when panels are cemented to fuselage. Clay on plane's nose is used for balance rather than movable wing.


One panel of wing is done at a time. If oven is large enough, wooden form may be long enough to accommodate entire wing. Otherwise, with short wooden form, put one wing on from one end, the other wing later from the other end. Don't make two wings for the same side.

PREFAB NOSE is improved by enlarging the hole in the fuselage bulkhead so knotted rubber goes in easily. Plastic nose piece of Ranger can cut rubber and is too small for enlarged motors. A simple removable nose with a piece of 1/16-inch sheet wood fitted to key into the fuselage former works (Continued on page 40)




ier Cless winner, Don Elbe, 20, American Airlines employee. By of keen competition in all three AMA age-class divisions.








MODEL




Dizzy Bee

by BOB LAUDERDALE

A master flier presents a 29 Mono-Line speed model. Thoroughly contest tested.







▶ The Dizzy Bee was built for the 1957 Nats in Philadelphia. No official flights were recorded because the new Fox 29X wasn't thoroughly broken in. For the 1958 Nats in Chicago, the Dizzy Bee was refinished and the engine was given more running time. The best flight turned was 149.92 mph, good enough for 6th place behind Harris and Shelton who hit 155 for a new record. Since then Dizzy Bee has won three firsts at speeds of 150 mph and is very capable of going faster under the right weather conditions.

To begin construction you

(Continued on page 36)



by RON ST. JEAN

Scale a hot airplane to different size and the result often is a "dog." This article solves long-standing free-flight mystery.

To cor

Rai ma

the wir yet

the

pre

cer

day

hav ten

sion

onl

wel

che loa

rati

um

sec

ply.

par

pro wei load the cub thro equ

reta sho only mal cub


The

thir win win

mo sam load is t app dim othe dim thre

For years now we have wondered why, back in the days of the minimum wing loading rule, the small models glided so poorly in comparison to larger free-flight gas models. It was explained to us that the smaller model flew at a much lower effective Reynold's Number than the larger one, and "everybody knew that you need a high R.N. for best performance!" We discovered that R.N. is merely the product of velocity, chord, and some rather illusive "air density factor." So to make a more efficient model by obtaining a higher R.N. we needed to increase the chord of the model (hence, a larger one) and increase its velocity. (We figured that finding denser air would be quite difficult.) An experiment was made in very low wing-aspect ratio, but it was a dismal failure; we then had too much "tip loss." Building a heavy model to increase velocity also didn't work. Some success was obtained, however, by building a very low drag model, and thereby increasing velocity.

With this background, we were somewhat surprised to find, in recent years, that our %A's could and did glide as well as our C jobs. "How come," we wondered. "What happened to Reynold's Number, was it repealed? Had small engines become much hotter for their size than larger engines? Or did the fact that the old wing loading rule had been abolished have something to do with this?



To check out the latter possibility, we computed the wing loadings of our Ramrod fleet, coming up with information in Fig. 1.

As can be seen from the tables, there is a very definite progression evident, the small models having a much lower wing loading than the large ones. And yet the glides (sinking speeds) on all these different sized Ramrods were

pretty much the same.

d

nt

LS

18

We felt we had found the answer but certainly didn't understand it, until one day it hit us like a bolt: For years, we have been thinking of wing loading in terms of so much per square something or other but the wing is not a two dimensional thing, it is three dimensional, and loading should be figured on a volume, not area basis; it has not only chord and span, but thickness as well. To test this hypothesis, we quickly checked this out, calculating the wing loading as so much per cubic inch, rather than square inch.

To make the measure of wing volume, we first determined the actual rib area of a typical Ramrod wing section, then divided the chord into this area value, in order to arrive at a measure of average thickness. Multiplying the average thickness of a particular wing by its area, then, would produce the volume in cubic inches. As shown in the table, dividing the weight in ounces by this figure gives us our three-dimensional, or cubic wing loading in ounces per cubic inch for the various sized Ramrods. (Fig. 2.)

As can be seen from the table, our cubic wing loading is almost identical through the various sizes. And since all these models have, in addition, equivalent gliding ability, a statement of principle seems in order: In scaling a design to a different size, so as to retain the same glide, the wing volume should be made directly proportional to the weight. Or, since we are dealing only with the same design, we can make the weight proportional to the cube of the span, or the 3/2 power of the area (square root of area cubed). The results are the same, the important thing being to put the measure of the wing in three-dimensional terms.

It is now apparent to us that figuring wing loading as so many ounces per square foot or square inch is useful as a measure of comparison between models only when those of almost the

same sizes are considered.

The real fallacy of making wing loading comparisons on an area basis is that we are co-mingling oranges and apples, so to speak. That is, weight is three dimensional and area only two dimensional. For any direct comparison, we need to express one in terms of the other so that each will be in the same dimension, whether it be one, two or three. (Continued on page 41)

FIG.1


MODEL	ENGINE DISP. (CU. IN.)	WEIGHT (OUNCES)	WING LOADING (OZ./SQ. FT.)		
RAMROD 150	.020	3	2.88		
RAMROD 250	.049	6.5	3.74		
RAMROD 400	.099	13 '	4.68		
RAMROD 432	.148	15	5.00		
RAMROD 600	.225	24	5.76		
RAMROD 750	.320	34	6.53		

FIG. 2

MODEL	AVERAGE THICKNESS OF WING (IN.)	VOLUME OF WING (CU. IN.)	WEIGHT (OUNCES)	WING LOADING (OZ./CU. IN.)	
RAMROD 150	.341	51	3	.0588	
RAMROD 250	.443	111	6.5	.0586	
RAMROD 400	.562	225	13	.0578	
RAMROD 432	.579	250	15	.0600	
RAMROD 600	.681	409	24	.0587	
RAMROD 750	.766	575	34	.0591	

FIG. 3

ENGINE DISP. (CU. IN.)	WEIGHT	WEIGHT RATIO (.049 = 1.00)	SPAN (IN FEET) CUBED	SPAN (IN FEET)	LINEAR RATIO	THEORE- TICAL AREA (SQ. IN.)	ACTUAL AREA (SQ.IN.)
.049	6.5	1.00	38.6	3.38	1.000	_	250
.020	3	.462	17.8	2.61	.772	149	150
.099	13	2.00	77.2	4.26	1.260	397	400
.148	15	2.31	89.2	4.47	1.323	437	432
.199	24	3.69	142.3	5.22	1.545	597	600
.320	34	5.23	202.0	5.87	1.737	753	750





Starter on this ball-bearing .15 not essential, but nice to use



Parts are typically Cox-and no costings utilized in its design

COX Olympic

▶ Maybe the new AMA rules are not everybody's meat: rule changes never are, anywhere, but, in reducing the class A displacement limit to .1525 cu. in., the AMA has gone a long way towards raising the world status of American contest modeling.

The reason for this is easy to see. The .1525 cubic inch (2.5 cubic centimeters) displacement is the limit that is internationally recognized for world championship model flying. For several years now, the two FAI world championship events for gas-engined models, free-flight and speed, have been restricted to 2.5 c.c., and, in Europe, individual nations have adopted FAI rules for most, if not all, of their own internal contests. As a result, engine designers have been encouraged to concentrate their ef-

forts on the development of high performance motors of this size, whereas American designers and manufacturers have, hitherto, devoted most of their resources to an entirely different set of requirements. Small wonder that no American modeler, or American engine, has won an FAI international contest for five years.

woi

sino

less

exc

wei

inte

rule


(2)

lift,

delt

The U.S. can produce engines capable of winning such events and there is no doubt about this in the minds of contest men all over Europe. Ever since it was first known, two or three years ago, that the Cox company had a .15 on the way, engine enthusiasts in Britain and continental Europe have awaited its appearance with bated breath. They are not going to be disappointed. There is no shadow of doubt that the new Cox Olympic .15 can better the performance of any stock 2.5 c.c. engine made in Europe at the present time. There is little doubt, either, that Western Europe will use this engine wherever its potential can be exploited: the challenge of East European state-sponsored contest engines makes this inevitable.

The Olympic follows the usual Cox layout, of reedvalve induction and reverse-flow scavenged twin-opposed port cylinder. Such notable Thermal Hopper features as the multijet carburetor and clean, hemispherical cylinder head with built-in glow filament, are retained. The main visible changes are the beam (Continued on page 58)





Conical camber shows in pic, drawings. If Miss Donna Hubbard seems to approve it's

because she is an Aeronautical Engineering student at University of Minnesota. Jetex 50.



by DON MONSON

Conical camber works on a model, too! Hand-launched glider and Jetex versions fly better. What is next?

▶ When Convair engineers tested the prototype of their delta-wing F-102, they were surprised to learn that it wouldn't go supersonic even with afterburner, especially since wind-tunnel tests showed that the delta wing had less drag than the swept wing while it was passing through the sound barrier. The main cause of this effect was the excessive interference drag between the wing and fuselage.

About the same time, two new aerodynamic discoveries were divulged by NACA scientists: (1) a reduction in interference and wave drag by application of the "area rule," popularly referred to as the coke bottle design, and (2) a reduction of the induced drag, i.e., the drag due to lift, by use of "conical camber."


"Conical camber" means that the leading edge of a delta wing has a progressive downward camber increasing in radius of curvature as it passes from root chord to tip chord (Ref. 2). Theory and experiment show that both area rule and conical camber have maximum effectiveness in the transonic range, i.e., the transition between subsonic and supersonic flight, with conical camber being effective also at high lift co-efficients; and when Convair applied these modifications to their F-102, the result was the highly successful supersonic F-102A that you see flying today.


The model version of this plane originated when we began to wonder what the effect of conical camber would be on a paper glider. A few hours and several gliders later, living room tests showed a noticeable decrease in the glide angle of the glider with conical camber over the one without camber. Further glide tests in a gymnasium where more conclusive tests could be (Continued on page 46)

FULL SIZE PLANS NEXT TWO PAGES

The whole is equal to the sum of its parts—and the parts cinch to slice from nice, white balsa. The Jetex 50 engine clips on easily.


for quickie, make flat-wing version—two top models. Others use conical camber; leading edge curls down progressively toward tip.





ALL PARTS I/16" SHEET UNLESS OTHERWISE NOTED L.E. CROSS SECTION AT WING ROOT ON SIMPLE VERSION, L.E. IS PLAIN I/16" SHEET. TO OBTAIN "CONICAL CAMBER," CARVE L.E. FROM 5/16" X 3/8" STRIP AS PER CROSS SECTIONS AT TOP OF FACING PAGE. (NOTE THAT L.E. DEPTH TAPERS FROM I/I6" AT ROOT TO 5/I6" AT WING TIPS). CONVAIR F-102 "DELTA DART" -FULL SIZE PLANS -"SCOTCH TAPE" ALONG L.E. 3/32" SHEET FUSELAGE (FOR REINFORCEMENT) IS OPTIONAL FC-386 1/4" SQ. TAPERS TO 3/32" X1/4" AT EACH END (SEE TOP VIEW), HARD BALSA REAR VIEW SIMPLE WING (RIGHT HALF) "CONICAL CAMBER"

AT






French Boy Scouts hear about RC from Sgt. James Duckworth, at Phalsbourgh AFB. Stand-

ing, right tip, Smog Hog, T/Sgt. Wing, American Scout Master; his L, H. Litzenberger, Director.



Powered glider, A. Friberg, Sweden, 100 inch span, transistor r'evr convertor, Telematic actuator.



radio control news

pas wise nun pari sun

dro at l pric

face with three free trol it v

Add

siste

tran Hea

grip

tain

doir

stuff

soal

wat

are

quic

tran

safe

F

dista 12th mod

pow

5-ch

and

dow The

mile

mph

In

fron TTP

seco

basic

has glan

How

sider

to th

freque

Ther

cies

amou hets


MOD


by EDWARD J. LORENZ

In good old summer time, strange and wonderful airplanes take to the skies.

TECHNICAL TOPICS

Now that hot weather is covering most of the country, treat batteries, transistors and wing hold down rubber bands in the right manner. Batteries should not be exposed to the hot sun for prolonged periods, referring, of course, to the regular carbon-zinc type. Transistor characteristics will change with heat, therefore keep them out of the direct hot sun. Rubber will rapidly deteriorate when exposed to heat and ultra-violet radiation. Several covers have been shown in this column in the





28


past, for protecting your plane. Otherwise cover the critical areas with aluminum foil. This is especially true when parked on the flying line in the direct sun for an hour or two.

Fig. 1 shows the method by the EBRC'ers in their Carrier, for bomb dropping. Since the run can be made at high speed, a shift to low speed just prior to the release presents no problem. The brass tubing is secured to the side of the fuselage with the notch face down. The hairpin hook is held within the notch area by the wire through the tubing. Be sure it operates freely and won't bind the motor control; Mount bomb behind gear where it won't get caught and make bomb from weights just heavy enough to fall. Add a silk streamer.

A reminder for working with transistors: don't apply too much heat when soldering them in place. Some transistors will take it, others won't. Heat may be shunted away from the header on the case by using pliers to grip the leads when soldering; maintaining about %" of lead length and doing the soldering quickly and by stuffing cotton around the leads, then soaking the cotton with alcohol or even water. Be sure the leads to be soldered are clean and then get the job done as quickly as possible. If possible, use transistor sockets and then you'll be safe.

From the Convairiety, we learn that R. A. "Dick" Everett set a new world distance record for RC planes on April 12th. Spanning 6½ feet, the 51" long model weighed 5½ pounds empty, was powered by a Torpedo 19 and used a 5-channel receiver. Fairly conventional and boxy in design, the outstanding feature was the gear. It came straight out from the fuselage and then straight down, the tread being about 14 inches. The new distance record is now 37.1 miles and the ground speed was 47 mph.

In an early issue of MAN we will present a series of articles on superhet receivers. The first one will be of the front end' type, adaptable to the WAG TTPW and other tone receivers. The second section will deal with other basic circuits. This particular circuitry has been well engineered, and at first glance might be said to over done. However, we have noticed that consideration has not always been given to the fact that we have many other frequencies other than the six allotted to RC work, all in the same band. There are a total of 28 spot frequencies to consider, in addition to the usual amount of random interference. Superhets will (Continued on next page)



Varicomp Switcher

by RALPH DeCECCO


For reliable "five-channel" operation two Varicomps, just add simple contacts, servo.

► Since the advent of the intermediate class in R/C a more reliable elevator action has been needed, instead of the torque rod system. Because the elevator action is so unstable, many fliers have gone to the more expensive dual tones, the crank arm and more expensive pulse systems. The average modeler cannot afford these systems.

In my opinion this switcher does the trick. Most fliers have Varicomps so by cascading them, with the switcher coupled to a servo, a more reliable action is established. The cost is low, the unit easily made.

You get five channel results with one channel equipment. The unit works as usual, but a more (Continued on page 52)

Finished switcher, left, and Citizen-Ship multi. The two contacts came from a pinball machine, serve; right, switcher parts as listed in text. Two Varicomps are cascaded as any installation.



Radio Control News

(Continued from page 29)
not become popular until articles are published which enable the modeler to build his own equipment, eventhough he may pay just as much for the parts as he does for a finished set. This may be one of the reasons that 465mc has not been exploited as much as it should be. It's the ideal frequency as far as intereference is concerned, but the builder has not been able to build his own equipment.

Fig. 2 comes from the Peoria RC Tattler and the circuit was designed by Hank Chesko for checking tone transmitters. No antenna is needed and the battery should last a whole season. No tuning is needed since the National choke and the capacitor provide broad tuning. No switch is needed because the battery is never connected until the headphones are placed into the normally open circuit jack.


Another item for Simpl/Simul comes from Joe Ballasch, 5309 Big Creek Parkway, Parma O. Fig. 2 shows how two auxiliary controls may be used with S/S. The relays used came from a weather balloon transmitter which you can pick up for about \$1.00 from a number of surplus stores or from ESSCO. Otherwise you can use a GEM 500 ohm relay. The 400mf capacitors (transistor electrolytics) can be obtained from Lafayette Radio.

Want to make your RC gear more rugged? Try a little fibreglass resin over and around the components, especially when mounted to a printed wiring chassis. This method is particularly effective when components are mounted in an upright position. Use about 50% more catalyst in the resin and apply with a brush or small stick. Be careful not to get into flea clips or sockets. We have found this method of conformal coating to work very well.

The Central Jersey Radio Control Club made tests on the new Eveready N46, size AA pencell Nickle-Cad cells. Figure 4A shows the results of this test, performed so as to simulate actual use in a pulse system. The batteries, two sets, were three of the cells connected in series and the load was a Mighty Midget plus a 10-ohm resistor. Pulsing was through regular relay points as set up for S/S, pulse ratefive per second with 50/50 duty cycle. Measurements were taken across one set of batteries and the chart also shows the voltage per cell. As can be seen, these cells will supply power for such a system for two hours. They are rechargeable.

Now let's see how these cells, which are of the non-sintered plate construction.

Now let's see how these cells, which are of the non-sintered plate construction, compare with VO cells which contain sintered plates. The N46's are rated at 450mah, at a 10 hour rate, or 45ma suggested maximum drain. Fig. 4B shows the discharge curve for one Eveready N46 cell having a 100ma load applied. Fig. 4C shows the curve for one VO-500 cell, also having a 100ma load applied. The N46 is rated at 450mah at a 10 hour rate and the VO-500 is rated at 500mah at practically no rate limit. As can be seen, the N46 was good for approximately 160 minutes (Chart B) and the VO-500 for about 320 minutes (Chart C), or about twice the life for the VO-500. These tests were run with three cells of each and the average given in the charts. As stated in previous columns, the sintered plate construction is capable of much higher current drains. The non-sintered plate construction is perfectly satisfactory if used within the limits given. For example, (Continued on page 58)



rod

top

gas bear bals the cem

dop

inel

of t

Star

the

rud

cen

rud

lead

in ma

the


five tha

for

me

par clo att

wi wi on the guarth th



Built for an altitude attempt, 80-in. job, Harald Kurth, Germany, 8 lbs., .60 engine, one channel.

Arvo Arrow, G. Kittner, Germany, 70-in. delta, with K & B .35 power. Weighs 7½ lbs., single channel.



Houdini

(Continued from page 15) rod does not bind at the rear eyelet. The top front cowl block is removed and the gas tank is fastened between the motor bearers with metal straps or blocks of balsa. The cowl block is drilled out for the filler tubes to protrude and then cemented back in place.

Give the fuselage two coats of clear dope, sanding lightly between coats, and then cover with silk. Two pieces of silk are cut out slightly larger than the profile, including the rudder, one for the left side of the fuselage and the other for the right. Start fastening the silk to the fuselage at the nose and, working back toward the rudder, the silk is pulled over one half of the turtle back and cemented to the center stringer. (Wetting the silk with a sprayer filled with water will simplify the stretching and eliminate wrinkles.) At the rudder, the silk is fastened only to the leading edge and the fuselage side running up the trailing edge of the rudder.

The bottom of the fuselage is covered in one piece from the nose to the tail, making sure that all exposed wood is covered with silk. The wing and tail dowels are cut to length and fastened to the fuselage. The fuselage then is given five coats of clear dope, making certain that the pores of the silk are sealed thoroughly. Make the holes and cutouts for the switches and jack. The radio equipment should be small in order that it may be fastened to the sliding tray. My model used a Gyro 22X receiver. The movable part of the rudder is hinged with either cloth or metal hinges and the yoke attached.

attached.

Stabilizer and wing: The stabilizer construction is strong and warpfree. The stabilizer is built on a flat board, making sure the leading and trailing edge are raised so that they are centered on the kxk" ribs. When dry, it is sanded with a large, flat sandpaper block, to a symmetrical airfoil, then covered with silk.

The wing also is made on a flat board and isjued together at the center section.

The wing also is made on a flat board and joined together at the center section with the wing gussets of the prescribed wood. The landing gear is bent to shape, one left and one right, and fastened to the wing through the holes in the plywood gusset with metal straps (tin can stock). A gusset is cemented between the rib and the spar where the landing gear protrudes through the bottom of the wing. After sanding, cover wing and stabilizer with silk and give five coats of clear dope. Paint with colored dope if desired.

A plastic canopy is cemented to the top of the removable cowl block, the block held on to the fuselage with rubberbands. The antenna is attached to the top of the rudder and held taut with a rubberband. Test flying: After field checking the radio equipment and making sure every-

Test flying: After field checking the radio equipment and making sure everything is in working order, do your test gliding. In the original model (which was free from warps) 1/16" right thrust was needed; down thrust is already built in. The model is glided from shoulder height holding it directly in front of the wing with the nose pointing slightly down. Use a running start. When the model glides flat, you are ready for power flight.

With about two minutes of fuel, attempt

With about two minutes of fuel, attempt a take-off. The model tends to stay in a turn so opposite rudder is required to bring it out of the turn. Do not hold signals long as Houdini responds instantly. Get plenty of altitude before attempting to turn so you can familiarize yourself with its characteristics.

The first flight is always the most dan-(Continued on page 36)



Manufactured from all new Hi-Fi quality components, this new receiver is a carrier responsive unit that has been thoroughly field tested for over a year. It incorporates "single-touch" tuning, 2 "twin-matched" transistors, plus a low drain hard tube. The "locked-in" deep etched printed circuit guarantees consistent quality and trouble-free performance. The Spacemaster MK1 can be tuned over all new alloted frequencies.

- Battery Requirements: 22½ V.B., 1½ V.A.
- Relay Operation; .6 MA on idle, rises to over 4 MA on signal for positive relay operation.
- Factory built, tested, ready for operation.
- Metal case enclosure—Wgt: 13/4 ozs, with relay.
- . FULLY GUARANTEED

POLK

Features printed circuit chassis, extended range transmission, 27% freq. & "tuning-eye" for fast, accurate checking, quality controlled hi-tolerance components & specially designed crystal.

E-Z ASSEMBLY KIT \$14.95
READY-TO-USE (less batt) ... \$19.95





ARISTO R/C MULTI-TESTER

Sturdily built, accurate testing unit covering every R/C need ±2%. Full 2%", moving coil type meter. Readings to 1000 MA, 200 V. DC, 100 to 10K ohms. Zero adjusting screw

ohms adjust, black and red test leads with prods supplied. Black plastic case, Instruction book included.

DEALERS JOBBERS. REG. TRADE PRICES . WE EXPORT IMPORT WORLD OVER 314 FIFTH AVE., DEPT. MA 89 , NEW YORK 1, N.Y.



George Aldrich — National Stunt Champion Dennis Alford — Jr. National Champion Woody Blanchard — Open National Champion Henry Spielman — A Top Stunt Modeler Lionel Miborrow — Top So. African Modeler Bob Hunter — F.F. Record Holder Billy Hunter — S Firsts — F.F. 1958 Nationals Jack Moreland — F.F. Record Holder

Riley Wooten — National Combat Champion Bill Arrowsmith — National Combat Champion Art Chambers — King Orange Combat Champ. The Health — King Orange Combat Champ. Mel Flint — West Coast 1 Hr. Ratrace Champ. Dick Williams — West Coast 1 Hr. Ratrace Champ. Gerold Chaney — West Coast 1 Hr. Ratrace Champ. Toshi. Mañsudo — A Top F.F. Modeler

THIS LIST COULD GO ON FOR MANY, MANY PAGES, BUT IT SHOULD GIVE AN INDICATION OF TODAY'S TREND.



The JOHNSON CORECABLE will not direct or spiral, it is more blok resistant and 15% strenger than other cables, Ninety (80) consecutive loops have been put in JOHNSON CORECABLES institute than of castles.



GL-1—STANDARD (LONG)
The JORNESON GLOW-PLUG in generatored to
take 2 Yols — Treet the granting test of 19
law. (41% law. in fast and 91% law. ourself's conference flight). Gave literies and
finetion a close 2 recent of 1811 IN.P.R.
Triple crimped and to villatured 200 PRI.
1,42 ling type.



GA-18—ALL-SPEED (LONG) 2000/2000 (ALL-GPEED) GLGW PLUGS are blead for R/C work, where low BFW is required. Are guaranteed to table a Valle. Element of an eathway NEW alloy of longth long leading finitions resistant comments — Mgh bent resistant. Triple orthup send that will held 200 ft. PRI 4-68 long.

SEE YOUR DEALER TO-DAY

DYNAMIC MODELS INC., FULLERTON, CALIFORNIA

FOR BETTER MODEL BUILDING BETTER FLYING - THE ONLY NAM YOU NEED TO KNOW IS



PREFERRED BY MODELERS...EVERYWHERE!

THE TESTOR CORPORATION . ROCKFORD, ILLINOIS






















THESE 1/2-A MODELS SWITCH FROM CONTROL LINE TO FREE FLIGHT & BACK AGAIN IN A

cach let contains: formed landing ser, push rod, elevator horn, wheels, fell crank, firewall, decals, and all necessary hardware. All parts are completely finished. Only select Grade-Analas is used. Full size detailed plans where step-by-step construction

with many step-by-step construction vatures making it easy to build and

TOPFLITE GAS KITS TOP THEM ALL!

Three terrific planes designed by George Aldrich, America's greatest stunt champion!



Th

the NOBLER CHAMPIONSHIP CONTROL LINE



STUNT

THE "WINNINGEST" STUNT MODEL EVER FLOWN . . . Won More Nationals and International Stunt Championships Than Any Other Model!



these CONTROL LINE COMBAT and STUNT TRAINERS are among America's greatest . . . two of the most successful planes ever designed!

Kit No. N-2

FLITE STREAK \$3.95 Mysels sitts

Engine sizes .15 to .35 Wing Span 42" Wing Area 390 sq. in. Length 28"

1958 NATIONALS WINNER of BOTH Senior and Junior

BOTH OF THESE KITS CONTAIN:

- Full length shaped and notched leading and trailing edges and spars.
 Shaped fuselage.
 Select grade A balsa.
 Printed and precision die-cut balsa and

ARROWJET 24

Top Flite PROP CHART

- rimed and precision dis-cur base and plywood parts. Formed landing sear and push rod. High grade silkspan. Hardwood engine mounts. Complete detailed plans with many step-by-step construction features making it easy to build and fly.

HERE'S WHY THEY'RE SUPERIOR MODELS:

RE'S WHY THEY'RE SUPERIOR MODELS:

1. Full length leading, trailing edges and spars.
Require NO SPLICING, an exclusive feature
for this size and type of model.

2. Assembly is easier, faster—
with perfect alignment.

3. This ligitime construction
of notched spars,
leading and trailling edges allows
you to construct
a symmetrical
wing on a flat
surface without
special jigs, also
making it warp
resistant.



Kit No. N-3 **\$2.95**

Engine Sizes .15 to .25 Wing Span 31"
Wing Area 230 eq. in.
Length 22"

by the makers of famous TOP FLITES and POWER PROPS . . . the Props of Champsi AVAILABLE AT ALL LEADING HOBBY SHOPS

TOP FLITE MODELS, INC., 2635 S. Wabash Avenue, Chicago 16, Illinois

TOP FLITE

The CHAMPS WIN with TOP FLITE & POWER PROPS for the 11th STRAIGHT YEAR!

ALL THOSE LISTED ARE FIRST PLACE WINNERS



1/4 SPEED SENIOR
Edw. Pilkington
Hialeah, Fla.
99.3 mph
Engine: K & B 049
Fuel: This Is It
PROP: 4½-7 POWER PROP
Plane: Original

FLYING SCALE CL OPEN Tom Dean Corpus Christi, Tex.

330 points
PROP: 8-6 TOP FLITE

16 A GAS FF JUNIOR

Bill Hester Sun Valley, Celif. Time: 823.0 Engine: Holland Hornet Fuel: Thimble Drone Racing PROF:

51/4-4 PLASTIC TOP FLITE Plane: Satellite



PAR CLIPPER CARGO OPEN

Lawrence Conever Cedar Rapids, Ia. Wt. Lifted: 137.25 oz. Engine: Thermal Hopper Fuel: Nitro X

6-3 PLASTIC TOP FLITE Plane: Pelican A BAS FF OPEN Charles E. Diller Riverside, Calif Time: 1906.2 Engine: Torp 19 Fuel: K & B 100 PROP: 9-4 TOP FLIYE Plame: Ramrod 600

RADIO CONTROL (MULTI) Beb Dunham Norwalk, Calif. 213.0 points PROP: 11-6 TOP FLITE

MAYY CARRIER JUNIOR Alfred Genzales Woodside, N. Y. Time: 308.02 PROP: 10-8 TOP FLITE



STUNT OPEN Robert Randall Indianapolis, Ind. 548.5 points Engine: Fox 35 Fuel: Fox Super Fuel PROP:

18-8 NYLON TOP FLITE Plane: Original

NAVY CARRIER SENIOR Robert Hominway Audubon Park, N. J. Time: 490.99 PROP: 11-8 TOP FLITE

FLYING SCALE CL JUNIOR Jim Yeasey Evansville, Ind. 244 points PROP: 11-4 TOP FLITE

RADIO CONTROL FLYING SCALE William F. Bertrand Allen Park, Mich. 88 2/3 points PROP: 12-4 POWER PROP A GAS FF SENIOR Ray La Heed Omaha, Nebr. Time: 996.0 PROP: 8-4 POWER PROP

PAA CLIPPER CARGO JR-SR Denald A. Gurnett Fairfax, Ia. Wt. Lifted: 151.25 oz. PROP: 6-3 NYLON TOP FLITE

1/2A GAS FF SENIOR
Dick Mathia
Dallas, Tex.
Time: 1153.0
PROP: 6-3 TOP FLITE.

R.O.W. GAS OPEN Vic Cunnyngham Baldwin Park, Calif. Time: 824.0 PROP: 8-4 TOP FLITE

BC GAS FF SENIOR Charles Gillland Tulsa, Okta. Time: 1096.0 PROP: 11-4 TOP FLITE



R.O.W. GAS JUNION
BILL HEARLEY
SUN VAILey, Calif.
Time: 737.2 (New Record)
Engine: Torp 23
Fuel: Ohlsson 200
PROP: 8-4 TOP FLITE
Plane: Satellite

COMBAT OPEN
William F. Arrowsmith
Rochester, N. Y.
PROP: 10-6 POWER PROP

FLYING SCALE FF OPEN Karl Spielmaker Grand Rapids, Mich. 132-2/3 points PROP: 6-3 TOP FLITE

MAVY CARRIER OPEN Stephen Babin Fairview Park, Ohio Time: 463.0 Engine: McCoy 60 Fuel: Mitro X PROP: 10-0 POWER PROP Plane: Original

famous TOP
FLITES and
POWER PROPS
and YOU'LL be
right up there
with these
Nationals

winners!

Choose these

e are th

NATIONALS

GLENVIEW, ILLINOIS



JR NATIONALS HIGH POINT WINNER Dennis Afford San Diego, Calif. PROPS: TOP FLITES Ward is all as greater



New ½ A Receré
R.O.W. GAS JUNIOR
Bart Balleatine
N. Hollywood, Calif.
Time: 11-31.2
Engine: Holland Hornet
Fuel: Thimble Drone Racing
PROP:
6-3 NYLON TOP FLITE
Plane: Satellite 330

TOP FLITE

TOP FLITE MODELS, INC., 2635 S. Wabash Ave.—Chicago 16, III.

Dealers - Write For Info On These Hot Items

OS Mark II Jet OS ENGINES - GLO

OS ENGINES - GLO
Max 35 Combatnik
Max 29 New Series
Max 15 II
Pet 09
Max 35 R/C
Max 29 R/C
Max 15 R/C

.15 LAP 88 "V" Seri .19 LAP 88 "V" Seri .29 LAP 88 "V" Seri .35 LAP 88 Combat .60 RING 88 G-24A .35 LAP Ret Reco...

.06 88 lap. .09 88 lap. .15 88 lap. .15 Plain 8 15 Diesel 6 .09 88 R / C

OTHER DIESELS — EXCLUS Oliver MK III Mod. 15*... Oliver MK III Sed. 15*... Devid-Anderson .06... Frog .15 IIII... Frog .049 "B0" Frog .049 "B0" Frog .049 "B0" Frog .21 cu. In. Diesel

CONTROLAISE R/C

Hand Held-Assem & Ant * 10.05 SM-3V No. 3 Volt Transistorized Tone Receiver with Relay* 29.95 HN-T-CW Transmitter — Both Tone and CW, Assembled and

OS R/C

SHAK

WORLD ENGINES SILK per yard (extra fine, extra fine). White... 89 [] Red... 1.00 Yellow 1.00 [] Orange 1.00 Green 1.00 [] Dk. Blue 1.00 Lt. Blue... 1.00

PRED SANKS OS 40 OHM 5 Channel ... 10,95 OS 40 OHM 8 Channel ... 12,95 OS 40 OHM 10 Channel ... 16,95

ESCAPEMENTS

OS 4000 OHM OS 100 OHM OS 50 OHM OS 4000 OHM

5' Antenna Club-Pak*



OS .09 Cu. In. Gla. \$4.95

ould like to beldly thrust out and state that the OS .099 has more sheer powe isan any other .099 glo (our pinion). OS .099 is equipped tith a 2-3 v. plug for extreme asy starting for beginners. ngine will not run backwards.



ombet version shown has one rige rare hall bearing, the rat oversion \$17.95 also has out hall bearing. These en-ries are equipped with a pra-re firting on the front housing give you timed pressure back the traft. (Sand 10 for our issure sheet.) Will kick yorm with 13/5 for heavy Astro-20, Clasy features sind. coller five lock, doal inserts, pr. fitting of also plug.



setrolaire SM-2\$14.95 Mr. Controlaire (Jack Port) tells Art. Controllating Clack Port) fells me he is not gaine to confinue to make these terrific plot confinue to make these terrific plot confinue to make these terrific plot fells confinued to the confinue to t



ant \$2.95 OS 25N Escape

Here is a high quality escape Here is a high quality escape-ment—again as exensitions of price. Escapement has ball bear-ing spindle mounting. The claw is of brass and the escapement lever is steel. Operation 3v. (self murrislizing). Pictured with the OS Pet .099 are the OS re-lays. Note we will self the lays. Note we will self the lays. Note we will self the self-sers over dealer first



Bennett Servo\$13.95 W/E Diesel Fuel Pint ...\$.90; Gel....\$5.50 my Hobby Supplies Ltd.

WORLD ENGINES

8206 BLUE ASH ROAD CINCINNATI 36, OHIO

gerous one and the model should be flown with caution. Study the flight with the power on to see if the model is flying straight with no signal; if not, the thrust should be adjusted to the left or right opposite the turn the model takes. If the model has a tendency to go left or right in the glide the rudder is adjusted for a straight glide. (Note glide turn in order to know which adjustment is first—Editor.) If the model has a tendency to stall under power and not in the glide, additional down thrust may have to be added by down thrust may have to be added by shimming up the motor mount at the rear. In case the model stalls in the glide it is either tail heavy (Not if the CG is where specified—Editor), otherwise positive incidence is put in the stabilizer. This is done by inserting thin balsa shim between the top trailing edge of the stabilizer and the fuselage. All thrust adjustments and incidence changes should be done gradually. cidence changes should be done gradually.

With a little patience and a lot of practice you will find that Houdini lives up

to its name.

The Tri-Traveler

(Continued from page 10)
a right and left set. The wing struts are held to the bottom of the wings by means of 3-48 bolts and blind nuts. The wing struts are held to the fuselage tabs by a small cottor pin which will enable the struts to pivot at this point. Before covering your model, we suggest that you scallop bulkheads B and C between the stringers so that the covering will not stick to

ers so that the covering will not stick to them when doped.

The original model was covered with light weight Silkspan, which smooths out with four coats of thin, clear dope. All the surfaces can be covered in a normal man-ner except for the vertical fin and the top of the fuselage. To cover this portion of your model, we suggest that you cover one side of the vertical fin and half of the top side of the vertical in and hair of the top of the fuselage with one piece of wet Silkspan. This should form a graceful fillet which is a distinguishing feature of the Champion Travelers. The cowl and wing struts are also covered; this will enable you to fill the wood grain much faster when doping. The tank is made from a lipstick holder.

The original model is white with blue

The original model is white with blue trim. Use wood filler on cowl, struts, and planked portions. If white or other light color, keep colored dope fairly thick. A very light sanding between coats with #400 wet-or-dry paper removes most of the brush marks left by thick dope. Thin the last colored coat for added smoothness

To form the windshield, carve a mold from a block of sugar pine and sand it very smooth. Take a piece of .030 thick celluloid and heat it until it becomes pliant—be careful not to overheat it. Pull the heated celluloid over the sugar pine mold until it forms a graceful canopy. Trim off until it forms a graceful canopy. Trim off the excess material from around the edges and fit it to your model.

and it it to your model.

Add the windshield and side windows after the second coat of colored dope. Mask off the portion of the windows which do not get doped and then proceed with the finish. To add the trim color, start by masking a border stripe 1/16" wide. Apply two coats of the trim color. When this has dired thoroughly amount to making a portion of the process of the trim color. When this has dired thoroughly amount are accounted to the process of the trim color. two coats of the trim color. When this has dried thoroughly, remove the masking tape. Add the solid fill-in trim, by masking off another border 1/16" in from the original stripe. Apply two coats of the trim color and carefully remove the masking tape, leaving the base color for the pin stripe. Your finished model should balance where shown on the plan. It should also be free of any warps. The original model was stable in both right and left power turns. However, we recommend a left-

turns. However, we recommend a

hand power flight pattern. A slight amount of right thrust may be required along with the downthrust. Do not attempt to control the power pattern of your model by turn-ing the rudder. The little Champion Tri-Traveler should ROG and climb at a very slight angle to the left at half-power with a 6-2 or 6-3 propeller.

Dizzy Bee

(Continued from page 21)

will need two pieces of basswood as specified. One for the wing, the other for the crutch; two balsa wood blocks for the engine cowling; plywood for the tall; and a cast aluminum speed pan. Dizzy Bee uses cast aluminum speed pan. Dizzy Bee uses the L & H speed pan from the L & H Hobby Shop, Mesquite, Tex. Finally you will need a Class B Speedmaster Monoline control unit. Although a Fox 29X is used the new Dooling 29 can be installed if desired with minor changes.

Fuecias: Start with the pan by filing the outside with a course file to remove any pits or rough edges, then use a smooth file to finish. Using \$270 wet or dry, sandpaper the surface until smooth, then rub to a high finish with DuPont \$7 rubbing compound.

compound.

The pan is drilled and tapped for the hold-down screws. Use a \$43 drill, then tap the holes using a \$4-40 tap. Be sure in locating the four engine mount screw locations that you allow for a slight left-thrust adjustment

For the fuselage crutch select a piece of For the fuselage crutch select a piece of straight grain basswood or pine and, using the pan as a pattern, draw the outline and cut out with a bandsaw or coping saw. Refer to the drawing for the inside lines of the crutch. Pencil these lines onto the fuselage block and cut out this inside por-

De

de wi WO

g sig

the

-1

wi

re Se

Carve the underside of the crutch to clear the engine shaft housing and carburetor, allowing the crutch to set against

the pan.

Wing: Select a straight fine-grain blank
of basswood or pine, remove the leading or basswood or pine, remove the leading edge portion, then spot glue it back in place and allow to dry overnight. The wing planform is drawn on the wing blank or the pattern used, also the outline of the wing cutout.

Taper the underside of the wing from the root section at the fuselage joint to each wingtip. Leave the wingtips as thin as possible. Carve and sand the airfoil into as possible. Carve and sand the airroil into the wing. Separate the leading edge portion of the wing from the larger portion by parting the cement-tacked center-line joint. Carefully cut and sand the groove in both

Slip the control unit into place and adjust so the tubular stem of the control unit just so the tubular stem of the control unit extends exactly centered in the grooved passageway. Drill holes through wing and lasten control unit mounting bracket with suitable machine screws and nuts. When tightening screws, make sure the control unit remains set with the tubular stem in perfect alignment with the grooved passageway. Replace the the leading edge section of wing. When cementing, there is the possibility that cement may be pressed into the passageway, around the tubular stem, for instance, which, when dry, can cause drag or binding. Use only enough cement to do the job and then rotate the cam a few times to make sure the tubular stem has not become cemented in the groove.

Now drill a 1/16" dia. hole through the wing to receive the bellcrank pivot pin. Adjust the pin in the hole so the bellcrank will move freely and fix pin into place by soldering on the opposite side. The bottom (Continued on page 38)

CARL GOLDBERG BRINGS YOU.



Dear Modeler: Our new Spaceman Trainer is really the plane to learn with. A beautiful, smooth flyer - yet designed RUGGED for beginner's needs. For instance, the landing gear is tough 1/8" diameter genuine music wire, held in place by an entirely new, simple shock absorbing method. And notice how the streamlined plywood doublers come back to the middle of the wing for extra strength. The controls have two positions—"gentle" to get you over those first flights, and "active" for wingovers and zooming up and down. It's designed particularly for the new Cox Thimble Drome 15 and Fox 15 engines, and has been flight-tested with the powerful K&B 23 as well. Simple to build because the structural parts are all die-cut balsa and plywood—no paper covering. In addition, the kit has all the hardware, screws, nuts, washers, wheel retainers, etc., a hard aluminum bellcrank and bushing, formed landing gear and tailgear, wheels, large attractive decal with all numbers, Spaceman figure, rudder decoration, pilot head, etc., engine bearers, nylon for hinges and reinforcing, and a fully illustrated clear step-by-step Plan, including instructions on Learning How to Fly. See your dealer now for this fine kit - a really big value at only \$2.95.



RANGER 30 - Die-cut balsa. 30" span for .020-.049 engine. \$1.95.



\$TUNT MAN 23 - Die-cut balsa. 23-1/2", for .049-.09 engine. \$1.98



SPACE JET 21 - Die-cutbalsa. 21" span, for .020-.049 engine . . \$1.69



SWORDSMAN 18 - Die-cutbalsa. 18" span, for .020-.049 engine \$1,49





\$1.00



SHOESTRING RACER - All die-cut balsa, rub-ber-powered, 18" span. Complete. \$1.00



SPIRIT OF ST. LOUIS - A rubber-powered miniature duplicate, 21" wingspan. \$1.00



RANGER 21 - All die-cut balsa parts, rubber-powered. 21" span beauty \$1.00



CESSNA 180 - Rubber-powered favorite, all balsa, 21" span. The champion of business liners \$1.00



P. S. The easiest way to get these planes, of course, is to see your dealer. If no dealer near you, or he doesn't have them, send me cost of plane plus 25f each for postage and packaging. Better yet, send cost of any three and I'll pay the postage!



GOLDBERG MODELS CLAREMONT . CHICAGO 9848



FOR BEGINNERS!

FLIGHT TRAINER

Kit S-16. Wing Span 24". For .09- .15 Engines Designed especially for beginners in control-line flying!
As completely prefabbed as a kit can get . . . a beginner
can put it together in less than two hours! All wood, rugged enough to take plenty of punishment, extremely

Completely carved wings and body, die-cut tail surfaces, finished landing gear including wheels, plywood parts for control system, etc.

FOR RADIO CONTROL EXPERTS!

PIPER CUB J-3

15 of

trol-li best

asse

der

hau

the

Rer

sea

the a s bac

oth

of

the into

of

star

top

ton

The

he

pin

ruh COV

ing

san

the

rais

abe

cer

tak

Kit FS-6, Wing Span 54". For .09-35 Engines

Especially designed for radio control, also turns in remarkable performance as free flight or control line models are beautifully die-cut and shaped, internotched for fast, accurate construction. Easy to fly . . . complete flight instructions included!

Fully prefabbed of balsa and plywood, with carved lower nose cowling, formed alumi-num front cowling, authentic insignia, etc.



NEW! SILVER PALLADIUM Contacts

Here's the sensitive and reliable tiny mite, now with better arc suppression. contacts won't tarnish, corrode, or oxidize. Harder, wears better. More resistant to

welding" or "sticking" of points. Extra tie points for resistors or condensers.

Weigh Less than 1/2 ez. Size: 3/4 H. 17/32 W. 1-1/16 L.



JAICO Products At Your Dealer

RELAYS 1921 W. HUBBARD

M.E.W. JET ENGINES

M.E.W. 307 JET ENGINE



Powerful, 5 lb. thrust 3 in. dia. x 201/2 in. long, burns gasoline, complete with spark plug.

M.E.W. 601 JET ENGINE

6 in. long, easy to assemble, \$1.95 prepaid

MINNESOTA ENGINE WORKS

5600 N. Hamline Ave., St. Paul 12, Minn.

of the cam-follower pin should have a slight clearance between the bottom of the groove in cam so that it will move freely; the bellcrank may be bent up slightly for clearance, if necessary.

The wing-tip control line bearing is formed of a short piece of brass tubing about %" I.D. by %" long. This tubing is flattened to an oval shape and securely fixed and imbedded into the wing tip

with cement; then sew several loops of \$50 thread around it for additional strength.

The wing now is finished, sanded and the trailing edge brought to a sharp edge.

Locate and then cement the wing to the Locate and then cement the wing to the fuselage crutch. Make sure to rotate the wing as shown. This will locate the wing-tip control line guide about %" ahead of the balance point when the model is completed.

After locating, drill and tap the pan for the fuselage tie-down screws. These hole locations are transferred to the fuselage

locations are transferred to the fuselage crutch and drilled with a \$35 drill.

Attach the wing and crutch to the pan with flat-head \$4-40 screws, then taper down the crutch to match the profile or side view. Use 3/32" medium hard balsa to cover the open portion of the crutch. Note that the cover is cemented inside, flush with the crutch walls.

Cowling: Use two pieces of medium-grade balsa. Curve the cowling as shown, sand the inside and apply two or three coats of Ditzler metal primer. After the cowling parts have been finished on the

cowling parts have been finished on the inside, locate and cement them into place.

The top of the cowling is carved, finished on the inside, and cemented into place.

Tall: To construct the "V" or "butterfly" tail, draw the outline on a 1/16" birch plywood and cut out. The leading edge is sanded to a round section and the trailing

edge to a sharp edge. Draw a center line, cut the plywood in half, and remove the elevator portion from the inside half. Cement the stabilizer halves together on the 1/16" plywood platform and allow to dry overnight.

The elevator horn is made from .040 dia. piano wire. Bend this as shown, then sew it to the elevator with \$50 thread. Attach the elevator to the stabilizer with cloth hinges. To insure a stronger joint at the "V" section of the stabilizer, a 1/16" thick plywood plate should be cemented in place. Make the necessary cutouts for the place. Make the necessary cutouts for the elevator control-horn movement. The tail assembly is held to the pan with \$4-40 flat head screws. Use a \$43 tap drill for the holes tapped in the pan and a \$36 drill for clearance holes in the tail.

With the tail assembly attached to the pan, the notch is cut out of the fuselage to clear the tail. The rear hold-down screw crossbrace is located and cemented into a local tasks and teaches the control of the second teaches and teach place. Locate, then drill and tap the pan for the \$4-40 rear hold-down flat head

Finish: For a real fuel-proof finish it is suggested that you use Ditzler primer coat and a colored Ditzler auto enamel. The general practice is to give the model two or three coats of primer thinned out about 50%. allow to dry from two to three days, finish sanding, and then spray with the enamel which should be thinned out about 40%. Allow the finish to dry for three or four days before rubbing with a rubbing compound.

compound.

Engine: The Fox 29X engine has considerable increase in rpm when the load is removed as it becomes airborne. This means that needle valve settings are critical. However, this can be solved by experimenting with different sizes of inserts



in the carburetor. A 40% reduction seems to be best.

For other modifications completely disassemble the engine and remove the cylinder liner from the crankcase. File the exhaust stack flush with the case and curve the front and back of the exhaust stack. Remove any burrs or loose pieces of metal from the inside of the case. The four-screw sealing area on the crankcase should be very lightly filed with a smooth file and then polished on a piece of ground glass or a surface plate. This will seal better the backplate.

backplate.

The crankshaft requires no reworking other than advancing the timing. This can be done by grinding away the leading edge of the port opening in the crankshaft. As of the port opening in the crankshaft. As the grinding is being done, insert the shaft into the crankcase and check the degrees of opening. The chankshaft port should start to close the carburetor at 45° after top-dead-center and open at 10° after bottom-dead-center.

The crank-pin should have about 1/32 in ground off the end and then polished. The bottom of the connecting rod should be nled to match the length of the crank-

be nled to match the length of the crankpin. These two things are done to prevent
rubbing and grinding away of the rear
cover when a starter is used. The connecting rod can be lightened considerably by
filing away all the square corners, then
sanding and polishing.

To retime the opening of the exhaus
port, use two cylinder-liner gaskets under
the flange of the cylinder liner. This will
raise the bottom edge of the exhaust port
above the piston when it is bottom-deadcenter, so file this edge down until it is
flush with the top of the piston. The intake port is left "stock," other than adding
a very slight radius around the port edge

on the inside of the liner.

The underside of the head was scalloped out to add more combustion area and sharp edges were removed around the glow-plug area. The connecting rod wrist pin should have each end filed or sanded to a radius as much as possible and polished.

Before assembling the engine, be sure all the parts are clean and free from any metal filings. Use one head gasket between the cylinder head and the flange of the cylinder liner. Assemble the engine and thor-oughly tighten all screws. Do not disasem-ble the engine again unless it becomes necessary to clean it. Be sure when mounting the engine to the pan, that the engine sets flush against the mounts, otherwise a bind will result on the shaft when the

mounting screws are tightened down.

Allow for several runs before expecting peak performance. Hot or lean runs on this engine do not seem to effect its performance and it appears that at least 20 to 25 good flights are needed to bring the engine up to peak operation.

Before test flying check the controls for binding or rubbing. The controls should operate freely for good take-offs and land-

Check out the control system to see that Check out the control system to see that you have at least 10° up movement and 10° down movement of the elevator. Be sure there is no rubbing of the elevator push rod or that the control unit bellcrank doesn't rub against the tank.

Use a 7" dia. 10" pitch Tornado propeller cut down to 6k" dia. with a little more pitch sanded into each blade. For maximum performance in record attempts use

imum performance in record attempts, use "This is it" or Franny's Hi Nitro contest fuels. Dizzy Bee is very stable and easy to fly. Don't be surprised if you find yourself breaking the class "B" record.

Available now!

The first complete Illustrated Guide



Missiles and Rockets

by Stanley Ulanoff

This invaluable guide for all missile-model enthusiasts features action photos, scale silhouettes, specification and data tables (manufacturers, types, dimensions, guidance system and power plant diagrams, performance, armament, etc.) and full descriptive text on 65 basic missiles, rockets, manned research aircraft and space vehicles. Written by a professional missile model designer, this expert, authoritative book is the only volume of its kind - a magnificently illustrated album that no model builder can afford to be without.

\$3.95 at all booksellers DOUBLEDAY

NOW-of HAWK KITS for



Send 10c for full color catalog on other fine HAWK MODELS

4600 North Olcott Ave. MODEL CO., Chicago 31, Illinois



"MARK II" SUPER-COMPOUND **ESCAPEMENT SERVO**

World's largest selling escapement for full rudder and elevator control plus motor control switch. Tops in reliability. Easy to install and operate. Handles any size plane. Complete with actuating arms and linkage. Rust and corrosion proof. Rubber-powered. Low current drain; 8 ohm coil, 2 to 3 volts.

No. 886 COMPLETE . . . \$7.95 By the makers of the world-famous BABCOCK R/C SYSTEMS Transmitters • Receivers Escapements • Models See Your Babcock Dealer . . . or write for complete Catalog.

Babcock MODELS INC. COSTA MESA, CALIF.

Souped-Up Pre-Fabs

(Continued from page 20) fine. Make it from tough 1/16" sheet or

fine. Make it from tough 1/16" sheet or plywood since the plane needs weight in the nose anyway.

The plastic nose-button or prop bearing should be used. Drill the nose block to take it snuggly. Have several buttons all the same size if you want to try different props. Put them on the prop shafts, bend the shafts to hold the rubber. Then to switch props, all you do is pull out nose button from nose bulkhead after rubber is unhooked. No shaft-bending at the contest. For winding, pull entire nose block out front, unhook rubber and place on winder hood. When wound, hold rubber one inch from end, let winder unwind, and put resulting loop of rubber back on prop shaft. But don't have lubricant on your fingers. PROPELLERS of all types have been tried. One theory is that fast turning props of smaller area give less torque reaction.

tried. One theory is that fast turning props of smaller area give less torque reaction. Norman Getzlaff uses this theory with some novel ideas of his own. He puts "scallops" in the trailing edge. They let the prop turn faster, he says.

Getzlaff's block is illustrated here. He found that old props worked better. Floor landings had knocked off the leading edge tip corner. Then he cut off the leading-edge tip corner of new ones and obtained the same results. So the design is followed. He prefers to plane off both rear and front faces of the prop blank and keep the blade angle in the center. He cuts the block by exacting methods using arcs.

blade angle in the center. He cuts the block by exacting methods using arcs. Standard hand-carved props give good results. But Mike Karlak simply cuts two blades from sheet wood, joins them at right angles or at 45 degrees to the shaft, and gets nearly three minutes.

RUBBER POWER for prefabs ranges from two loops of %-inch flat to two loops

of 1/16-inch square Pirelli. Some braid their strands. Everybody uses plenty of slack—about twice the fuselage length. Remember that you can get more power from a shorter motor, only it won't last as long. Or you can reduce the power of

No. 503...

To whic relat

the a

and

a sid If a will or e

cube

of ty sq. i to pr

Ou thing

ozs./

the s ounce get in squar two t inche duces

and : ounce

Since tional

mensi eight one,

root (

side o

threeever, tively to we by tal reduc then this to

In ing th weigh area 3 cube

cube

for th

also b or 64.

mensi

2/3 p

ponen

the ar

seem

enable

of the

tual an 8"

pariso

the cu

(one

puttin by cu

result.

"All E

Are y

MODE

Sinc

we rectly

In

as long. Or you can reduce the power of a given motor by making the loop longer. The main objective is to have the model land with some winds left in the motor. If it runs out at high altitude, the motor is too strong. If too much power remains after landing, rubber not strong enough. Maximum turns—%" flat brown rubber; 2 strands, various lengths; 115 turns per inch (21-1 winder)

Rubber		Total	Wind
10			150
15*			725 340
17"		18	955
18*	***************************************	20)70 185
20*	***************************************	25	300
21"	***************************************		115 375
-	***********		

These figures are for well-lubricated, fresh rubber of the best grade in peak condition. If your rubber is less than that, don't expect to get maximum turns. Reduce

to 100 turns per inch for safety. Four strands of %"-flat brown Maximum turns—3/32-inch flat, two strands (one loop), 130 turns per inch; Four strands (two loops), 94 turns per inch. (Reduce to 90 to allow for poor grade of rubber.)

14" 15" 16" 17" loop - 1260 turns - 1350 - 1440 1530

MODEL AIRPLANE NEWS . August, 1959

Wing Loading Is Three Dimensional

(Continued from page 23)

To clarify this, let's taken an example, which may be more familiar to us all: The relationship between the side of a cube, the area of any one side, the cube's volume, and weight. Consider a cube two inches on a side which has a weight of eight ounces. a side which has a weight or eight ounces. If a side is two inches, the area of a side will be the square of two, or four square inches; the volume will be the cube of two, or eight cubic inches. In describing this cube, we might say that it has a "loading" of two ounces per square inch (8 ozs./4 sq. in.). But if we used this relationship predict what the area need be to have a cube of the same material to weigh 64 ounces, our answer is obviously incorrect.

Our erroneous reasoning might go something like this: The large cube is to weigh eight times as much as the small one (64 ozs./8 ozs. is 8). The large cube will have the same "loading" as the small one, two ounces per square inch (here's where we get into trouble). To find the area needed to "support" 64 ounces at two inches per square inch, we merely divide the 64 by two to arrive at our new area of 32 square inches. Taking the square root of 32, produces the value for one side, or 5.66 inches, the volume being about 181 cubic inches.

In correctly reasoning the above problem, and arriving at a cube size to weigh 64 ounces, our thinking should run like this: Since the volume will be directly proportional to the weight (both are three dimensional), and the 64 ounce cube will be eight times as heavy as the eight-ounce one, it will also have eight times the volume, or 64 cubic inches. Taking the cuberoot of this will give us the value for a side of four inches (4 x 4 x 4 is 64).

In our incorrect solution to this problem, we "mixed apples and oranges" by directly comparing a two-dimensional to a three-dimensional thing. Let's assume, however, that the volume was difficult to measure, whereas measuring the area was rela-

were, that the volume was difficult to freestere, whereas measuring the area was relatively simple. How can we compare area to weight? Merely by expressing the area in three-dimensional terms. We can do this by taking the square root of the area, thus reducing it to one dimensional terms, and then cubing this figure. We can express this two ways: $\sqrt{\text{area}}$ or area 3. In the problem above, our solution, using this expression.

ing this method, would work this way: The ing this method, would work this way: The weight will be directly proportional to the area ½ values, which, for the two-inch cube will be √4 °, or 8. Since the large cube will have a weight eight times that for the smaller cube, its area ½ value will also be eight times that of the smaller cube, or 64. To then put the 64 back in two-dimensional terms, it is necessary to apply the 2/3 power to it in order to cancel the exponents: *√64 is 4. Four squared is 16, the area of the 64 ounce cube. This may seem like the long way around, but it did enable us to compare the weight and areas enable us to compare the weight and areas of the two cubes, without resorting to actual computations of volume. Utilizing an 8" circular slide rule, this type of com-

parison is quite fast.

Since a direct scale-up was involved in the cubes, we could have compared a side (one dimensional) to the weight, by first putting the side in three-dimensional terms by cubing, and thus arrived at the same

"All right," you say, "So what?"
Are you planning on building an FAI

(Continued on page 44)

SEND ONLY \$2.95

FOR THIS \$11.95 BOOK

(remaining \$0.00 to be paid \$3.00 per month)



Only book that contains not only all the Aircraft flown in World War One, but also hundreds of photos and drawings of rare and experimental type so hard to find. Book is cloth bound, 234 large 11 x 8 3/4" pages. 80 full page 1/72" scale plans shown of planes from USA. England, Prance, Germany, flat, etc. Full page photos of Squadron line ups, plus half page and third page photos of each plane, in all over 200 photos. Full Dimensions, Weight, Armament, Performance, Power Plant, and constructional details are given for each plane, plus its Operational History. This book is of great interest to any who have flown these old planes, to any who are interested in the building of true scale Museum type models, and to those who simply like to see top notch photos and write ups about these, now rare, aircraft. This book is a collector's item. Book weighs almost 2 pounds, it is sold on a money back guarantee, after you have paid for the book in full, if not satisfied with it we will grant a full money back refund within 10 days after you have received it.


SAMPLE PAGES and Circular about the book above256

SAMPLE PAGES and Circular about the book above25e

CHECK OFF THE FORM BELOW and PRINT your name and address in column this ad add 25c, postage per book,

Please send me the 14-18 book above, I enclose full \$11.95 Please place me on order for the 14-18 book above, I enclose only \$2.95.......I agree to pay the remaining \$9.00 in three monthly payments of \$3.00 each

"AEROMODELLER" magazine contains scale plans. Year sub. \$4.50. Sample 25c Gull Model Airplane Co. 10 E. Overlea Ave., Dept. M2 Baltimore 6, Md.



NE R/C EQUI

FACTORY BUILT . TUNED . TESTED READY TO OPERATE . FULLY GUARANTEED



MC Model 100 T

- · Absolutely reliable
- 6007 detector plus 2 transistors
- · Printed circuit · epoxy glass board
- · Weight only 11/2 ounces

AYHAWK

2120 (E) TENNESSEE LAWRENCE, KANSAS



TRANSMITTER ... MC Model 250 T

- · Stable, reliable circuit
- · Standard 1,000 cps tone
- Frequency choice 27.255 or 26.995
- 54" aluminum antenna steel case

SPECIAL COMBO OFFER

ONLY \$39.95 POSTPAID (less batteries)


ORDER YOUR COMBO 'T' TODAY Write for free literature on the complete MC line.

Dealer inquiries invited



CESSNA 172.....\$2.95 Here's the newest Cessna pri-GESSNA 172......\$2.75 Here's the newest Cessna private plane that you can fly yourself . . . by U-Centrel, ef course, using just about any ½2 gas engine (up to an .074). Performance-wise you'll find this model just about the snappiest you can fly—regardless of price. And—note the trim, slim, uncluttered lines of this scale beauty. Wingspan is a full 21 inches. The kit is all prefabricated . . . with a pre-carved balsa fuselage and all parts already cut, fermed or shaped for you.

CYCLONE ... CYCLONE\$2.95 U-Control fans . . . get ready to fly up a storm! You're looking at our brand new "CYCLONE" . . . 7 ounces (with the engine, that is) of sheer "CYCLONE"... 7 ounces (with the engine, that is) of sheer flying dynamite. The enormous wing area of this model (21" span) provides tremendous "lift" that lets you take off realistically... fly every stunt in the books... then land as softly as a feather. You can power your very ewn Cyclone with any small bere gas engine .035 to .099. And—assembly of the model is a cinch from the all prefabricated kit (with our pre-carved balsa fuselage, too).





52

CURTISS HELLDIVER





COMBAT MASTER







PIPER CUB RESCUE

every

AT YOUR DEALER e specific, say SCIENTIFIC

If no dealer is svallable, add 20 (postage & packing) to cost of m SCIENTIFIC MODEL AIRPLANE COMPAN 113 MB MONROE ST. . NEWARK 5, N. J.



gingPtM \$1.69 PAN: 14" For .020 to .049 Eng. trand new profile stant model with a big M sg. lock wing. Control flow. 41 perfection.



AIRCOUPE \$2.50 SPAN: 18" For .020 to .074 Eng. A real "beaut" of a model. It's authentic scale . . for U-Control flying. Prefabbed. Carved fuselage.





Gee Bee Sportster \$1.95 SPAN: 18" For .020 to .074 Eng. Brand new U-Cantral scale model. An excellent perfemer. Kit is all prefabricated. Carved fuselage.



Half Plat Recor \$3.91 LENGTH: 9" For "V/A" Sex En New, Improved madel. Speaks on

SEND FOR OUR FREE CATALOG

It's brand new! Just off the press. See your dealer or send press. See your dealer or send a postal card for your free copy. Features all our exciting gas powered models airplanes, boats and race cars. A must for every modeler.



Greatest Values! Top Performers! Best Looking, Too!



Stuke Dive Rember \$2.50 SPAN: 18" For .826 to .074 Eng. Sanething newl This U-Central thriller drops bomb as you 152-refathed with carved dealings.



\$1.95 SPAN: 18" For .020 to .074 Eng. One of our hettest looking and performing U-Control planes. Styled from Goodyear Racer. Prefabbed.



No. Am. "Texes" \$2.50 SPAN: 18" For .020 to .074 Eng. Authorito scale model of the traff ATE Trainer, A top-notal "fly in passaff" model. All preferance



P-40 Flying Tiger \$2.50 SPAN: 18" For .039 to .074 Eng. Our popular U-Control model of this Curtiss World War II fighter. Prefabbed w/carved fuselage.



SPAN: 18" For .020 to .074 En



Speedboot \$2.95 Powered OUTBOARD Eng. ength 20", Beam 8" e mabegany venous bell. A poedster, All grefabricates



"ELDORADO" \$1.69 14½" Long. For Elec. Outld. Mtrs. Fast, sleek speedboat — really modern w/wrap-around windshield & swept wing fins. Prefab.



Buckeyo Jr. Carbin \$3.75 Far "1/2 h" Eng., Electric Maters Sard's our stock colle craiser. Hee. a remarable bales colle, 16" evered hallo half - 1807, complete.



F4U-5N "Corsair" \$1.50 SPAN: 18" For .020 to .074 Eng. Profile fly-it-yourself model of this famous WW II fighter. It's U-control, files like a fram. Profab.









ZIG-ZAG \$1.69 SPAN: 18" For .020 to .074 Eng. Fast! Colorful! Here's a red but U-Control model with real get up and get Prefab. Carved fuscings.



LITTLE MUSTANG \$1.95 SPAN: 18" For .020 to .074 Eng. Famous escort fighter model. Completely prefabbed. Features carved balsa fuselage, formed balsa wing.





LITTLE STINKER \$2.95 SPAN: 16" For .020 to .074 Eng. "Pitt's Special" championship stunt flyer. Highly colorful model. All profabbed kit.





T-28 TRAINER \$1.50 SPAN: 18" For .035 to .074 Eng. Morth American's U.S.A.F. standard training plane. New you fly it U-Control. All prefab., profile model.





AT YOUR DEALER ... be specific say



Cossan 182 Tricyclo \$1,95 SPAN: 18" For ,839 to ,874 Eng. Scale Gy-ti-pourself maded of tempos private plan. All produc

SCIENTIFIC MODEL AIRPLANE COMPANY

113 M8 MONROE ST., NEWARK 5, N. J.

more AIR POWER with TORNADO

Yes, undisputed King of model air power these days is NYLON! No finer material for max. thrust delivery from engine-plus-propeller! Beats wood in FLEXI-BILITY and durable resilience. HOLDS SHAPE and thrust at top RPM's. Practically UNBREAKABLE . . . survives even ground loops and belly landings! TEMPERATURE-PROOF — doesn't "brittle" at sub zero - nor soften in tropic heat. FUEL PROOF no corrosion from today's standard or special fuels. SMART COLORS, TOO! A one-trip dip in any boiling type Nylon dye provides brilliant, beautiful color finish . . . and it's permanent!

Because NYLON protects and maintains the superb thrust power of GRISH-Engineered propeller contours at all speeds . . . it's the BEST for longer, carefree flying! Ask for Grish TORNADO Propellers in most sizes of 3 blades, 2 blades, both tractor and

GRISH St. John 1. BROTHERS Indiana

2 Blade Tractor 5-3 5-4 51/2-3 51/2-4 6-3 6-4 7-4 7-6 8-4 8-6 8-8 9-4 9-6 9-7 9-8 10-4 10-6 854 11-4 11-6 RC 12-4 12-5 12-6 \$1.50 2 Blade Pusher 51/2-3 51/2-4 6-3 6-4 254 8-6 854 9-6 10-6 3 Blade Tractor 5-3 5-4 6-3 6-4 504 3 Blade Pusher 6-3

> TORQUE ENGINE

MAXIMUM THRUST from

KRAFT TONE RECEIVER PARTS

Due to popular demand, Ace has made individual parts for this unit available. Buy them separately or in a combo-parts package.

PC Base reworked to hold the CR60 transformer, undrilled	1.75
5 mf IEI electrolytic	.75
20 uh RFC	.45
CR60	1.63
CK722	.99
6007	1.95
Wound coil 271/4 mc	.85
PB #1	.10
Complete combo parts package	19.95

ACE RADIO CONTROL

Write for Catalog No. 59AD

BOX 301 HIGGINSVILLE, MO

job for that hot new Torp .09? Don'tl Building anything other than the maximum allowed (2.5cc) would put you at a severe disadvantage, since FAI rules call out a minimum surface loading based on square measure; and as you can now see, the smaller model is doomed under such a rule, since its true loading (volumetric) would be much higher than that of the maximum-sized model.

Perhaps next time we vote on FAI rules, we should all push towards the elimination of the surface loading rule, or at least try to get them to measure it on a cubic basis. We feel that the best way of doing this would be to work with the 3/2 power

of the area, as mentioned above. Should the FAI rulemakers be unsympathetic towards eliminating the minimum surface loading requirement completely, we would specifically recommend a minimum loading of 3 gm/sq. dm 3.

In practice, the minimum weight could be figured this way: For a model of 40 sq. dm surface, (619 sq. in.) the area 3

value would be 253. Multiplying this by 3 gm gives a minimum weight of 759 gm, or 26.7 ozs. (To simplify this calculation, a curve could be prepared for the use of contest directors to read weight against area directly.) Similarly the minimum weight for a model of 19 sq. dm surface (295 sq. in.) would be 249 gm (8.8 ounces.). Under the current rule, the total area corresponding to this weight is 193 sq. in., obviously too small for an .049 powered job to compete against the 15's. Because of the curve ball FAI rule-makers have inadvertently thrown, one seldom, if ever, sees other than a .15-powered model in FAI competition. Adopt-

ing either a no-wing-loading rule, or bas-ing loading on the 3/2 power of the area, as above, will see the bringing of .049's and .09's to the FAI fold. This should act as a great stimulus to American interest in FAI Power.

ing v arca to W of th cuhe ratio ing 1 span (4.26

to sc

397).

found

above

feren

3.

mode

build

than

like !

scale

a lar

Using

cubic

hence

you v As

new for a came slow

large

ounce termi 1. Wei

where

two ! scale

shoul

der to

have

inche If

still v

on it! graph

large

squar

you v

Your

going and 2

specti area divide squar dimer

divide

ing, stumb

are u

than

indire factio

MOD

Sin

To

In other

Back in 1953 and 1954, we were satisfied with the Ramrod design and were building literally dozens of models just to find the best size for each engine we wanted to use. For each particular engine size, the process was one of trial and error from beginning to end. Many models were drawn up, built, tested, then discarded, only to repeat the process on one of a different size for the same engine. Most of this could have been eliminated if we had known then what we know now. By use of the process illustrated below, it is possible to find size by trial and error for just one engine, say an .049 for convenience, and then predict with an uncanny

degree of accuracy what the size should be for any other engine and weight. To set up a procedure for doing this and check its validity, we used the Ram-rod 250 (%A) as a base to project theoretical areas for all other sizes, using only the cal areas for all other sizes, using only the desired weights (actually, the average weights for models already built) as a starting point. Our assumption is that the weights will be directly proportional to the cube of the span (a measure of vol-ume, as is weight). The span was figured in feet rather than in inches to avoid large

numbers.

As you can see from the table, the theo-retical areas are, in each case, surprisingly close to the actual areas we had found from the trial and error method. (Fig. 3.)

These theoretical areas were found in this way: First, the weights for all were set into the table, followed by the span

and cube of span for the "250." Assuming we want to find out, on this basis, the area to make an .09 job which we want area to make an .09 job which we want to weigh 13 ounces, or twice the weight of the .049 job, we multiply the span cubed value for the .049 by the weight ratio of two (38.6 x 2 equals 77.2). Finding the cube root of this value (77.2), gives us a span of 4.26 feet. Dividing the span of the .049 job into the new span for span of the .049 for into the new span tor our .09 model gives us a factor, 1.260 (4.26/3.38 is 1.260), by which we can multiply all dimensions on the .049 plans to scale up to .09 size. Our .09 job area will be the square of this linear factor times the %A area (1.260 x 1.260 x 250 is

In like manner, the proper size for any other model of a desired weight can be found by relating it to the KA as in the

It should be pointed out that this entire analysis presupposes several things:

1. We wish to scale one design to a dif-

ferent size, not mix different designs. 2. The same sinking speed is desired.
3. Structures are scaled approximately.
4. The same builder is involved. (Some

4. The same builder is involved. (Some modelers using the same plans as others build a 35 job as much as 9 ounces heavier than their friends.)

To further aid those of you who would like to use the principle stated above to scale your %A original, or other model, to a larger one, we have prepared a graph. Using the graph will give you the same cubic wing loading on both models, and hence an equivalent glide. Also, should you wish to scale a design down, the graph will aid you in selecting the proper factor to use. (Fig. 4.)

will aid you in selecting the proper tactor to use. (Fig. 4.)
As an example to illustrate the graph's use, let's assume you wish to scale your new 600 square inch .09 job up to one for a .20. Due to the fact that the 600 for a 20. Due to the fact that the 600 came out at 20 ounces, and is somewhat slow at getting upstairs, you'd like the larger version to just hit the required 35 ounces. In going to the graph, first determine the weight ratio: 35 ozs./20 ozs. is 1.75. Find 1.75 on the horizontal "Weight Ratio" scale and read up to where your imaginary line intersects the vocurves. Reading over to the vertical scale will then show that the linear ratio should be 1.20 (the number by which you must multiply all 600 dimensions in order to produce the larger model) and the area ratio, 1.45. Your 20 job will then have an area of 1.45 x 600, or 870 square inches. inches.

If your particular ruler should happen to be calibrated in centimeters, and your scale in grams, don't fret—the graph will still work, since only ratios are involved

on it!

As an example to illustrate how the graph might be used to "dehydrate" a large model, let's assume you have an 800 square inch, .15 powered "floater" which you were able to build to 26 ounces. You now wish to make %A version and will tolerate an all-up weight of 8.5 ounces. Your weight ratio is 28/8.5, or 3.08. In going to the graph, you will pick off 1.45 and 2.10 as the linear and area ratios respectively. Instead of multiplying by the area ratio, however, we must this time divide, to arrive at your new area of 381 divide, to arrive at your new area of 381 square inches. In scaling down, multiply dimensions by the reciprocal (the number divided into 1) of 1.45, or .69.

Since the principle of cubic wing loading, which we were fortunate enough to stumble across, is basic in nature, there

are undoubtedly many more applications than we have indicated in this article. We hope that knowledge of it may directly or indirectly help us all achieve greater satisfaction and success from our hobby.



Model-Craft HOBBIES

RYTHING YOU NEED FOR SMOOTH SAILING MODELS

BATTERY CHARGER



WITH SELECTOR SWITCH Charges 2 V., 4V. & 6V Wet Cell Batteries. Heavy duty transformer and rectifier. Com-pact, it has a ventilated metal case, features

indicator lamp and a selector switch for correct charging \$795 rate. 110 Volt A C input.



DUAL-MOTOR POWER UNIT

Fits into Ideal's popular Wheeler Cruiser, Has Twin Motors, Battery Holders, Switch & Uni-versal Couplings. No soldering, wiring or cutting

AARINE POWER-PACKS

FOR SMALL BOATS (6" to 12")

FOR LARGER BOATS (12" to 18")



ARISTOMATIC COMPOUND ACTUATOR FOR R/C

Self-contained electric motor (low-drain) special integral switching give 2 channel of tion from low-cost single channel of



COMPACT "A" ACTUATOR

COMPACT A ACTUATOR
Engineered to withstand the strains and stress
encountered in the radio control of aircraft, this
serve is also ideally suited for boats, care, etc.
"A" is easily installed, requires no shock mousting; that a low bettery drain of only 200 MA,
'allows more flight time with less battery
changes. The high-terque mater delivers power
to move even the sizest control surface through
a quiet running, long-life gear train. All electrical
contacts are salf-adjusting for trusible-free operation. There are no adjustments to make!

The Commant "A" Arbutor is seaded in a rises.

The Compact "A" Actuator is sealed in a cleer plastic dust cover; all wires are color s1095 coded; complete instructions are inc.



DOUBLE PER-MAG MOTORS



small physical size, long life, NOT surplus batteries! Manufactured from hi heavy duty plates, clear plastic case, marked ter-minals. Add 50¢ shipping

minata. Add 50° shipping charges to belatry prices. TYPE 64 – 6V., 4 Amp. Hr. Cap. 21% – 31% – 11% – 11% TYPE 25 – 2V., 3 Amp. Hr. Cap. (31% – 22% – 11%) – 177 TYPE 18 – 2V., 6 Amp. Nr. Cap. (11% – 11%) – 11% – 11% – 11% (11% – 21%) – 11% – 11% – 11% (14% – 11%) – 11% – 11% – 11% (14% – 12%) – 11% – 11% \$4,75 \$1.75 \$1.65 \$3.00

1" Sq. MILLIAMETER Small enough to build into your Model. Specify range itesired when ordering. 0 to 1, 0 to 5, 0 to 10 \$495





for that "finishing touch" hobby spray gun

stewart / lundahl co.,



FOR BETTER PERFORMANCE!

AT BETTER DEALERS EVERYWHERE

NO PLATING ON ACME TANKS. BAFFLES BUILT IN WHEREVER NEEDED. EVERY TANK TESTED FOR LEAKS and GUARANTEED. MOUNTING STRAP WITH EVERY TANK. A TANK TO FIT EVERY PLANE AND BOAT. FREE CIRCULARS ON REQUEST.

Radio Central and Boat Fans. Use ACME Battery Holders for top efficiency from your batteries.

See your DEALER for ACME PRODUCTS

6224N-15th AVE. BROOKLYN 19, N. Y







... in the new and easier-to-use Pin-Point Tip. Gives you as muchor as little-as you need. (And right where you need it, too!)

There's a LEPAGE'S cement or glue for every hobby need.

Metuchen, N. J. @ L'59

Delta Dart

(Continued from page 25)

made, indicated that the use of conical camber increased the glide velocity, in-creased stability, and decreased the sinking speed slightly.

From the information obtained in these tests it can be shown that the effect of conical camber is to reduce the induced drag by adjusting the lift distribution closer to that of an elliptical lift distribution, and so reducing the intensity of the tip vortices. To further note the effects of conical camber, we decided to check the performance of simple Jetex 50 powered models with and without conical camber. We decided to make two profile models of the F-102, since the camber principle was first applied to this plane and the large rudder needed no correction for scale effect. Also, we examined these impressive planes up close and saw them go through their paces when they were installed in 11th Fighter-Inter-ceptor Squadron at Duluth, Minn., giving us an added enthusiasm. Another convenient feature of the delta wing is that sweepback gives effective dihedral so that you can build a flat wing and still have sufficient lateral stability.

The effect of camber showed up during the powered portion of flight, also. The educed dates gave greater rate of climb

reduced drag gave greater rate of climb and hence more altitude and longer dura-tion. The models were easy to fly and, if you are a beginner or just a sport flier and care little about conical camber, per-

and care little about conical camber, performance, etc., but like realism and simplicity we invite you to try a straight F-102 for some enjoyable flying.

If you are a model designer, an experimenter, or just curious about conical camber, we invite you to try two models, one with each without conical camber, and with and one without conical camber, and

note the effects for yourself.

When Convair added conical camber when Convair added conical camber to their F-102, they did not add it in the aerodynamically complete form but ap-proximated it by using a constant radius of curvature of the leading edge from root to tip. They also reduced the curvature in to the They also reduced the curvature in the vicinity of the tip so that there is no curvature at all at the very tip. Latest reports indicate, however, that later models of the F-102A will have the complete form of conical camber.

form of conical camber.

In the past, the delta-wing model has not compared favorably with the conventional design in competition. Now the use of conical camber on the delta wing should reduce the inequality. Delta-wing models are a favorite with many radio control modelers too, and the use of conical camber on their deltas can give them improved performance. Another possibility of reducperformance. Another possibility of reducing drag and increasing the lift coefficient that should be investigated is that of using turbulators in conjunction with conical camber. A properly designed turbulator will increase the lift and reduce the drag due to separation at low Reynolds numbers.

Little need be said about construction.

Little need be said about construction. Choose your wood carefully so that the model will balance at the position shown on the plans. The secret of top performance is also a low wing loading so keep your model light. Our models weighed .77 ounces with the engine putting out a measured .88 ounces of thrust, enabling the model to fly straight up with certain trim adjustments. Cut out and cement together the inner portion of the wing first leaving the leading edge and elevons off.

Cement the wing to the fuselage before the leading edge and elevons are added. The cambered leading edge must be carved to shape. Tack glue a block to the front of the wing and carve the top curve first, then the bottom curve. Remove the lead-

then the bottom curve. Remove the lead-

ing edge to enable you to carve in the camber near the fuselage, and then sand it well and cement it on permanently. The straight leading edge is made of 1/16" sheet; just cement it into place and sand

the leading edge round.

Some of you who build the model may find it easier to carve a uniformly curved leading edge. Those of you that desire to investigate the complete form of conical camber should carve little or no curvature in at the root chord and then gradually in at the root chord and then gradually increase it uniformly until it is a maximum at the tip as shown in the plan.

Give the complete model one coat of

thinned clear dope and if you wish you can spray on a thin coat of silver dope for can spray on a thin coat of silver dope for realistic color. Realism may be further enhanced by detailing the control out-lines, insignia, and so on, with a speedball pen and india ink or with a wet colored pencil (if you do not use a coat of silver dope). Air Force insignia decals can be purchased at most hobby shops. The leading edge will be greatly strengthened against nicks by an application of scotch tape. Cement some aluminum foil to the fuselage and wing in the vicinity of the

Th Spor

> thr run

mach tir

.049 |

Mod

fuselage and wing in the vicinity of the exhaust to prevent scorching these parts.

Test glide the model in the usual way. To trim for a left climb first add two degrees left thrust, leave the left elevon straight and bend the right elevon down about 3/32". Add clay to the right tip until the model has a very shallow glide to the left. If the addition of clay to the tip leaves the model nose heavy or tail heavy add clay to the nose or tail of the heavy, add clay to the nose or tail of the fuselage for the correct balance. Leave the rudder straight. When the glide is satisfactory, try a powered flight. Light the fuel igniter wick, wait for the thrust to build up, and launch smoothly on a level keel. The model should climb in a level keel. The model should climb in a fast left spiral and glide almost straight. If the model spins to the right under power take some clay off the right tip. If the model turns too tight to the left under power add some clay to the right tip. 1. *Interavla*, January 1957, p. 59.

2. Aviation Week, November 26, 1956, p. 26.

ATTENTION Week-end Pilots:

Here's a gold-mine of information, facts, hints and tips to help you get the most out of your plane and pilot's license.

Frank Kingston Smith (AOPA 124393) is a week-end pilot. He started out with a Cessna 140 and an auto map of his home state. Two years and hundreds of flying hours later he was piloting his whole family in a Cessna 172 with hight plans that covered two continents.

In a breezy, amusing account of his advantage.

In a breezy, amusing account of his adventures in the air, Mr. Smith passes on all that he has learned about flying. You will find his book full of wonderful new ideas and suggestions that will add immeasurable enjoyment to your own hours

of flight time. WEEK-END PILOT has lively, yet authoritative

chapters on:

buying your own plane

a plan for syndicate ownership

the fine points of navigation—s

the fun of cross-country travel implified

• the fun of cross-country travel
• tips on safe'sy
• sharing America's historic spots with the family
• cutting the cost of week-end flying
• how to trade in your old plane
• getting your wife to tolerate flying
As you can see from this partial list of subjects covered, WEEK-END PILOT is the perfect guidehook for every flying enthusiast. Order your copy today. Just send this ad, with your name and adverse, and remittance of \$3.95, to the publishers, EANDOM HOUES, INC., Dept. WP-3, 457 Madison Avenue, New York 22. Your money back in 10 days IF not delighted with the book.



Thimble-Drome

MANCE PERFOR

the key to more fun in every model sport!

Engines that start easily! Models that run well! Names that fly right! Send for Illustrated Folder M8

WATER WIZARD

Exciting Step Hydro

Slam-bang hydro action at the beach, or in your swimming pool! 15" overall - 81/2" beam. Easy-starting .049 Babe Bee Engine. Long life nylon prop. Spring Starter. \$1000

M. COX MANUFACTURING CO., INC. Box 476, SANTA- ANA, CALIFORNIA

World's Largest Manufacturers of Ready-to-Fly Planes, Engines, Fuel, and Accessories

New!


FOUR NEW EDITIONS FOR YOUR AIR AGE TECHNICAL LIBRARY

Completely new, another set of four man-uals—covers the "great" fighters of World War 2. Be up to date on the very popular warplane designs of the second world war Plans, pictures, and date a collector's item.









AIR AGE INC. 551 Fifth A	ve., New York 17, N.
Herewith \$	for the followin
booklets in your TEC	H MANUAL Series
50¢ each, or enclosed	\$2.00 for all four [
copies P-51 Mustang	copies P-4 Thunderbol
copies P-38 Lightning	copies F-4l Corsair
Name	
Address	
City	State

A Place to Fly

(Continued from page 13)

good letter from the President of the Fresno, (Calif.) Control Liners stated, as did 10 other letters, that the Director of Recreation for the city was interested and helpful. He says "It seems that we no sooner obtain a site than for some reason we were asked to leave... complaints . . . noise . . . the usual reasons.
The City Director of Recreation was at first The City Director of Recreation was at first reticent. I suggested a possible site, a newly grassed park on the outskirts... quite suitable. He agreed to let us use the area, subject to city council approval, if we secured written approval of all people living on the streets bordering the park.

The pretition we observed.

The petition we circulated contained conditions which we imposed upon ourselves with an eye to the future. The conditions were as follows:

(1) All fliers would be covered by insurance provided by the Western Associated Modellers group with which our club is affiliated. The insurance covers bodily injury and property damage through Lloyd's of London.

(2) We would fly only at given times on Saturdays and Sundays.

(3) All flying would be under adult

supervision. (4) No jet models would be flown. (Jet

noise is a justifiable cause for complaint.)

(5) Flying circles would be completely "roped off."

The letter stated that these conditions The letter stated that these conditions were more severe than they would like, but, note the eye to the future. This agreement gives the club good facilities and the possibility of later softening of the agreement if their experiences are good.

It is interesting to note that all except three neighbors signed the petition. When they found out that everyone else had cooperated, the last three signed. It is stated, "So far our experience with the field has been good no complaints, we feel that

been good, no complaints . . . we feel that the fact that the residents nearby were consulted . . . is of great influence." Notice here again a definite plan, specific rules, good leadership, and hard work brought success.

3. From Westfield (Mass.) Aeronauts comes the news that after the usual sad experience of members cutting grass and making a good flying field, complaints terminated its use. However, its Advisor went to see the former Mayor, who owns acres of land." They put up their case and outlined applies requesting uses of a lot outlined a plan requesting use of a lot about 1% miles from town, in a semi-industrial area. This they were granted rent free. The former Mayor "is very much in-terested, and hopes to see us build a club house this summer. At present we are operating 150' circles. We have our own electricity and our own PA system." Because some of the boys do not like to fly over blacktop, they plan only two such circles, others will be clay or grass. They plan a two-way strip for radio-control fly-

The Advisor makes the following points:
(a) "The club does its own maintenance." We have agreed to set up a work night We have agreed to set up a work night every Thursday . . . so everything is ready for the week-end. Our flying hours are 8 a.m. to 8 p.m. weekdays. Sundays from noon to 8 p.m. For sanctioned meets we ask the Playground Department to mow our grass. The Auxiliary Police take care of contest traffic, the Air Scouts handle parking of cars, and the Kiwanis Club, which is our sponsor, runs a refreshment which is our sponsor, runs a refreshment stand and gives us a percentage." (b) Noise is not a problem if you "get the right location and if you control the flying time." (c) It is important to let the public

SEVEN TECH MANUALS WITH PLANS, PHOTOS DATA, FAMED PLANES



TECH MANUALS 50¢ each.

B-25 MITCHELL

Best medium bomber WW 2, the ship used by Doolittle on Toyko raid from carrier.

B-24 LIBERATOR

Companion in arms to the B-17, the Liberator "heavy bomber" noted for range.

B-17 FLYING FORTRESS

The most famous of all the World War 2 warplanes, B-17 "heavy" was tough ship.

From beginning to end, P-40's prominent in all theatres excepting the European.

What the Mustang was to WW 2, the Sabre was to Korean war. Classy jet fighter.

F-94 STARFIRE

All-weather jet with tremendous rocket firepower, seeks out intruder by radar.

B-47 STRATOJET

AIR AGE INC.

More of these six-jet bombers in Strategic Air Command than any other machine.

Herewith 5			tor	the	TOHOWIR
oklets in your	TECH	MANU	JALS	at 5	Og eac
copies B25			0	opies	F86
copies B24			CI	ppies	F94
cepies B17 copies P40			е	opies	B47
☐ Enclosed	\$3.50	for all	seven	сор	ies.
ame		*********		*******	
Idam					

551 Fifth Ave., New York 17, N. Y.



FIRST IN QUALITY . FIRST IN VALUE FIRST IN DESIGN

NEW! 1959 CATALOG-SEND 10c FOR POSTAGE AND HANDLING

ENTERPRISE MODELS, INC. MINEOLA, NEW YORK

know what you are doing. "You gain a good reputation by doing something constructive for the young people of the community, and with this good reputation people will overlook the noise." (d) "Our Club is operated strictly according to AMA regulations." This helps also in gaining a good reputation. reputation.

OS.

ES.

errier.

bero

ar 2

ship.

inest

fire-

tegic

ın.

reputation.

4. Anyone who has driven south from Syracuse, N.Y., can picture the ideal location obtained by the Syracuse Sky Knights in Manlius, N.Y. They used a new method to obtain the use of a beautiful field, which merits a try in other parts of the country. The Elmira Flying Sparks tried the idea with equal success. The key to this situation is the Soil Bank Program of the Department of Agriculture.

This plan can provide an excellent site.

This plan can provide an excellent site In spain can provide an excellent step for control line and radio control flying, possibly even for free flight. It cannot, how-ever, provide for any blacktop circles. Hundreds of communities may find this an adequate solution to their flying site

Look for the Agricultural and Stabiliza-Look for the Agricultural and Stabiliza-tion and Conservation County Office. This will be in your County Building. If you cannot locate it, ask any County Agricul-tural Agent or the teacher of vocational agriculture in your high school. The Agri-cultural Stabilization and Conservation County Office knows the location of all land in the "Soil Bank" program. Some land is bound to be clear and level, just right for flying.

land is bound to be clear and level, just right for flying.

One of the "spark plugs" of the Sky Knights says "I believe our deal went smoothly because we first talked with the owner of the property and were lucky to find one who was interested in model flying. He sent us to the conservation officials, and then sat down with his own lawyer and went over all the legal aspects


of the deal. We took out a public liability policy to protect the club and also the owner of the field. We are also working on incorporating the club to protect the in-dividual members." dividual members.

This leader said that the Soil Bank officials were very cooperative, so this idea should work just as well for you. Look in your phone directory under some such title as Soil Conservation, and make your title as Soil Conservation, and make your first contact through them. Keep in mind that the land cannot be "improved," only mowed. Still, who would turn down a real nice place to fly. The photo of their site would make any model flier drool. A huge flat field with no trees!

would make any model flier drool. A huge flat field with no trees!

5. One of the most glamorous sites is the Charles A. Donnelly, Jr. Modelport, in New Orleans, La. The President of the New Orleans Aero Club who is also a model plane Contest Director says, "After being pushed around as most modelers are in various cities, I met a man willing to listen to my story." This prominent "oil" man was interested in helping modelers. He had his company architect draw ideal plans. The "Modelport" is located across from an amusement park, and the flying site measures 320 ft. by 380 ft. The field is enclosed with chain link fence, and has auto parking space outside the fence. There are four flying circles. One for 70 ft. lines and three for 60 ft. lines. Each has a 6 ft. concrete slab for pylon flying." Read on and drool some more. He says "Located in the corner of the field is the control tower. The upper floor all glass enclosed, provides an area where all clerical (contest) work, tabulating and recording is carried on. The Contest Director has an electronic timing and lap counting device in the tower, and all trials are directed by inter-comm. to stations in the circles. (Continued on page 50)

rected by inter-comm. to stations in the circles. (Continued on page 50)



- PLANES BOATS
- ACCESSORIES
- ENGINE PARTS AND PRICE LIST





ONLY

REFUNDABLE ON FIRST 50c \$10.00 PURCHASE!

LEE'S FINE	PRODUCTS					
	4 Os.	Pint	Qt.	Gel.		
. LEE'S GLOW FUEL		.79	1.40	4.95		
. LEE'S CLEAR DOPE	.40	1.20	2.19	8.50		
. LEE'S COLORED DOPE	.45	1.50	2.89	10.95		
. LEE'S CEMENT	.50	1.79"	3.19	10.98		
. LEE'S GRAIN FILLER	.40	1.20	2.19	8.50		
. LEE'S BALSA PUTTY	.79	2.98				
. LEE'S KWIK KLEEN		.59				
. LEE'S THINNER	.35	.90	1.65	5.25		

All products are available at a Lee's approved dealer agency or directly from us. Send us your dealer's name and location with your order so that we might contact him.

2072 FRONT STREET EAST MEADOW, L. I. N. Y.

`AIR ACES OF THE 1914-1918 WAR"

Edited by Bruce Robertson Produced by D. A. Russell, M.I.Mech.E.

Contents:

Biographies of 135 Aces, and the military background to their particular Air Service, of the eight main countries engaged in the 1914-1918 War: British, French, American, Belgian, Italian, Russian, German and Austro-Hungarian. Lists of each country's Aces by scores, with unit in which served or machine flown; many identification markings; lists of every airman to receive the British Victoria Cross, the German Ordre pour le Merite or the Congressional Medal of Honor, Altogether, over 1,500 airmen are mentioned in this amazing book. Book contains 212 large pages 11¼" x 8½". Bound in stiff boards, gilt blocked. Weighs nearly 21/4 lbs. Over 100,000 words. Over 320 photographs, many of which have never before been published!

\$8.50

THE PUBLISHERS FIXED PRICE



fo

This price includes airmail acknowledgment of your order, especially strong cardboard carton for safe transit, postage and insurance of your copy. Pay by personal check if more convenient than buying an International Money Order. Post direct to Publishers, address below. Your copy despatched same day your order received. Average transit time to United States and Canada only 12 to 18 days.

HARLEYFORD PUBLICATIONS, LTD. LETCHWORTH, HERTS, ENGLAND.

"A splendid PA system keeps contestants and spectators constantly informed. Sur-

and spectators constantly informed. Surrounding this upper room is a balcony from which supervision can be exercised."

Work tables with formica tops are part of the furnishings of the 2nd and 1st floors, while a shop, work bench, and lockers are also on the 1st floor. Two rest rooms, and a drinking fountain are appreciated, and a flag pole with wind sock and flags trim up this excellent control tower. Outside four flood lights make night flying possible. Pretty keen Modelportl New Orleans is really fortunate, but you can be too.

Possibly your eventual site may not have all the features of the New Orleans Modelport, yet with proper planning you can look forward to less complaints and more permanence. The 30 cities studied showed

increasing permanence. A great many new mcreasing permanence. A great many new Modelports are now in process. Cities like Dayton, Ohio; Ft. Wayne, Ind.; Detroit, Mich.; and smaller cities like Union, New Jersey, have operated Modelports successfully for periods varying from 10 to 15 years. Evidently these cities have found a satisfactory solution and noise is not a serious problem.

Many other cities and towns have in-

ious problem.

Many other cities and towns have interesting and very adequate flying sites. Such places are St. Paul, Minn.; Boulder, Col.; Los Altos, Burbank, Oakland, Alameda, Livermore, Hayward, Sunnyvale, Santa Ana, San Mateo, Calif.; Plainville, Conn.; Denver, Col.; Wichita, Kan.; Houston. Tex., and many others. Then there is the huge Los Angeles Model Airport in the Sepulveda Basin area as fully described in the March 1959 issue of this magazine.

From the Vancouver (Canada) Gas Model Club bulletin it is evident that the same problems exist to the north. Their approach is unique, broader than usual, but good. The British Columbia Society of Model Engineers decided to build a center for all hobbies. They approached the municipality for a grant of land. The Park Commissioners felt that this would be a worthwhile project. They gave nine acres of land worth \$70,000. On this nine acres will be built three U-Control circles, a pond 100 feet by 200 feet, a railroad track around the pond, a three-story hobby center building, complete with hobby museum, machine shop, woodwork shop, ham seum, machine shop, woodwork shop, ham radio room, and a complete custom carbuilding shop.

At the present moment, a forest appears (Continued on page 52)









Sterling SPECIFIES AMBROID!!

Most of the people in the model plane industry are enthusiasts from way back, as well as being long-time Ambroid cement users. Like genial Ed Manulkin of Sterling models (seen below with his 'Corsair' and 'Space Master Jr.' kit models), who built his first model plane with Ambroid back in '29! Says Ed—"Ambroid is the finest and strongest cement ever manufactured—its superiority making itself felt not only in the model plane field, but also in model boat building. We at Sterling recommend Ambroid to all model builders—and that also goes for Ambroid Plastic Cement, which is perfect for our plastic Chris-Craft 'Cobra' and 'Express Cruiser' electric-power boats."

Look for the familiar Ambroid blue and orange tubes (Regular, Extra-Fast & NEW Plastic Cement) at YOUR local model shop.





In Every Field There's A Leader - In Cement It's

AMBROD

AMBROID CO. . BOX 30 . WEYMOUTH BB . MASSACHUSETTS

HERE IT IS! THE LITTLE ADV WITH THE

AT LAST! Full house operation is now possible on a single BC channel using the NEW THIT/FH receiver. The super-reliable STD Esseo THI used as "front end" to give you proportional rudder & escapement operated elevator and motor controls. ALL with your present CW XMTE using a simple pulse which type pulser. Simple, inexpendive & fully reliable multi-control at a price within reach of all. 37.93 ADAPTOR UNITS to convert existing models of Essac THI receivers to the FULL HOUSE STSTEM ... 18.88 A SPECIAL DUAL CONTROL THY for the besters who only require simple rudder and motor operation ... 34.83

FOR ULTIMATE PERFORMANCE AND DEPENDA-BILITY . . . THE EXPERTS SAY: "The Esse THT is without a doubt the best single channel receiver buy in without a cours are the RC industry."
STD THT with MICRO GEM or Paladium non-pitting contact relay, housed in small attractive metal case 21.86

ANOTHER NEW DEVELOPMENT in receivers, ask for by spany. THE ESSCO THEY/M.C., gives reliable desired). Crass in area clears of the state of the case of the state of the state of the state of the d os wt. A batt drain under 60 ma. Complete ready fly, deluxe unit

ing the VOLTABLOCS & SILVERCELS. Compact unit with full wave constant current circuit for PROPER regu-lar or trickle recharge service, a EBSCO Super Special 4.96





MAY'S MEW & BEST in BC, available first at NEW MONO MODULATOR, a compact stable or suitable for converting ALL CW XMTRS to Especially suitable for the MAC IIs Esquires only inutes to install. Tone variable 300 to 1900 eps \$.80

to be occupying this area, but not for long. In May the bulldozers would level the field and the tress will have to be cut down. neid and the tress will have to be cut down.

In July the Engineers' Langley track goes in. In August the grass will be seeded for the flying field. The last sentence is the key to their ambitious program, it says, "See you out there every Saturday morn-

ing 8 a.m. to 1 p.m. Bring an axel

Here are some points that from the
analysis of 30 reports seem to be important

in preparing your plan:

1. Leadership, should be adult, strong

yet cooperative.

2. Planning, develop a plan in writing that will have appeal to groups, then get the help of local businessmen or organizations.

3. Self discipline, be ready to curtail flight hours, or even install motor mufflers in order to show cooperation.

4. Support, attend city meetings and get to know people and city problems. Cultivate the friendship of your Superintendent of Recreation, State Director of Aeronautics, County Soil Bank Officer, newspaper staff, airport manager, Kiwanis, Rotary, Exchange Clubs, etc.

5. Public relations, guard your club reputation, don't let one or two "non-cooperation, don't let one or two un trouble. Take

time to write newspaper accounts of the science achievements of members. Newsmen will take the photos. Keep your skills on display. Make friends with neighbors

on display. Make theirds with reighbors if you can.

6. Reliability, keep your word, build your club reputation.

7. Work, roll up your sleeves, you may have to clear land, grade, seed and maintain for a while until you can prove that you have a worthwhile activity.

8. Cost. What will it cost a Recreation Department? Some say about \$1,000 re-placement cost and \$100 per year for maintenance

Several letters from Directors of Recre-Several letters from Directors of Recreation say that until the noise problem is improved, there is no chance of getting a favorable flying site. There are at least three motor mufflers on the market. Have you thought that eventhough it is not desirable, still if everyone who flew at your site used them, competition would be fair?

What is your particular problem? What ideas can you use from the experience of others cited above? Reflect, then plan!

Varicomp Switcher

(Continued from page 29) sturdy action is obtained for the elevator sturdy action is obtained for the elevator on the third and fourth pulses. ("Quick blip" for motor is the fifth "channel.") The elevator horn decides the positions of the elevators. If placed on top of elevators, the third position is down and fourth is up. If horn is reversed, the action is reversed. Due to the fast or slow rate at which the Varicomps accept the pulses, the servo action from switcher is reliable and stable. Since 4½ volts on each side of servo hook up give better power, working the servos to three volts or lower still will give plenty of service.


The action of the switcher will give such rapid action that, if the fourth position is necessary, you can pass through

tion is necessary, you can pass through the third pulse almost without noticing it. There is no breakdown on the switcher if

There is no breakdown on the switcher if built correctly. The unit has been bench tested for six months and 10,000 operations and still is working.

The bottom Varicomp to which the switcher is attached should use ¼" rubber, with at least 75 to 100 turns on it at all times. No spark suppression is necessary, so this is of some value to the receiver. Hook-up should be followed as per manufacture's schematics of each unit (Variative's schematics) facture's schematics of each unit (Vari-comps and servo). Use any servo that will Hold, Release, Hold (Citizen-Ship or Bonner). The mechanical relays are con-tacts are obtained from any pinball machine (get from service man or company). The author can advise prices and sources of material.

Photo shows parts:
Base, insulated board; contacts (2); old needle valve %" long (cut from threaded end); 2 mounting bolts 4-40 (1" long with binding nuts); 1 center torque board (obtained with Varicomps); 1 pc. steel wire (Continued on page 54)



IN DEALER FIRST! If he docum's stock is. CLEVELAND MODEL PRODUCTS CO.

th. Include 35c per model for parti-part.

4506 LORAIN AVE. "Since 1919" CLEVELAND 2, OHIO

ANNOUNCING the FINE NEW

THE FIRST Really NEW R/C Model Advancement in over 5 years!

Not since the advant of the let live With has there been each a sensational oftrace of the sense of the let live With the three been each a sensational oftrace of increasing development the "Chainer" same with features which sake
at the first fully acredualt RIC model hit Coty new is it possible to desplane
to the first fully acredualt RIC model hit Coty new is it possible to desplane
the completely full sizes deterral controls any address representations to them.

The "Chainer" has symmetrical attribut wings for greater stability and equalised
merited measure-trip. Its Bighane writes give the ears required to provide a
forcide with the 6th acreedy-material equalities conse are required to provide a
forcide with the 6th acreedy-material equalities conse a brilliant related
taking new homemore a planaeric.

With the "Chainer" Live Witer you have the most modern and versatile roll
attailing new homemore a planaeric.

"Giant full size plane with complete as"The Base delines the interhibities instructions
with detail!"

"Giant full size plane with complete aswith detail!"

"Generate provided and fright intertractions:

"Chain feature writeth is for I'm.

Was areas 1185 mp. in. Wing

prodight and flying instructions: promium grade beins and tough he parts! ed and sharply die out of formed dural gear and seconsary

ME MIDE Custom LIVE WINE

A truly Spectacular Multi-Channel R/C Model!

FOR USE WITH .25 to .35 ENGINES AND



deBOLT MODEL ENGINEERING CO.

Check these of Top wing span: 46"
Wing area: 1808 so, in.
Plying weight: 5% to 7 lim
Model weight minns R/C of
Controls as dangered.

Home of Design-engineered Models

SEE YOUR HOBBY DEALER

Surprise! Fun! Authenticity!



e-is

he he is

e-at es, of k-ill

if

u-

ri-ill

or

n-

With these NEW Monogram Models

Here are two fine new kits in a long line of famous Monogram models. Both are authentic and true-to-scale and packed with plenty of fun and many surprise features. See them at your favorite store today.



and the first model of this unusual aircraft. Main and tail rotors both revolve. Cabin doors can be set in open or closed position. Completely detailed cabin interior and instrument panel. Model follows hospital transport design and is accompanied by five figures-pilot-two stretcher bearers-two men on stretchers. Authentic de-




It "Goes" Too! Power With "Jetex" CO2 Capsule

Only 98¢

The slingshot Dragster is an authentic drag strip racer model scaled from topwinning cars. Has all of the conforming drag racer features-long nose shell housing, big exposed engine in center, oversize exhausts, big squarish rear tires and the driver in the "hot seat" at the extreme rear. Kit includes scale Chrysler engine with 6 carburetors, pin stripe decorative decals and power unit mount for racing.

lt's a Slingshot Kit Only 98¢



YOU'RE ALWAYS IN GOOD HANDS



When You Buy At The Store Displaying This Dealer Emblem

(Dealer inquiries invited) Write To:

CRAFT, MODEL & HOBBY INDUSTRY

30 East 29th St. New York 16, N.Y.



ANNOUNCES THE ALL NEW

> DURAMITE **MULTI-SERVO** 125

> > WEIGHT: 2W OZ. OVER 4 LBS. THRUST

FEATURING OUR OWN MOTOR ESPECIALLY DESIGNED FOR SERVO USE-NOT AN IMPORTI

TEST MODELS OPERATED FOR OVER ONE

QUARTER MILLION COMMANDS! AVAILABLE AT YOUR DEALER NOW!

BONNER SPECIALTIES 2900 Tilden Ave

1/16" x 1" (with washer to fit); 2 cam followers (1 for rudder) (1 for switcher Varicomp); 1 3/32" x ½" eyelet; 2½" spacers.

Assemble switcher before mounting to bottom Varicomp with aid of 2½" spacers. Contacts should be mounted in overors. Contacts should be mounted in over-size holes so adjustments can be made. Once set, the relays can be forgotten as they hold indefinitely. The cam follower should be loose enough so that it can ro-tate in needle valve. Do not solder to wire while in place on nylon gear. The Vari-comps should use 4½" volts for a good reliable action; ¼" rubber on both Vari-comps. Use color code book hook-up as servo specifies. If instructions are followed, you will have many good hours of flying fun. You don't need a 5-channel job to do most of the maneuvers the Multi boys do!

Foreign Notes

(Continued from page 2)

young hobbyist with small glow engines, in this way, would have a serious effect on the strong position that the diesel has held for so long.

GERMANY

Surprise item from West Germany is that the big Metz radio firm—widely known outside Germany for their Mecablitz elec-tronic photoflash units—are in the model radio control business. They have just an-nounced their first outfit, to be known as the Metz Mecatron.

This is an audio-tone outfit for 27.12 mc., and gives a choice of single-channel control, or three channels by means of adapter units on receiver and transmitter. The transmitter uses a single tube and two transistors and features a transistorized D.C. converter to utilize the cheap power supply of four 1.5-volt batteries. Afternatively, it can be connected to a 6-volt car tively, it can be connected to a b-voic car battery supply, or, with the aid of a spe-cial connector cable, to a 12-volt car bat-tery. It is housed in a flat plastic case ap-proximately 8 x 6 x 2-in., with carrying strap. The Mecatron receiver is fully transistorized and is temperature checked up to 140 deg.F. It operates on 6 volts and is enclosed in a case measuring 3.6 x 1.6 x 1.4-in. A neat battery box with switch and plug connection to receiver is available.

This new Mecatron equipment only started reaching the hobby trade in late May, but already Metz is working on new equipment, including a proportional out-

INDIA

The tenth annual All-India Model Air-craft Rally was, this year, held on the newly-built Indian Air Force runway at Barrackpore. The meet was officially open-ed by the Indian Minister of Civil Aviation in the presence of a distinguished gathering of officers of the government and armed forces of India and before about 4000 members of the public.

members of the public.

Official support for model building is now being considered in India. The Directorate of Civil Aviation is investigating the possibility of establishing a modeling center at the proposed new civil airport at Behala, which would include flying sites, workshop facilities and a design and accepancy section. In this way, when conresearch section. In this way, plus con-cessions for the increased import of modeling goods, it is hoped to greatly expand model interest in India.

AUSTRALIA

Carrier deck events are getting popular in Victoria. In addition to using the accepted scale navy carrier type models, enthusiasts have restored to converted teamracers and stunt jobs to try this fascinating branch of the hobby, which is so little known outside the U.S. Practically all the engines used at present are of the O.S. Multi-speed series with coupled exhaust/intake throttles operated through a third line, the I. Roberts Flight Control handle

and bellcrank being most widely favored.


Model building in Australia follows U.S.
rather than British trends and the main center of activity is concentrated on the eastern sea board state of Queensland, New South Wales and Victoria. Over on the western side, Noel Mitchell, secretary of the West Australia Model Aeronautical Association, Perth, tells us that, with 1500 miles separating them from the next capital city, Adelaide, exchange of modeling idea between east and west travels slowly and that, as a result, West Australians tend to take a lead from trends as reported in M.A.N. Mitchell asks us to mention that if any U.S. modeler would care to write to him, he would welcome such correspondence. His main interests are team-racing stunt, combat and RC and his address: 378

Mill Point Road, S. Perth, W. Australia. SOUTH AFRICA
Our Capetown correspondent, noted South African modeler, Pete Visser, reports that the recent S.A. Nationals, held this that the recent S.A. Nationals, held this year at Johannesburg, were quite a success. For the energetic Visser they were, anyway... Driving 1000 miles up from the Cape, he placed in six events, obtaining three firsts (Open Rubber, FAI Gas and Nordic A2) and, by a coincidence, three fourth places: %A Gas, Open Glider and A

Gas.

Two other Cape Province modelers.
Brian Partridge and Robbie Rowe also did
well, Partridge winning %A Payload and
Jetex, and Rowe taking the B Gas event,
plus the F/F Championship Shield. Crand
National Champion (F/F and C/L to
qualify) was Cannon of Bloemfontein and
the Champion Club was the well-known
Western Providence MAC Western Providence M.A.C.

Western Providence M.A.C.
U.S. design trends are evident in Clas
A and B free-flight gas with Torpedo powered Ramrods and Spacers still much in
favor-especially for Class B. T/Hoppers
are the accepted engines for %A. Diesels
in English model designs are more widely
used in FAI gas, and Visser's winning
Dream Weaver used an Oliver Tiger, although diesels, in general, were at a disadvantage at the high altitude (6000 ft.)
of Johannesburg. of Johannesburg.



Look for the name that guarantees championship performance in...

little

2.0

st/in-

andle

ored.

U.S.

main the New the ry of I As-

1500 apital ideas and and to

d in that write

ond-

cing, 379 ralia

oted ports this

cess.

any-

ning

hree

d A

lers

did and ent,

and and own

own in pers esels dely

ning

dis-

ft.)

- . MODELS
- . ENGINES
- . BOATS
- · ACCESSORIES



products

.35C COMBAT ENGINE

Built for combat and rat racing.
Crankshaft absorbs strains of violent
maneuvers. High speed porting gives
top rpms and thrust. Special fitting
for use with pressure tank — \$16.95



FUEL III

Many from perceity compounded synthetic subsection requirements a resist glow furly Soft, rates therefore reacts contains Veco WHEELS

% to 41/4" Diameter

Largest selection of rugged, lightweight, die cast hub wheels. Inflatable, semipnoumatic, aponge or hard rubber tires.



27" harher er 35" ocean-going models. Expertiy anginsered for multi- or singlechannel R/C. Formed styrene holl, pilot and decknesse. Die-cut plymood planked deck. All metal fittings provided. Harbour Yug—\$18.95 • Ocean Tug— \$24.95.



FUEL TANK \$1.45
Designed for combat and stunt. Longitudinal battle keeps fuel under pressure. Power failure and engine sage eliminated. 2 oz to 4 oz.



SPINNERS

Hand spun aluminum for maximum strength and lightness, perfectly halanced. Regular

VECO PRODUCTS ARE SOLD BY LEADING HOBBY DEALERS EVERYWHERE. VECO PRODUCTS CORP., BURBANK, CALIF.

WYLAM PLANS EIGHT 14x 20 IN. PLATES TO EACH SET!

For the first time in sets-YOU asked for them! Now available!

Set # W-1

Just

off

the

two

new

sets

Wylam

0

press!

SOPWITH CAMEL Famed WW-1 English pursuit WRIGHT MODEL A A true pioneer-a gemi WRIGHT MODEL B

Another collector's item
SE-5A
WW-1 pursuit—a favorite

W-2

SPAD S-XIII C. 1
Renowned WW-1 Franch pursuit
CURTISS MODEL A
A competitor of the Wrights

SPAD S-VII
Great French WW-1 pursuit
WRIGHT FLIER
Man's first flyable plane

Sel = W-3

CURTISS P-1 HAWKS Glamorous Army fighters F11C-2 GOSHAWK Novy corrier fighter P-6E HAWK

Greatest of all the Hawksi

W-4

REPUBLIC P-47D
The wonderful Thunderbolt
SPITFIRE 2
Battle of Britain hero
MESSERSCHMITT Me-

109J ww.2 German fighter CURTISS P-40D American ww.2 Warbird

GRUMMAN F6F-3 Novy's shipboard fighter DOUGLAS C-54

> DOUGLAS A-26 Invader-new 8-26 BOEING B-17

The Flying Fortress

CONSOLIDATED B-24
Liberator—a heavy!

CURTISS A-25
Navy divebomber
CONSOLIDATED PBY

NORTHROP P-61

BOEING B-29

BOEING C-97
Military transport

MARTIN B-26

For over 20 years, William Wylam has been an acknowledged master of the detailed drawings af historically famous airplanes. MAN is happy to comply with the many requests for Wylam plans by making available this selection

MODEL AIRPLANE NEWS 551 Fifth Ave., New York 17

E	A	C	H	S	P	
			_	_		

\$1.00

ALL SIX . . . \$5.00

Enclosed	is	f	or	plan	set	s n	um	bere	d in	bo	xes	belov
Please prin	your	number I	DIS	TINCTLY	in	box	for	each	plan	VOU	desire	

PLAN SET PLAN SET PLAN SET PLAN SET

NAME PLEASE PRINT

ADDRESS

ZONE

STATE

MODEL AIRPLANE NEWS . August, 1959

W-5

PLAN SET

NO STAMPS PLEASE

24-HOUR SERVICE

MODEL AIRPLANES CRAFTS TOYS MODEL RAILROADS

YOUR BIGGEST SOURCE OF SUPPLY . . . OUT GIANT new Catalog with over 300 pages. Send for it on your letterhead, we sell to dealers only, 100% wholesale, fast service



P. O. Box 10353-B 2009 Farrington Dallas, Texas

Dept. KC-B 1120 E. 13th St. Kansas City, Mo.

P. O. Box 506-B 510 E. Sixth St. Des Moines, low

Dept. M-B 577 Scott St. Memphis, Tenn.

ARGE SIZE PLANS

WYLAM MASTERPLAN

Drawn by MODEL AIRPLANE NEWS' William Wylam, these drawings consist of four % inch to the foot plans—each 14x20. Two plates show side view and cabin details, two more the dimensional layout and front details. Complete set \$1, post-paid.

AIR AGE INC., 551 FIFTH AVE., NEW YORK 17, N. Y.

YOU'RE ALWAYS IN GOOD HANDS



When You Buy At The Store Displaying This Dealer Emblem

(Dealer inquiries invited) Write To:

CRAFT, MODEL & HOBBY INDUSTRY 30 East 29th St. New York 16, N.Y.

Engine Review Cox Olympic

(Continued from page 24)

mounting lugs (a recent departure and also seen on the new Space-Hopper .049) and the twin ball-bearing mounted crank-

shaft.

Constructionwise, the new Cox is typical of this manufacturer's products. No castings are used. Crankcases are turned on screw machines from extruded bar stock, afterwards passing, in turn, through two other machines which do all the remaining constitute. ing operations-i.e. those non-concentric to the shaft. Pistons are machined from bar steel and are hardened on the wearing sur-face only, in order to leave the socket for the conrod ball-joint sufficiently ductile for

the conrod ball-joint sufficiently ductile for subsequent working. Connecting-rods, which are of steel, are assembled to the pistons by a special machine, built in the Cox company's tool shop. The operator merely places rods and pistons in two hoppers feeding the machine, which assembles them entirely automatically.

In the finishing of such items as cylinder bores, much emphasis is placed on temperature control, as an aid to accurate working. All grinding, cylinder boring, honing, etc., are therefore done in a temperature-controlled room, in which the temperature is maintained constantly within one degree, after being pre-set at a comfortable working level. fortable working level.

The Olympic uses a ball-bearing mount-ed crankshaft, because, all other things be-ing equal, a ball-bearing engine must achieve higher mechanical efficiency than a plain bearing motor. Agreed some highly impressive performances have been put up impressive performances have been put up by plain-bearing motors, but these have been in spite of, not because of, having plain bearings. Frictional losses in the Olympic are obviously very low indeed. The chankshaft journal itself is of small-er diameter (¼-in.) than is usually em-ployed in .15's. This is practical because

it does not have the stress-raising intake port of a shaft-valve, and, being supported in ball-bearings, does not need the added bearing area of a large diameter journal. The shaft has a chamfered circular web and a machined-in crescent counterbalance. The connecting-rod is rather longer than average and piston side thrust is thereby held to a minimum. The piston is flat crowned and uncovers the large exhaust ports at 70 degrees BBDC, a normal tim-ing. Bypass timing, on the other hand, is ing. Bypass timing, on the other hand, is very advanced, the tops of the two internal bypass flutes being almost flush with the upper edges of the exhaust ports. The cylinder, as in other Cox motors is machined in one piece, with integral cooling fins, and screws into the crankcase. The combined glow head unit screws into the top of the cylinder and seats on a soft copper gasket.

per gasket.

Cox reed valves have been simplified, compared with the assemblies used on the Space-Bug and Thermal Hopper. On the Olympic, a single copper reed, retained by a wire snap ring, is used. Reed valve housing, crankcase backplate and carburetor venturi are combined in a single machined unit. The familiar and highly effective Cox triple-jet carburetor is featured, whereby fuel is supplied, finely atomised, via three small jets bored equidistantly around the venturi. Actual metering takes place before the fuel reaches the jets, by means of a venturi. Actual metering takes place before the fuel reaches the jets, by means of a separate needle-valve. The complete needle-valve unit is secured to the venturi by means of a nut with a large screened intake, and can be rotated through 360 degrees, for the most convenient location for individual installations.

for individual installations.



plugs. 360 providi greater peak ope tion and still p · Performs bette S

prov

on a

pime.

will

reso

start

mot

ency

wer

agai star first

nee ture

will Pro

eou

adju

pro

ergi

awa

bres

pre

test

befo

Tes

tally

wit

read

equ

pro-sel incr the the pic Act

con

pro per x 3

cyc

cial

ing

San

MO

Lasts Longer LONG LIFE GLOW PLUG 650 Long Thread - Short Thread

OHLSSON MANUFACTURING CO W. 16th ST. . LONG BEACH.

LATEST OFFICIAL AIRCRAFT PHOTOS

NOW, FIRST TIME, GET exclusive, official, sharp photos of advanced Supersonic Rockets, Jets, Mistorical planes. All makes, hundreds from which to choose.

SPECIAL INTRODUCTORY OFFER with your name and address. Send only 50c

1. 4 31/a5 photos, world's insteat lois.
2. 4 31/a5 world war planes.
2. 4 31/a5 world war planes.
2. 5 21/a5 world war planes.
3. 1 kill photo Booling 8.52 to Homber.
3. 1 kill photo Leckhood F. 1688 Startighters. 32. 55 1/a6 for Starting March 1988 Startighters. 32. 55 1/a6 for Starting March 1988 Startighters.

Absolute money back guarantee.
MAIL YOUR ORDER NOW . . . TODAY.

AVIATION PHOTO EXCHANGE

Dept. MA Box 75084, Los Angeles 5, California

BUILD A SKYHOPPER NOW ONE OR TWO-PLACE MODEL



PLANS \$50.00 Money Bock Offeri Clear, simplified and easy to read drawings. All ribs and fittings are drawn full size and may be used directly as templates in making parts. 260 sq. ft. of drawings supplied. Planse eligible for CAA license. SPECIAL OFFER INBOARD AND 3-VIEW. PHOTOS. DATA . . . 25.00. SKYHOPPER AIRPLANES, INC. 3500 ENVILLE PLACE, (Dopt. M), Los Angeles 16, Calif.



DUCTED FAN IMPELLER FOR LAND, SEA, OR AIR CRAFT

65 C. EACH AT YOUR DEALER OR ORDER DIRECT, POSTPAID; OUTSIDE U.S.A. : 10C.

More Thrust Than a 6-3 Prop! Pusher Type, 3" In Diameter For .049 Engines. Die Formed Aluminum Alloy.

- ASTRODYNE -

P.O. BOX 117. EAST MOLINE, ILLINOIS

Surprise item with the Olympic is the provision of a starter spring. Incongruous on an "expert's" engine? You will doubtless think so-until you have tried it a few times. There may be a few diehards who will insist on finger flipping rather than resort to such a "sissy" item as a spring starter. And they won't have any trouble because the Olympic is an easy-starting motor. But reed-valve motors have a tendency to occasionally start backwards, especially on small, light props. The starter definitely does a better job of starting: we were convinced of this after trying it against normal hand flipping. No reverse starts and the thing works like a charm, first time, every time. Starting from cold needs a cylinder prime, plus a couple of turns of the prop with the intake choked to draw fuel to the carburetor. The engine will then start within two or three attempts, Surprise item with the Olympic is the will then start within two or three attempts, will then start within two or three attempts, provided it has been adequately primed. Restarts with a hot engine are instantaneous. If there is fuel in the delivery line, no priming, no choking and no needle readjustments are necessary: just wind the prop back one turn against the spring, energize the plug, release the prop and she's

As on other Cox engines, no lengthy break-in is needed and it is normally quite safe to let the motor have its head after a preliminary rich mixture break-in of only one minute. However, as a courtesy, our test engine was given 30 minutes running before any performance agures were taken. Tests were carried out with the aid of our reaction-dynamometer, cn which, incidentally, some 40 different types of .15 engines, both diesel and glow, have been

IG

gines, both diesel and glow, have been evaluated to date.

The first thing that became apparent with the Olympic, was its high torque. This reached a maximum of 23 oz. inches at between 11,000 and 12,000 rpm, which is equivalent to a brake mean effective pressure of 60 lb/sq. in., is better than any glow .15 previously tested and closely approaches the very high torque of top diesel 15's like the Oliver Tiger. As rpm are increased, however, the normal decline of the torque curve is less abrupt than with the diesels and in consequence, the Olympia. the diesels and, in consequence, the Olympic reaches a higher bhp peaking speed. Actual bhp figures, obtained with a fuel containing 30 percent nitromethane, were as follows:

At 10,000 rpm-.218 bhp -.24811,000 " -.270 13,000 288 .300 .310 16,000 -.31617,000 18,000 -.318-.317

18,000 "—,317
Running qualities throughout the tests were excellent, the motor running smoothly and consistently, and the response to the needle-valve was just right. Suggested prop for achieving maximum free-flight performance would be around 8 x 4 or 8%

Summary of Data

Type: Reverse-flow scavenged two-cycle with reed-valve intake.
Weight: 4%-oz including starter spring.
Displacement: 0.1495 cu. in. or 2.45 c.c.

Bore: 0.585 in. Stroke: 0.556 in.

Stroke/Bore Ratio: 0.95:1.
Specific Output: 2.13 bhp/cu. in.
Power/Weight Ratio: 1.24 bhp/1 lb.
Price: \$12.98 including starter and special wrench.

Manufacturer: L. M. Cox Manufactur-ing Company Inc., 730 Poinsettia Street, Santa Ana, California.

by P.G.F. Chinn

MODEL AIRPLANE NEWS

Anniversary SPECIAL



LIMITED SUMMER OFFER

OFFER GOOD UNTIL OCTOBER 1959

Celebrating Our Thirtieth Consecutive Year of Service to the Model Airplane Builder

Twelve Months wo Full Years

Yes, it's only about once in 30 years that we can make an offer like this! Why not celebrate with us too by taking advantage of this Big Saving? Think of it-twelve jam-packed issues covering your favorite hobby for only \$3. Act now as offer is limited!

MODEL AIRPLANE NEWS, 551 F	th Ave. N	ew York	17.	N.	٧.
----------------------------	-----------	---------	-----	----	----

I want to take advantage of the Anniversary Offer.

Enclosed is: 3 for one year

□ \$5 for two years

(Please print) Address City Zone State

Canada & Pan American Union Add 50c Per Year . All Other Countries Add \$1.50 Per Year

X-ACTO KNIFE HELPS MAKE PLASTIC MODELS VALUABLE SHOW PIECES!



bling easier, faster, more ac-curate. The finished model is perfect in every detail... adding to its value as a col-lector's item.

X-ACTO knives from 29¢. Write for new X-ACTO Hobby Tool Guide - 25e.



X-ACTO, INC. 48-53 Van Dam Stree Long Island City 1, N. Y.



WEIGHT: 21/2 CZ. FEATURING OUR OWN MOTOR ESPECIALLY DESIGNED FOR SERVO USE-NOT AN IMPORT!

TEST MODELS OPERATED FOR OVER ONE QUARTER MILLION COMMANDS!

AVAILABLE AT YOUR DEALER NOW! BONNER SPECIALTIES 1990 Tilden Ave



Radio Control News

(Continued from page 30)

the N-46, while rated at 450mah will give this capacity only at a 10 hour rate, or a maximum drain of 45ma. The quick discharge in no way affects future life.


.

CLUB NEWS
The Lakeland RC Club, c/o Bill Deff-The Lakeland RC Club, c/o Bill Definer, 165 Bank Street, Waukesha, Wis. is holding an AMA sanctioned two day contest on July 18th and 19th. This 6th Annual event at the Waukesha County Airport will cover rudder-only, intermediate, multi, pylon and scale, with plenty of trophies and other prizes. If you go early, a welcome party at the Avalon Hotel. Flying from 9 am until 5:30 pm on the 18th and from 9 am until noon on the 19th for eliminations and from 12:30 pm until 5 pm on the 19th for the finals. until 5 pm on the 19th for the finals.


From the Bison Beep Box, Flying Bisons, Buffalo, we learn that Stan Keysa is building an ME-109 fitted with a .15 or .19 engine. Rudder-only to start and then elevators and engine control. Bud Marsh has finished a Piper Commanche using an O.S. Max. 25 to power the 56" model. Vince Rasp built a Cessna L-19 and should have no trouble with scale jobs since he built the Boeing F4B-4 last year.

Looks like quite a scale outfit, in addition to the Smog Hogs, Astro Hogs and Live Wire designs. Cliff Barber points out that trouble can occur when using sub-minia-ture sockets if the tube leads are not straight (no kinks) and you are careless in inserting the tube, or transistor.

Interesting comments from the Central Jersey RC club tend to back up statements made in this column. Superhets won't be popular until the price is reduced and, at present, little if anything has been published to enable the RC fan to build his own. Super-regen circuits have been proven over many years and are now quite reen over many years and are now quite reliable. They can be built by the average builder and except for the interference problem are perfectly satisfactory. Superhets will be coming onto the scene but in the meantime don't sit around and watch others fly just because you have an "old-fashioned" super-regen. In the Rolling Breadboard operation (RC cars) on March 10th, Herm Birnbaum took first with his three-wheeler with a WAG TTPW system and a Mighty Midget for steering. Jan Mock took 2nd with his four-wheeler, one driving, and a two-relay delay network for two channels. Nick Ciampa 3rd with a three-wheeler having the two front with a three-wheeler having the two front wheels driven separately by Mighty Mid-gets. The tail wheel was free to swing and (Continued on page 61)



SHAPED AND NOTCHED LEADING AND TRAILING EDGES DIE-CUT RIBS, TAIL SURFACES AND PLYWOOD PARTS



SILKSPAN COVERING MATERIAL

SHAPED FUSELAGE

FORMED LANDING GEAR AND PUSH ROD

GENUINE DECAL

lightning!

Guillow's GALAXY 45 in.
Wing span

U - CONTROL MODEL

STUNT-COMBAT- SPORT

The "jet styled" Galaxy is exceptionally fast and tight maneuvering when used with a hot combat 35 engine. When powered with standard motors, it is a sensitive and highly maneuverable stunt and sport model. The Galaxy's light weight sturdy construction and superior design endows it with the flying qualities dreamed of by all U-Control fans.

AIRFOILED BALSA WING

GENUINE DECAL

HARDWARE PACKAGE

HARDWOOD **ENGINE MOUNTS**

Wing area . . 400 in.

Engine . 19 to . 36 disp.

Guillow's

KIT GM-19

20 inch wing span

ZKA KING

U-CONTROL MODEL FOR .020 ENGINE

Completely pre-fabricated

The Sky King is designed primarily for the 020 engine but can also be easily adapted for .049 motors. Repeated tests by designer Lou Andrews has proven that the Sky King will "stay out on. the lines" even in high winds. No equal for flight performance and durability in its class. An ideal trainer model for beginners - a terrific value for every modeler!

STURDY MOTOR MOUNT SYSTEM

COMPLETE HARDWARE PACKAGE

NEW ANGLE POISED LANDING GEAR ARRANGEMENT PAUL K. GUILLOW Inc.

EXTRA VALUE INCLUDED IN KIT! DACRON FLYING LINES

AND CONTROL HANDLE

If not available at your Hobby Dealer send direct to factory adding 25¢ packing and postage in U.S.A., 40¢ outside U.S.A.

MODEL AIRPLANE NEWS FULL SIZE PLAN SERVICE The editor's selection of all time favorites, including completely new combinations of the greatest designs. All types!

PLAN SETS 50c p.p.

54.

PLAN OF THE MONTH

TRI-TRAVELER: Sc, FF, .049 HOUDINI: RC. .15 DIZZY BEE: Sp., U/C, .29 61. Maneuverable but stable, Houdini, a low wing; Dixxy Bee, Lauderdale's latest Mono-Line.

> SURE FUN: UC Sport, .29-.35 PROFILE SILVAIRE: FF Profile, 1/2A. ZEPHYR: Rubber, Fuselage Central line on floats. Sport Gassie.

AEROCOM'DER: Scale, U/C, 2 .15. MARS: Bob Palmer stunt, .29-35. NOBLER: Aldrich's Nats Winner, Stunt, .29-.35. Palmer and Aldrich, plus a twin ukie. Imagine!

SMOG HOG: Bonner's Multi RC, .19-.35. 45. STRATOLINER: 2 Half A, U/C. GUARDIAN: U/C Scale, .29 up. Greatest Multi RC of all time—a beauty!

GAMBLER: Mirror Stunt Winner, .29-.35. DOUGLAS 8-66: ducted fan FF, .049. B-66, the ducted fan job that beats all others.

WHIRLING WINGS: Sikorsky XH-5, .15, 'copter. BREEZY: Small field RC, .049. SPITFIRE: Stunt, semi-scale, .29-.35. P. Schoenky, 'copter master-his Sikorskyl

T-CRAFT: FF scale, .049. FENO: Combat, stunt, .29-35. PADDY'S WAGON: Contest FF, .049. Paddy's Wagon—one contest job ok for beginner.

HEATH PARASOL: RC, FF, Scale, .075 .09. GUARDIAN: Nats carrier winner, .29's. SHARPIE: FF Sport, .02-.049. -Guardian a dilly.

RE-8: WW1, U/C. .29-.35. FLAPPING WINGS: Rubber, 15. ornithopter. BOOMER: FF, sport, pusher, .049. Can planes fly like birds? Ornithopter sure does. MOONEY MITE: 1/2A Scale FF. '55 RAMBLER: .29 Team Racer. WACO CABIN: 1/2A FF Scole Rambler still beats 'em. Waco-Cute!

> QUICKIE TRAINER: Speed, .29. AMAZOOM: FF, contest, .15. deBolt's best, the Equalizer? Amazoom-Stan Hill's hi-thrust.

CONVAIR'S DELTA: Jetex FF. LIL DYNAMITE: .15 stunt, UC. SWAT: 1/2A, FF, contest. A trio of exceptional planes.

ASTRO-HOG: Multi RC, ,29-.35 MITCHELL: Profile, .09's, .15's UC. Dunn's low wing radio-tops! Nothing matches this multi. The Mitchell a fine flier.

PROPJET B-47D: U/C, .15's. RUFFY: Stunt, .29-.35. NOR'EAST'ER: Nordic glider. B-47D, beaut of a project Ruffy: big winner-it's new! FOKKER E-3: 1/2A, FF, Scale. NAVY RACER: Rubber, semi-scale. WOODY: .29-.35, UC Combat. Hotl E-3, beautiful model, fine flier.

SPORTCOUPE: .09, U/C, Stunt. WHATIZIT: .35, Combat, Wooten. SWIF-F-FT: Jetex, two sizes! Whatizit, settles fuse-wing debate! CONQUISTADOR: .29-.35, U/C Stunt.

TWO-STAGE ROCKET: Jetex (2). Stunter is a thing of beauty, and it flies as well as it looks! DUMBO: PBY Scale, U/C, .19's. FRENCH OLDTIMER: 1914, 1/2A, FF. Dumbo, the Catalina, man-sized ukie, takes off, lands on water

or ground.

52. The Mite, stable, real looking low winger. EQUALIZER: .15 to .19 multi, RC.

BOMARC: Scale, Jetex, missile. CUTLASS: Sport U/C, .049's. 51. Scorpion power makes Bomarc terrific filer. Americano is National Champ's very latest.

GAUCHO: RC Stunt, .29-.35. THE CHAMP: Best U.S. Wakefield.
LAIRD SOLUTION: U/C Scale, 15-23.

AMERICANO: .15 FF, by Blanchard.

co

Int

rin 250

cei

opo

ton

er

out

trai

and

mai

teri

the

witl

ers

tow

MOD

Gaucho, Argentine Champ, does pattern inverted. Champ, a single Wakefield! SNAP: Sport U/C, .19-.23. PELICAN: PAA Corgo, .049. WINDMILL: FF, 'giro, .02-.049.

53. For proto take-off and landing realistic Snap tops 'em all. Other two, collector's items. SATELLITE: Hunter's FF, .19-.35.

SUPERMARINE S-68: U/C Scale, .09-.15. Satellite is top contest free flight '58-'59. Schneider racer, S-

6B seaplane is one of FAST club's best projects. DETROIT STUNTER: U/C .29-.35.

HORNET MOTH: FF, Scale, .02-.049. 55. THE BARDON: Wakefield. D'troit St.: McDonald's Strathmoor, Nats favorite. Bardon: Canadian

and US Nats winner, tops in rubber. RYAN PT-22: U/C, .19-.25. SNIPE: Gurnett's Nordic.

56. Lovely scale job, that PT, with workable flaps, throttle. Tow-line glider long, strong wing, right sections, etc.

Twin Lizzie: 1/2A FF. Com-Bat: U/C, .29-.35. **57. .** Fireboat: Marine, RC. T-Liz, a cute sport job. The boat, Musciano, a beaut.

SE-5: FF, .09-.15 PIED PIPER: Rat Race, UC. 1/2 WAVE: RC, .049 SE-5 most beautiful flying scale model ever published.

GASSER: Willard RC, .09 1958 WAKEFIELD WINNER 59. SKY LANCER: Team, Proto, .29 Gasser, hot pylon racer. Both the others beauties, too.

BELLANCA: Scale U/C, .19-.29 HALF ALPHA: FF. .049 60. DUNWOODY GLIDERS Gliders (4) from Dunwoody series of articles.

PLAN SETS 50c p.p. NO STAMPS PLEASE

MODEL AIRPLANE NEWS . 551 FIFTH AVENUE, NEW YORK 17, N. Y.

40.

48.

49.

Enclosed is for plan sets numbered in boxes below PLAN SET PLAN SET PLAN SET PLAN SET Please print your number DISTINCTLY in box for each plan you desire. PLAN SET PLAN SET PLAN SET PLAN SET PLAN SET List additional plan orders on separate sheet.

PLEASE PRINT

NAME

ADDRESS

Limited Supply of Plans Listed Below. Order Early! Check Correct Number on Coupen.

24. Aero Bat, Snoopy, Seaguil

26. Corsair, Gyro-Glider, Santanita 29. Cougar, '55 Nordic Winner, Dizzy Boy

30. Great Lakes Trainer, Triple Threat RC

34. Corben Super Ace, Cessna 310, Profile Lightning MODEL AIRPLANE NEWS . August, 1959 steering was accomplished by alternating power to each drive motor. Ed de Fillipo was 4th with his three-wheeler and three-channel receiver, only two channels used. Ed's was the only non-pulse entrant.

A. B. Kunz, 2804 Liberty Street, Allentown, Pa. advises there are about 30 active filers in his area, most on single channel. The multi channel fliers use Orbit, Bramco, Marcy and WAG TPW.

Too late to announce more on the 6th International RC Contest held June 20-21 in London, Canada. Mentioned a new Perilous Pylon Race. For rudder-only, it had to be a flying start and a flying finish. For intermediate an ROG start with one loop down and one loop back and a flying finish. For multi an ROG start with two loops down and two back and then an upwind landing.

Photo from A. Friberg, Box 224, Tyringe, Sweden, shows him with his 2500mm (100") powered glider. The receiver uses a DL651 tube and three transistors, features a transistor converter and operates from six volts. The control actuator is a Telematic, mentioned in previous columns. Other interesting photos showed his transmitter, usable on either tone or CW and also featuring a DC power converter. With 6v input it gives 180v output at 20ma and uses two 2N256 transistors. RC gliders are an important phase of model building in the European and Scandanavian countries. Transistorized power converters are also widely used, mainly due to the higher cost of B batteries.

Speaking of RC gliders, we learn that the Wichita, Kan. boys really go all out with their RC glider work. Fourteen footers using eight channels and a 1200-foot tow line. Control is maintained on the tow and, without hitting a thermal, a four-minute flight is about normal, the tow being almost overhead to the full 1200 feet of line. Just think, no engine or gear to install, no vibration problems, less building cost and the feeling of real accomplishment with even a two or three minute flight. The west coast fliers are the only ones we know of (Stan Hill in particular) who have done much to date in this field. Good conditions should produce flights of several hours with a five to six footer.

A quick check of the Carrier (EBRC'ers of Oakland, Cal.) shows that Bob Heise took 1st in the multi five-lap pylon race with a Torp .35 powered racer using the TTPW system. Dale Root was 2nd with the same style racer using the Torp .45 and Orbit-8. Dick Jacobsen came in 3rd with a scale PT-19 with Torp .35 and Orbit-8. In rudder only, three-laps, Bob Forbes was 1st with Breezy Sr. Torp .19 and Marcy Tone. Ralph Hall with a Super Cub was 2nd and Larry Murphy with a Max .19 Waco bipe and Orbit single was 3rd. Scale is really coming into its own out that way with PT-19's, Waco bipes, Aeroncas, a Stearman bipe, Cessna 170, Monocoupe and an exact scale P-38-stand back! Dale Root, in addition to holding the speed record at 65.7mph, now holds the Bay Area Trophy for duration. His Comet Clipper (do you remember?) kept its wheels off the ground for 1 hour 24 minutes.

The Washington DC/RC Newsletter has it that Walt Good may be taking up RC gliders and Tom McCraw had returned to him his six-foot "Pterodactyl", the only damage being to the stabilizer which was stepped on by a cow or other large animal, probably a dinosaur. Symposium papers from the April convention will be availbale from the AMA for \$2.00. This



Maynard Hill was "snowed" in his attempt to Put his "Maxie" into the air for demonstration at the RC Symposium, held in Washington, D.C., on April 12. More than 125 enthusiasts attended a second annual RC Symposium, put on by the DCRC and Academy of Model Aeronautics. FLASH! And still they come...

Jan. Triple A Southwest Regional Meet. Phoenix, Ariz, FIRST in Class A.

Feb. FIRST and SECOND in "A. Thunderbugs.

FIRST and SECOND in A. Pacific Coasters.

Mar. FIRST in "A. AMA. Thunderbugs.

Mer. FIRST in "A. AMA. Thunderbugs.

What are you waiting for? Move up today to

Toshi

Matsuda's ZERO



The hottest thing in 1/2A! It climbs higher, faster... stays up longer. Designed to use ALL the power of the best .049s! For an unsurpassed thrill, hang your engine on a ZERO. See for yourself the super performance that has already won a string of Firsts! At a recent contest the "anyone can get 5 minutes" models were doing 3 to 3½ minutes. Tosh dethermalized his ZERO three times straight at over SEVEN MINUTES. Does that tell the story!

WARNING! Watch the engine-runor you may put your ZERO in orbit!



Only A-1 Class Nordic Glider on the market! Adapted from latest, hottest German designs. With Auto Rudder and Pon-Up De-thermalizer.



If you too are curious about a Delta, here's dependable performance and true Delta characteristics in a job that has been thoroughly proven before being announced.



A good flying R/C Model doesn't have to be an ugly box! Miss Tiny is world-famous for her beauty and flying qualities. Uses hot .049 to .099 engines, depending on weight of R/C gear. Wing Span 46". Finished cowl and die-cut parts.

Ask your dealer, or send M. O. and we'll ship prepaid. (Mr. Dealer: If your jobber won't supply you, send M. O. for prepaid shipment, regular discounts.)



ADVERTISING INDEX-AUGUST, 1959

Ace Radio Control	4
Acme Model Engineering Co.	41
Ambroid Co., Inc. America's Hobby Center Astrodyne	51
America's Hobby Center	6, 7, 1
Astrodyne Aviation Photo Exchange	54
Aviation Photo Exchange	54
Babcock Models, Inc.	40
Berkeley Models, Inc.	E4 54
Aviation Photo Exchange Bebook Models, Inc. Berkeley Models, Inc. Bonner Specialties	34, 30
CG Electronics Corp. Champion Products, Inc. Cleveland Model Products Co.	d Cave
Claveland Model Products Co	52
Comet Model Hobbycraft Inc	
The Controlon Co	62
L. M. Cox Mfg. Co., Inc.	47
Craft, Model & Hobby Industry	54, 54
Dealers Hobby Supply	56
Comet Model Hobbycraft, Inc. Comet Model Hobbycraft, Inc. The Controlon Co. L. M. Cox Mfg. Co., Inc. Craft, Model & Hobby Industry Dealers Hobby Supply The deBolt Model Engineering Co.	52
Doubleday & Co. Dynamic Models, Inc.	39
Dynamic Models, Inc.	31
ESSCO	52
Enterprise Model Aircraft Co	49
Forster-Appelt Mfg. Co., Inc.	63
Fox Manufacturing Co., IncSecond	Cover
Forster-Appelt Mfg. Co., Inc. Fox Manufacturing Co., Inc. Carl Goldberg Models, Inc.	37
Grish Brothers	44
Baul V Guillew Inc	8.0
Gull Model Airplane Co	41
Harleyford Publications, Ltd.	50
Hawk Model Co.	40
Hawk Model Co. Herkimer Tool & Model Works	5
Jaico Products	36
Jayhawk Models	
K & B Allyn Co.	54
Kap-Pak Products, Inc.	54
Lee's Hobby Supplies	49
LePage's Inc.	44
LePage's, Inc. Minnesota Engine Works, Inc.	28
Modelcraft	41
Monogram Models, Inc.	53
Ohisson Mfg. Co.	56. 58
Pactra Chemical Co., IncFourth	Cover
Perfect Parts Co	2
Perfect Parts Co. Polk's Model Craft Hobbies	31. 45
Random, House Inc.	44
Scientific Model Airplane Co.	42 43
Skyhopper Airplanes, Inc.	84
Sterling Models	38. 39
Stawart/Lundahl Co.	AS.
Stewart/Lundahl Co. The Testor Corporation	32 33
Top Flite Models, Inc.	24 35
Veco Products Corp.	37, .33
World Engines	34
X-Acto. Inc.	
A-ACTO, ITC.	

Do It Yourself ...



- Real stick control from outside the circle lets you perform complete AMA stunt pattern.
- Perfect for all planes

 up to and including
 .35 engines.
- All metal—precision made. Not a toy!
- Control stick 14";
 pylon 14½" high,
 4" square at base.

NEW LOW PRICE!



BESTOOGE

Bestooge is a modeler's best friend. It allows one-man operation of U-control airplanes. Includes rubber-padded spring clamp. Thoroughly proved in use.



Get Controlon and Bestooge now — at your Dealer's. If he cannot supply you, order direct — include 35¢ for postage.

THE CONTROLON CO. 6913 Sprague Rd., Cleveland 31, Ohio

100 pages plus proceedings will bring you up to date on the technical topics discussed.

Following is the proposed system for selection of FAI RC team members to represent the USA. The country will be divided into three regions with division lines at 80 and 100 degrees longitude. One team member will be selected from each region and will have the highest number of points within his region. Points will be earned as follows, 1st through 10th place: (Multi) 1958 Nats-180, 95, 85, 75, 65, 55, 45, 35, 25 and 15 points; 1959 Nats-200, 115, 105, 95, 85, 75, 65, 55, 45 and 35 points. In addition, the candidates can gather other points in their own regional contests as follows: 1959 RC/DC at Washington, D.C.—1st place 36 pts; 2nd, 24 pts; and 3rd, 12 pts. Same points given at the 1959 Great Lakes Meet, Detroit, and at the LARKS Meet in Bakersfield, candidates must hold valid AMA cards and comply with applicable FCC regulations. This system will also be used to select the 1st, 2nd and 3rd alternates in each region.

NEW ITEMS

New to most modelers, Celastic is a "poor man's fibreglass". Thanks to Mr. Ev Schoenberg, 811 Whittier, Witchita, Kan. we have tried a sample. Celastic is a fabric-based material impregnated with other fibres and a thermoplastic material. It is about 3/64" thick and is ready for use after it has been dipped in a solvent. We found acetone, thinner, MEK and other solvents to be excellent, with the best mixture for our use being 50/50 acetone and dope thinner. After a quick dip in the solvent, the material becomes very pliable and is easily formed and adhered to practically any surface, wood or metal, flat or with mild compound curves. While not as tough as fibreglass, it is easier to use and can be applied over dope and even oily and greasy surfaces. Once in place, and you can smooth it and feather the edges by applying a few drops of solvent. It dries in about 45 minutes.

The only apparent drawback is that it is not fuelproof, otherwise you can sand, saw, file and dope it. What can you do with it? John Worth repairs broken fuse-lages in about 30 minutes. Dean Zongker uses it for wing tip skids on "Speed Merchant", Dick West on landing skids for his ½A RC job, and Tom Williams repairs fuselage and reinforces noses. Good for dihedral joint splicing. Two square feet cost about \$2.00 from Serco Imports, Wichita, Kan. or, a club can obtain it in quantity from Ben Walters Inc., 156 7th Ave., New York 11, N.Y.

Reports in on the Tomoser MP-H servo are very encouraging. Low drain and high torque, together with smooth action and versatility of application make this servo a must for pulse (especially WAG TTPW) systems. Tests have gone up to 750,000 operations, which actually represents 1,500,000 commands on multi use. Dale Springsted has run two of the MP-H units for over an hour on three 500mah nickle-cadmium cells. An up-and-coming servo for the proportional field. Tomoser Electronics and Mfg. Co., 217 Vulcan St., Buffalo 7, N.Y.

Gyro Electronics Co., 36 Walker St., New York 13, N.Y. offers the following from 1959 RC Directory! Diagrams for receivers, transmitters, pulsers and other items can be had for 19 cents. A reversestop stepping switch for boats or cars is \$3.25, a telephone dial for 1-10 impulses, \$3.50. A joystick control box, made for an Automatic Pilot and containing five microswitches is \$3.95. Gyro also has a wide range of subminiature disc and electrolytic capacitors.

United Mineral and Chemical Corp., 16 Hudson St., New York 13, N.Y. has a new pressure-sensitive Foam Tape that may be used for shock-mountng, seal against dust, anti-slippage and other applications. Available in 'm', '\u03b4'' and '\u03b4'' thickness and from 4\u03b4'' to 18\u03b4'' widths with colors being green, gray, brown, black and creamwhite. Prices are reasonable and we trust an enterprising hobby distributor will be able to make this readily available to the RC and other modeling fans.

Ace Control, Box 301 Higgsinsville, Mo., has a spiral plastic, flexible tube that helps eliminate floppy wires in an installation. The tubing is merely wrapped around the bundle of wire, which may be up to about ¼" in diameter. This is the ideal thing for multi jobs at 7 cents a foot. Ace also features a more complete line for those desiring to make their own printed wiring patterns. Individuals or clubs can now make a sizable number of patterns with the minimum amount of work.

From F & M Electronics, 537 Grove St., N.E., Albuquerque, New Mex., word of forthcoming single-channel proportional system using frequency modulated subcarrier to carry the information. This will be a 3v superhet working directly into a Sage actuator or equivalent. There will be no pulsing and the system will be failsafe in that controls remain in neutral on loss of signal. Relay for throttle operates by elimination of modulation.

When CG discontinued their multi-channel sets (new line impending) F & M purchased entire stock, now offered as follows: RT-8 receiver, \$139.50, RT-5, \$105.00; RT-3, \$70.00; RT-2, \$55.00. In each case, the transmitter comes free. Limited supply of T-11 x-mitters at \$9.95

MAN at Work

(Continued from page 4) judges, watch holders, and well wishers turned the event into an all day jam session. Seems everybody had a trunk full of shiny models accumulated during the winter. The joint was Simpl/Simul crazy. Having an inexhaustible battery supply in the FAI job, made 21 flights, experimenting with flight patterns over hot runways and green woods.

Three-channel Marcy receiver gives left and right on Bonner servo, with third channel for spoilers. This will be replaced with four-channels, giving down trim with last channel for quick neutralizing. All engines present suffered from heat, as usual, so, putting a three-inch diameter piece of tin under the compression adjustment crank of the Diesel, picked up 750 rpm to normal. You cannot turn an oversize" prop on any modern engine on a hot day—manufacturers don't believe in fins or cooling, we gather. This tin hat-really crazy, but it stays! Marcy multi uses filters, not reeds, so one less worry on long flights.

filters, not reeds, so one less worry on long flights.

What a day! At Moon's Memory Inn, alongside the Dutchess County Airport, some 30 couples (ancient order of Skyscrapers) and their wives—and a raft of kids—were set for a reunion. Wonderful idea that other old clubs should try. On the airport were many gliders assembled for a Northeast Gliding Meet. Things got lively when some power plane guy, so far

RICH'S HOBBYTOWNE

ic

be

il-

m

ng

st

be

ed

av

ete

OI

of

of

it

ıbvill

rill

nil-

on

tes

anur-

-5,

Ĭ'n

.95

es-

of inzv.

ntays left aird ced

ith All

eter

ust-

750 ver-

n a

in at-

ong

Inn, oort,

Sky-

On

got far

t of erful U.S. HIGHWAY 46 PARSIPPANY, N. J.

> featuring America's Only

TRI-O-RAMA FIELD

FLYING CIRCLES
2 Large—3 Small Paved
Runways. Center Posts.



MIDGET RACE CAR TRACKS Large & Small Cars

BOAT POND
Hydro Racing and Radio
Control



ROCKET
LAUNCHING
Platform for Safety.
Approved Rockets

QUARTER MIDGET CAR AREA



Free field information upon request. Come for the day or week-end.

Send for Souvenir Brochure 35¢

BRANCH STORE
1241 MAIN AVE., CLIFTON, N.J.
PRESCOTT 3-4442

47 BROADWAY, DENVILLE, N.J. OAKWOOD 7-0794 off course that he was in the wrong part of the country. sent out a "May Day." Asked to describe the country beneath, he reported a Castle on a lake. This proved to be West Point on the Hudson River. Later, he tried to take off downwind—much shouting, arm waving, and running about! Eating ice-cold watermelon beneath the shade trees—with-Lorenz, Don Grout, and Norm Rosenstock, watching the air tows of gliders down the road a piece, has it all over trying to break records in the hot sun. For MAN at Work, E.J. put up a hammock. The darned thing collapsed. Sitting uneasily as this is written, MAN at W has his suspicions!

And there were some on the old Skyscraper list, lost in war or since gone peacefully. Since the modern hobby dates back to the Wrights—the Frenchman, Penaud, built a fine flying model in 1872, it is natural that all those who have passed on, but are always with us, could put together a great competitive team. Jim Saftig, who used to do Western Notes in this magazine, who was one of the truly great stunt men, just recently succumbed to injuries from a light-plane accident. And a few months ago, Art Heinrich, whose "53 Years of Modeling" appeared in MAN a few years ago. Art was a pioneer flier and a barnstormer of note before 1910. When twin pushers were king, he built the world's best and lightest—one and a fraction ounces.

And Hans Pfeil, an old time German modeler, respected throughout the world for a spirit that recognized no borders. In his very last letter, Hans commented of the model magazines, American and English, which were thoughtfully sent him: "What a constant, faithful gift—my only contact with modeldom and a monthly revoir with all my friends who formerly wrote but now are silent because I can't muster the strength to drop a line to everybody. So I have the constant pleasure of hearing what's going on, of seeing the latest developments, and feel my fingers itching like mad for the odd building iob... in view of this universal spirit of which Lindbergh said, 'If we fly, we all speak

Department of the book of the control of the contr

How Should You Choose An Engine?

In one word - CAREFULLY. Be sure it has time tested features as follows:

Short stroke "over-square" design for less friction.

Spherical combustion chamber, burns fuel faster and cleaner.

Cylinder head gasket "locked-in", cannot blow out.

Compression ratio 9 to 1 for greater efficiency.

Connecting rod of forged aluminum alloy, tough as steel, but light in weight.

Carburetor designed for high fuel lift to give certain fuel draw in all stunt or combat maneuvers.

Needle valve with "micro-fine" thread, which may be reversed if desired.

Piston of precision cast mechanite lapped to a perfect fit.

Baffle plate scientifically formed to direct the gas flow.

Crankshaft of alloy steel, counter-balanced, hardened, ground and polished, with a large, square port.

Cylinder of heat-treated steel, micro-honed to a perfect finish with large square ports for high volumetric efficiency and deep fins for good cooling.

Piston pin of hollow, hardened steel, precision ground. Retaining spring clips keep the pin in place, making pads unnecessary. Main bearing of aircraft quality, low friction, long-wearing bronze.

All of the above features, and others too numerous to mention, are found in the new, easy starting, powerful and speedy

FORSTER

There are eight FORSTER models to

29R	Air cooled			\$14.95
29RC	Speed Control			\$19.95
29RW	Water Jacket			
29RCW	Speed Control	&		
	Water Jacket			\$24.95
35R	Air cooled			\$14.95
35RC	Speed Control			
35RW	Water Jacket			
35RCW	Speed Control	&		
	Water Jacket			\$24.95

Beside all the above, you get up to \$5.00 trade-in allowance for your old engine at your Authorized FORSTER Dealer. Send coupon for free illustrated literature, and name & address of your nearest FORSTER Dealer.

Forster-Appelt Mfg. Co., Inc.

or at arounding severy	artification, the
Name	
Address	
City	
State	

MODELS OF THE MONTH by Berkeley

· Authentic Decals

- Full Size Berkeley Detailed
- . Die-Cut Balsa and Plywood
 - . Formed Wire Landing
 - · All Necessary Hard
 - Formed Plastic

STINSON SR-9

FOR .099 TO ..29 ENGINES - CONTROLINE

1" SCALE 42" WINGS AN

\$3.95 KIT No. 4-19

One of the "Great" private airplanes of all time.

Popular at a ery airper during the 1930's, it also found use as a lie son plane are Civil Air Patrols during World War II.

Sur as five place, powered by a 275 h.p.

8. Whiteey engine. Cruising speed is 140 m.p.h.

A truly beautiful free-flight or controline, this highly authentic and detailed scale replica is a must for every scale fan.

"SWEITZER"

\$2.95 KIT No. 4-18 1-30

120 TO .049 ENGINES FREE-FLIGHT

UP TO .099 ENGINES CONTROLINE)

1" SCALE 40" WINGSPAN

America's newest certified lightplane. Designed and built by the famous Swetzer Glider Co of Elmira, New York, it makes an ideal design for high performance scale model flying Perfect for the .020 size engise, very easily assembled - an exceptional flyer!

For the new PAA rules for both
Clipper Cargo and PAA-Load.
Can be flown as a so eight contest design
with an .020 engine yet it flies so easily
that it is an a cellent model
for beginners and for sport flying.

PAY LOAD - SPORT

PAY LOAD - SPORT

FOR .020 ENGINES 36" OR 48" WINGSPAN

\$1.95 KIT No. 18-3

BERKELEY MODELS INC.

if ne local dealer is convenient mail orders will be filled by Berkeley Model Supplies. Dept MA. West Hemostand N. Y. Please include 25: packing & postage





IT'S HERE

FORMULA

This fuel is a scientific blend of those high quality ingradients.

CASTOR OIL

first pressing, filtered

METHANOL

NITROMETHANE

PROPYLENE OXIDE

SYNTHETIC LUBRICANTS

You will find this fuel aspecially suited to the following meters:

FOX 09, 15 and 19

FOX COMBAT SPECIAL

MICOY 29 and 35

ORPEDO 19, 29 and 35

PRICES
Pints
95

\$169

\$ 5 50



...NOW:

the ULTRA of TODAY'S model fuels.

superlative quality . . . performance

MISSILE MIST

for high compression

gives you

MORE POWER - QUIC MARTING
COOL BURNING LESS SENSITIVITY
to mixtures and weather conditions GREATER ECONOMY

MISSILE MIST, the new liquid propellant, contains perfectly matched components. This was achieved by first testing, in comparative flight operations, nearly all model airplane fuels on the market as well as the favorite mixes of many well-known modelers. MISSILE MIST fills all the needs of the most demanding experts and is designed to give the finest performance with all medium and high compression motors . . . a truly premium fuel at a non-premium price.

premium price.
You will find MISSILE MIST superior in the world of model airplane fuels. Every can of MISSILE MIST is guaranteed to give you complete satisfaction.

TRY IT! Ask for it by name — the New Champion MISSILE MIST liquid propellant — at your Hobby Shop.

S A T I S F A C T I O N G U A R A N T E E D



CHAMPION PRODUCTS

FORT SMITH, ARKANSAS

HERE THEY ARE!

Eustemizing

AUTOMOTIVE COLORS

AUTOMOTIVE COLORS

for your individualized "show" models!

Special paint jobs are as essential to "customizing" your car kit as tail fins, chrome bumpers and wheel discs—and Pactra's new Customizing AUTOMOTIVE COLORS are ready for the job! Here is 'Name!—the kit builder's favorite paint—in special "custom" colors to match this season's popular makes. Pick your kit today and paint it with these Pactra authentic automotive colors:

104 per berte. 3 for 254

METALLIG FOR CUSTOMIZING CARS





METALLICS COLOR KIT 596

pactra

PACTRA CHEMICAL COMPANY, 1213 NORTH HIGHLAND AVENUE, LOS ANGELES 38, CALIF.

